

This military standard is mandatory for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

REVIEWER: GL, IS, MI, MC, NSA, SS  
(USER: AS, AT, CL, EL, MC, ME)

FED. SUP CLASS 5320																																																																																																																																																	
BODY DIAMETER D	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>NOM</th> <th>1/8</th> <th>3/16</th> <th>1/4</th> <th>5/16</th> <th>3/8</th> <th>7/16</th> </tr> <tr> <td>MAX</td> <td>.127</td> <td>.191</td> <td>.253</td> <td>.317</td> <td>.380</td> <td>.443</td> </tr> <tr> <td>MIN</td> <td>.121</td> <td>.182</td> <td>.244</td> <td>.305</td> <td>.365</td> <td>.428</td> </tr> </table>	NOM	1/8	3/16	1/4	5/16	3/8	7/16	MAX	.127	.191	.253	.317	.380	.443	MIN	.121	.182	.244	.305	.365	.428																																																																																																																											
NOM	1/8	3/16	1/4	5/16	3/8	7/16																																																																																																																																											
MAX	.127	.191	.253	.317	.380	.443																																																																																																																																											
MIN	.121	.182	.244	.305	.365	.428																																																																																																																																											
HEAD DIAMETER A	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>MAX</th> <td>.225</td> <td>.334</td> <td>.444</td> <td>.552</td> <td>.663</td> <td>.772</td> </tr> <tr> <th>MIN</th> <td>.205</td> <td>.308</td> <td>.414</td> <td>.518</td> <td>.625</td> <td>.728</td> </tr> </table>	MAX	.225	.334	.444	.552	.663	.772	MIN	.205	.308	.414	.518	.625	.728																																																																																																																																		
MAX	.225	.334	.444	.552	.663	.772																																																																																																																																											
MIN	.205	.308	.414	.518	.625	.728																																																																																																																																											
HEAD HEIGHT H	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>MAX</th> <td>.078</td> <td>.114</td> <td>.151</td> <td>.187</td> <td>.225</td> <td>.261</td> </tr> <tr> <th>MIN</th> <td>.066</td> <td>.100</td> <td>.135</td> <td>.169</td> <td>.205</td> <td>.239</td> </tr> </table>	MAX	.078	.114	.151	.187	.225	.261	MIN	.066	.100	.135	.169	.205	.239																																																																																																																																		
MAX	.078	.114	.151	.187	.225	.261																																																																																																																																											
MIN	.066	.100	.135	.169	.205	.239																																																																																																																																											
HEAD RADIUS	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>R1</th> <td>.039</td> <td>.059</td> <td>.079</td> <td>.098</td> <td>.118</td> <td>.137</td> </tr> <tr> <th>R2</th> <td>.106</td> <td>.159</td> <td>.213</td> <td>.266</td> <td>.319</td> <td>.372</td> </tr> <tr> <th>R3</th> <td>.429</td> <td>.641</td> <td>.858</td> <td>1.070</td> <td>1.286</td> <td>1.500</td> </tr> </table>	R1	.039	.059	.079	.098	.118	.137	R2	.106	.159	.213	.266	.319	.372	R3	.429	.641	.858	1.070	1.286	1.500																																																																																																																											
R1	.039	.059	.079	.098	.118	.137																																																																																																																																											
R2	.106	.159	.213	.266	.319	.372																																																																																																																																											
R3	.429	.641	.858	1.070	1.286	1.500																																																																																																																																											
LENGTH L	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>DASH NUMBER</th> <th>DASH NUMBER</th> <th>DASH NUMBER</th> <th>DASH NUMBER</th> <th>DASH NUMBER</th> <th>DASH NUMBER</th> </tr> <tr> <td>1/4 0.250</td> <td>1</td> <td>13</td> <td></td> <td></td> <td></td> </tr> <tr> <td>5/16 0.312</td> <td>2</td> <td>14</td> <td></td> <td></td> <td></td> </tr> <tr> <td>3/8 0.375</td> <td>3</td> <td>15</td> <td>34</td> <td></td> <td></td> </tr> <tr> <td>7/16 0.438</td> <td>4</td> <td>16</td> <td>35</td> <td></td> <td></td> </tr> <tr> <td>1/2 0.500</td> <td>5</td> <td>17</td> <td>36</td> <td></td> <td></td> </tr> <tr> <td>9/16 0.562</td> <td>6</td> <td>18</td> <td>37</td> <td></td> <td></td> </tr> <tr> <td>5/8 0.625</td> <td>7</td> <td>19</td> <td>38</td> <td>55</td> <td>72</td> </tr> <tr> <td>3/4 0.750</td> <td>8</td> <td>20</td> <td>39</td> <td>56</td> <td>73</td> </tr> <tr> <td>7/8 0.875</td> <td>9</td> <td>21</td> <td>40</td> <td>57</td> <td>74</td> </tr> <tr> <td>1 1.000</td> <td>10</td> <td>22</td> <td>41</td> <td>58</td> <td>75</td> </tr> <tr> <td>1 1/8 1.125</td> <td>11</td> <td>23</td> <td>42</td> <td>59</td> <td>76</td> </tr> <tr> <td>1 1/4 1.250</td> <td>12</td> <td>24</td> <td>43</td> <td>60</td> <td>77</td> </tr> <tr> <td>1 3/8 1.375</td> <td></td> <td>25</td> <td>44</td> <td>61</td> <td>78</td> </tr> <tr> <td>1 1/2 1.500</td> <td></td> <td>26</td> <td>45</td> <td>62</td> <td>79</td> </tr> <tr> <td>1 5/8 1.625</td> <td></td> <td>27</td> <td>46</td> <td>63</td> <td>80</td> </tr> <tr> <td>2 1/4 2.250</td> <td></td> <td>28</td> <td>47</td> <td>64</td> <td>81</td> </tr> <tr> <td>2 1/2 2.500</td> <td></td> <td>29</td> <td>48</td> <td>65</td> <td>82</td> </tr> <tr> <td>2 3/4 2.750</td> <td></td> <td>30</td> <td>49</td> <td>66</td> <td>83</td> </tr> <tr> <td></td> <td></td> <td>31</td> <td>50</td> <td>67</td> <td>84</td> </tr> <tr> <td></td> <td></td> <td>32</td> <td>51</td> <td>68</td> <td>85</td> </tr> <tr> <td>3 3.000</td> <td></td> <td>33</td> <td>52</td> <td>69</td> <td>86</td> </tr> <tr> <td>3 1/2 3.500</td> <td></td> <td></td> <td>53</td> <td>70</td> <td>87</td> </tr> <tr> <td>4 4.000</td> <td></td> <td></td> <td>54</td> <td>71</td> <td>88</td> </tr> </table>	DASH NUMBER	DASH NUMBER	DASH NUMBER	DASH NUMBER	DASH NUMBER	DASH NUMBER	1/4 0.250	1	13				5/16 0.312	2	14				3/8 0.375	3	15	34			7/16 0.438	4	16	35			1/2 0.500	5	17	36			9/16 0.562	6	18	37			5/8 0.625	7	19	38	55	72	3/4 0.750	8	20	39	56	73	7/8 0.875	9	21	40	57	74	1 1.000	10	22	41	58	75	1 1/8 1.125	11	23	42	59	76	1 1/4 1.250	12	24	43	60	77	1 3/8 1.375		25	44	61	78	1 1/2 1.500		26	45	62	79	1 5/8 1.625		27	46	63	80	2 1/4 2.250		28	47	64	81	2 1/2 2.500		29	48	65	82	2 3/4 2.750		30	49	66	83			31	50	67	84			32	51	68	85	3 3.000		33	52	69	86	3 1/2 3.500			53	70	87	4 4.000			54	71	88
DASH NUMBER	DASH NUMBER	DASH NUMBER	DASH NUMBER	DASH NUMBER	DASH NUMBER																																																																																																																																												
1/4 0.250	1	13																																																																																																																																															
5/16 0.312	2	14																																																																																																																																															
3/8 0.375	3	15	34																																																																																																																																														
7/16 0.438	4	16	35																																																																																																																																														
1/2 0.500	5	17	36																																																																																																																																														
9/16 0.562	6	18	37																																																																																																																																														
5/8 0.625	7	19	38	55	72																																																																																																																																												
3/4 0.750	8	20	39	56	73																																																																																																																																												
7/8 0.875	9	21	40	57	74																																																																																																																																												
1 1.000	10	22	41	58	75																																																																																																																																												
1 1/8 1.125	11	23	42	59	76																																																																																																																																												
1 1/4 1.250	12	24	43	60	77																																																																																																																																												
1 3/8 1.375		25	44	61	78																																																																																																																																												
1 1/2 1.500		26	45	62	79																																																																																																																																												
1 5/8 1.625		27	46	63	80																																																																																																																																												
2 1/4 2.250		28	47	64	81																																																																																																																																												
2 1/2 2.500		29	48	65	82																																																																																																																																												
2 3/4 2.750		30	49	66	83																																																																																																																																												
		31	50	67	84																																																																																																																																												
		32	51	68	85																																																																																																																																												
3 3.000		33	52	69	86																																																																																																																																												
3 1/2 3.500			53	70	87																																																																																																																																												
4 4.000			54	71	88																																																																																																																																												
<p><b>NOTES:</b></p> <ol style="list-style-type: none"> <li>1. <b>MATERIAL:</b> Steel, Carbon, per Fed. Std. No. 66, compositions 1005 thru 1022, any condition.</li> <li>2. <b>PROTECTIVE COATING:</b> Uncoated.</li> <li>3. <b>HARDNESS:</b> Maximum Rockwell hardness shall not exceed B60 as measured on side of shank.</li> <li>4. <b>DIMENSIONS:</b> All dimensions are in inches.</li> <li>5. <b>TOLERANCES:</b> Length L <math>\pm 0.016</math> in.</li> <li>6. <b>PART NUMBER:</b> The MS part number consists of the MS number, plus the dash number. Example: MS35743-1</li> <li>7. For design feature purposes, this standard takes precedence over procurement documents referenced herein.</li> <li>8. Referenced documents shall be of the issue in effect on date of invitations for bid.</li> </ol>																																																																																																																																																	
<b>P.A.</b> Other Code YD R2	<b>TITLE</b> RIVET, SOLID-SMALL, PAN HEAD, STEEL, ANNEALED	<b>MILITARY STANDARD</b> <b>MS35743</b>																																																																																																																																															
<b>PROCUREMENT SPECIFICATION</b> FF-R-556	<b>SUPERSEDES:</b>	<b>SHEET 1 OF 1</b>																																																																																																																																															