

FED. SUP CLASS
6350

REVIEWER: GL MD MI MR FS
USER: MO SM

PART NUMBER	PACKAGING
MS36434-1	5 gal pail
MS36434-2	55 gal drum

SAFETY
PRECAUTIONS: DANGER! HARMFUL OR FATAL IF SWALLOWED
WARNING! FLAMMABLE

If swallowed, do not induce vomiting. Avoid prolonged or repeated breathing of vapor. Use only with adequate ventilation. Avoid prolonged or repeated contact with skin. Avoid contact with eyes; in case of contact, flush with plenty of water for at least 15 minutes and get medical attention. The use of gloves and protective equipment is recommended.

INTENDED USE: For use in cleaning fuel oil tanks, lubricating oil tanks and machinery space bilges by emulsification of the oil.

MATERIAL: Single phase liquid.

REQUIREMENTS: Shall be an emulsifier or a mixture of emulsifiers and solvents, free from caustic soda, benzol and chlorinated compounds; readily miscible in a 3½ percent salt solution.

The flash point of the compound shall be not less than 150 degrees Fahrenheit, determined by the Pensky-Martens Closed Cup method.

NOTE: 1. Referenced documents shall be of the issue in effect on date of invitations for bid.

This has been approved by the MILITARY STANDARDIZATION Department of the Army and is mandatory for use by that activity. All other military activities are required to employ this standard where suitable.

APPROVED 12 March 1965 REVISED

P.A. MU	TITLE	MILITARY STANDARD
Other Cust	CLEANING COMPOUND, SOLVENT fuel tank and bilge	MS36434(MU)
Procurement Specification MIL-C-22230	SUPERSEDES:	SHEET OF 1 1