



REVIEW ACTIVITIES:
USER ACTIVITIES MI, YD, MC

DASH NO.	NOM. CAPACITY CU. FT.	OUTSIDE DIMENSIONS		F	CAP	DOT SPECIFICATION
		D	H			
-1	10	4 ± 1/2	12 ± 1			8 OR 8AL
-2	40	6 ± 1/2	19 ± 1-1/2			8 OR 8AL
-3	50	7 ± 3/4	22 ± 1-1/2			8 OR 8AL
-4	225	12 ± 1	29 ± 1		-2	8 OR 8AL

NOTES:

- ALL DIMENSIONS ARE IN INCH
 - FOOTRINGS, WHEN REQUIRED IN UPRIGHT POSITIONS, DRAINAGE HOLES, ETC.
 - THE MS PART NUMBER.
 - FOR DESIGN DEVELOPMENT DOCUMENT
 - REFERENCE FOR BID.
 - UNIT SHALL
 - FOR "
 - WHEN T
 - W.
 - SEAMS SHALL
- USED TO STABILIZE CYLINDERS
VENTILATION HOLES AND 2
- SHEET NUMBER PLUS THE DASH
- AND TAKES PRECEDENCE OVER PROCUREMENT
- ISSUE IN EFFECT ON DATE OF INVITATIONS
- CONCAVE BOTTOM HEAD SHALL BE ACCEPTABLE.
- FLANGING OF THE FOOTRING SHALL BE PERMITTED.
- CYLINDERS SHALL BE SUPPLIED WITH 3/8 - 18 NGT
PROVISION SHALL BE MADE FOR A SAFETY DEVICE
- SHALL NOT BE REQUIRED FOR 10 AND 40 CU. FT. CYLINDERS.
- DOT.

CANCELLED AFTER 31 MARCH 1975
USE MIL-C-3701 B

THIS MILITARY STANDARD IS MANDATORY FOR USE BY ALL DEPARTMENTS AND AGENCIES OF THE DEPARTMENT OF DEFENSE. SELECTION FOR ALL NEW ENGINEERING AND DESIGN APPLICATIONS AND FOR REPETITIVE USE SHALL BE MADE FROM THIS DOCUMENT.

(A) ENTIRE STANDARD REVISED

P.A. ARMY-ME Other Cust NAVY-SH A. F. -68	TITLE	MILITARY STANDARD
	CYLINDER, COMPRESSED GAS: DOT SPECIFICATION 8 OR 8AL FOR ACETYLENE	MS 39227
PROCUREMENT SPECIFICATIONS MIL-C-3701	SUPERSEDES:	SHEET OF

APPROVED 16 APRIL 1963 REVISED (A) 23 JANUARY 1969 (B) 31 MARCH 1975