



(a) DIMENSION P TO BE CONCENTRIC WITH DIMENSION Q
WITHIN 0.015 FULL INDICATOR READING

TABLE L DIMENSIONS FOR "B" COUPLINGS

TUBE DASH NO.	HOSE DASH NO.	HOSE I.D. (REF.)	NOMINAL THREAD SIZE	H	K MIN	L MAX	M MIN	N +0.030 -0.000	P +0.005 -0.000	Q MIN	C MAX	S MIN	J MIN
-5	-4	1/4	1/2-20	.625	0.19	.89	0.331	0.375	0.355	0.156	2.94	0.52	.50
-6	-6	3/8	9/16-18	.688	0.22	1.19	0.333	0.375	0.435	0.260	3.16	0.58	.56
-8	-8	1/2	3/4-16	.875	0.31	1.20	0.375	0.422	0.570	0.380	3.33	0.77	.75
-10	-8	1/2	7/8-14	1.000	0.31	1.20	0.461	0.500	0.680	0.380	3.38	0.89	.87
-12	-12	3/4	1-1/16-12	1.250	0.48	1.75	0.469	0.562	0.850	0.600	4.08	1.08	1.12

TABLE H
MAXIMUM WORKING PRESSURES C COUPLINGS

HOSE I.D. (REF)	1/4	3/8	1/2	3/4
PRESSURES	5,000		3,500	2,250

OVER-TIGHTENING TORQUE FOR SWIVEL NUT

DASH NO.	H.O.D. REF	TORQUE
-5	1/4	180 INCH POUNDS
-6	3/8	250 INCH POUNDS
-8	1/2	425 INCH POUNDS
-10	5/8	590 INCH POUNDS
-12	3/4	850 INCH POUNDS

(A) ENTIRE STANDARD REVISED

P.A. ARMY-ME Other Cust	TITLE COUPLING HOSE; FIELD ATTACHABLE (REUSEABLE), HYDRAULIC, SCREW-ON, PRESSURE TYPE, FEMALE SWIVEL, 37° FLARE, STRAIGHT, DOUBLE WIRE BRAID HOSE.	MILITARY STANDARD MS39290
PROCUREMENT SPECIFICATION MIL-C-52525	SUPERSEDES.	SHEET 1 OF 2

DD FORM 672-1

(Coordinated)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

U.S. GOVERNMENT PRINTING OFFICE: 1978-603-022/5299

REVIEW ACTIVITY:

USER ACTIVITY: MU, WC, SH, 82

THIS MILITARY STANDARD IS MANDATORY FOR USE BY ALL DEPARTMENTS AND AGENCIES OF THE
DEPARTMENT OF DEFENSE. SELECTION FOR ALL NEW ENGINEERING AND DESIGN APPLICATIONS
AND FOR REPEITIVE USE SHALL BE MADE FROM THIS DOCUMENT.

APPROVED 26 AUGUST 1966 REVISED (A) 28 December 1970 (B) 25 October 1978