

REVIEW ACTIVITIES: ARMY-ME; AF-84; DLA-GS  
USER ACTIVITIES: ARMY-EL

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable. AMSC - N/A  
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

FED. SUP CLASS 6220			
	<p>CONTOUR INDICATED BY PHANTOM LINES MAY VARY FROM THAT SHOWN TO SUIT MANUFACTURERS DESIGN</p> <p>6.0 DIA MIN AT BASE OF LENS</p> <p>0.30 R (MIN)</p> <p>SEE NOTE 10</p> <p>TOGGLE BOLT <math>\frac{1}{4} \times 5</math> 3 REQD</p> <p>10.00 SKIRT DIA 11.00</p> <p>5.00 6.00</p> <p>10.00 11.00</p> <p>5.13 MAX</p> <p>B</p> <p>B</p> <p>0.26 ± 0.01 DIA THRU 3 HOLES EQUALLY SPACED</p> <p>6.25 BC</p> <p>REDUCED VIEW B-B SHOWING TOGGLE BOLT HOLES IN BASE PLATE</p>		
<p>NOTES:</p> <ol style="list-style-type: none"> <li>1. TYPE AND CLASS SHALL BE AS SPECIFIED IN TABULATION IN ACCORDANCE WITH PROCUREMENT SPECIFICATION.</li> <li>2. DOME MUST BE REMOVEABLE FOR REPLACEMENT OF LAMPS.</li> <li>3. DIMENSIONS ARE IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES ARE <math>\pm .02</math> ON DECIMALS.</li> <li>4. FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN.</li> <li>5. THIS STANDARD IS NOT INTENDED TO LIMIT CONSTRUCTION TO FEATURES OTHER THAN AS SHOWN HEREON BY DIMENSIONS, NOTATIONS, AND REFERENCED DOCUMENTS.</li> <li>6. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.</li> <li>7. MARKING SHALL CONSIST OF THE MS PART NUMBER, VOLTAGE RATING AND MANUFACTURER'S IDENTIFICATION IN ACCORDANCE WITH MIL-STD-130.</li> <li>8. MECHANISM FOR ROTATING LAMPS SHALL BE SHIELDED TO PREVENT INTERFERENCE WITH WIRING.</li> <li>9. UNIT MOUNTING SKIRT OR MOUNTING HARDWARE SHALL NOT BE PART OF THE ELECTRICAL CIRCUIT.</li> <li>10. WIRES SHALL BE ROUTED THROUGH HOLE IN SKIRT.</li> <li>11. MINIMUM OF TWO SEALED BEAM LAMPS REQUIRED.</li> <li>12. LEAD-IN WIRES FOR ALL TYPE II (28 VOLT) LIGHTS SHALL BE MADE OF WIRE, M13486/1-3, AND SHALL TERMINATE WITH CONNECTORS MS27144-2 AND MS27142-3 (ONE EACH). WIRES SHALL EXTEND A MINIMUM OF 12 INCHES BELOW BASE OF SKIRT.</li> </ol>			
<p>(D) ENTIRE STANDARD REVISED</p>			
<p>P. A. ARMY-AT Other Cust AF - 99</p>	<p>INTERNATIONAL INTEREST</p>	<p>TITLE <b>LIGHT, WARNING, VEHICULAR, ROTATING, DC</b></p>	<p><b>MILITARY STANDARD</b> <b>MS51317</b></p>
<p>PROCUREMENT SPECIFICATION MIL-L-45325</p>		<p>SUPERSEDES:</p>	
<p>SHEET   OF  </p>		<p>6220-0336</p>	