



TABLE I. DIMENSIONS AND PART NUMBERS.

NOMINAL SIZE		.164	.190	.250
THREADS PER INCH		18	16	14
ØA - HEAD DIAMETER	MAX MIN	.322 .306	.373 .357	.492 .473
H - HEAD HEIGHT	MAX MIN	.115 .105	.133 .122	.175 .162
L - LENGTH	TOLERANCE	DASH NO	DASH NO	DASH NO
.750 1.500	+.031 +.047	1	2 3	4

REQUIREMENTS.

1. MATERIAL CARBON STEEL SHALL BE IN ACCORDANCE WITH ASTM A29-79 GRADE 1016 (UNS G10160), GRADE 1018 (UNS G10180), GRADE 1019 (UNS G10190), GRADE 1021 (UNS G10210), GRADE 1022 (UNS G10220) OR ASTM A29-79, GRADE 1024 (UNS G10240) IN ACCORDANCE WITH PROCUREMENT SPECIFICATION.
2. FINISH ZINC COATED IN ACCORDANCE WITH ASTM B633-78, Fe/Zn5 (5 µm), TYPE II.
3. THREADS THE THREADS SHALL BE IN ACCORDANCE WITH PROCUREMENT SPECIFICATION.
4. RECESS THE RECESS SHALL BE IN ACCORDANCE WITH MS9006.
5. PART NUMBERS THE BASIC MS PART NUMBER IS FOLLOWED BY A DASH NUMBER FROM TABLE I.

EXAMPLE: MS51486-1 - SCREW, TAPPING, THREAD FORMING, TYPE AB, PAN HEAD, CROSS-RECESSED, NOMINAL SIZE .164 LENGTH 1.500, ZINC COATED

NOTES

1. ALL DIMENSIONS ARE IN INCHES.
2. FOR APPROXIMATE HOLE SIZES SEE MS24632.
3. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BIDS OR REQUEST FOR PROPOSAL, EXCEPT THAT REFERENCED ADOPTED INDUSTRY DOCUMENTS SHALL GIVE THE DATE OF THE ISSUE ADOPTED.
4. FOR DESIGN FEATURE PURPOSES THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN.

PA	AR	INTERNATIONAL INTEREST	TITLE	MILITARY STANDARD
Other Cust	SH		SCREW, TAPPING, THREAD FORMING, TYPE AB, PAN HEAD, CROSS-RECESSED	MS51486
	99			
PROCUREMENT SPECIFICATION	SUPERSEDES		PAGE	OF
FF-S-107			1	1

USER ACTIVITIES
ARMY - ME, MI
NAVY - MC, OS

REVIEWER ACTIVITIES
ARMY - CR, EA
AIR FORCE - 82
DLA - IS
NSA - NS

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.