


REVIEWER: E.A.S.MI, NS, PA, WV
USER: ATEL GL, MC, ME, MUOS



FED. SUP CLASS
5305

TABLE I

NOMINAL SIZE		.086		.112		.138		.164		.190		.250	
THREADS PER INCH		32		24		20		18		16		14	
A HEAD DIA		MAX MIN		.167 .155		.219 .205		.270 .256		.322 .306		.373 .357	
H HEAD HEIGHT		MAX MIN		.062 .053		.080 .070		.097 .087		.115 .105		.133 .122	
		(A) DASH NUMBER											
L LENGTH	TOL	CARBON STEEL	CRES STEEL	CARBON STEEL	CRES STEEL	CARBON STEEL	CRES STEEL	CARBON STEEL	CRES STEEL	CARBON STEEL	CRES STEEL	CARBON STEEL	CRES STEEL
.188	1.031	1	1C										
.250		2	2C										
.312		3	3C	12	12C	22	22C						
.375		4	4C		13C		23C						
.500				14	14C	24	24C	34	34C	44	44C		
				15	15C	25	25C	35	35C	45	45C	65	65C
.625	1.047			16	16C	26	26C	36	36C	46	46C	66	66C
.750				17	17C	27	27C	37	37C	47	47C	67	67C
.875						28	28C	38	38C	48	48C	68	68C
1.000						29	29C	39	39C	49	49C	69	69C
									40	40C	50	50C	70
1.250	1.047							41	41C	51	51C	71	71C
1.500										52	52C	72	72C
1.750										53	53C	73	73C
2.000													
2.250													74
2.500												75	75C

NOTES:

- ① 1. **MATERIAL:** Carbon steel shall be AISI 1016, 1018, 1019, 1021, 1022 or 1024 (hardened) in accordance with Fed. Std. No. 66. Corrosion-resisting steel shall be AISI 410 (hardened) in accordance with Fed. Std. No. 66.
- ① 2. **PROTECTIVE COATING:** Carbon steel shall be cadmium plated in accordance with QQ-P-416, Type II, Class 3. Corrosion-resisting steel shall be passivated in accordance with QQ-P-35.
3. **THREADS:** The threads shall be in accordance with procurement specification.
4. **RECESS:** The recess shall be in accordance with MS9006.
5. **HOLE SIZES:** For approximate hole sizes see MS24632.
6. **DIMENSIONS:** All dimensions are in inches, unless otherwise specified.
7. **PART NUMBER:** The MS part number consists of the MS number, plus the dash number.
Example: MS51861-12
8. Referenced documents shall be of the issue in effect on date of invitations for bid.
9. For design feature purposes, this standard takes precedence over procurement documents referenced herein.
- ① 10. Supersedes AN530, MS24617, MS24618, MS24621, MS24622, MS24641, and MS24642; BCX3.1, BCX3.2, BCX5.1, BCX5.2, BQX3.1 and BQX5.1.

U.S. GOVERNMENT PRINTING OFFICE: 1981-703-023/4316

P.A. WC Other Cust YD 82	TITLE SCREW, TAPPING-THREAD FORMING, TYPE AB, PAN HEAD, CROSS-RECESSED	MILITARY STANDARD
PROCUREMENT SPECIFICATION FF-S-107	SUPERSEDES SEE NOTE 10	MS51861
		SHEET 1 OF 3

DD FORM 672-1 (Coordinated)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

APPROVED 27 AUG 1969 REVISED ① 15 MAY 1975

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

(A)

INTERCHANGEABILITY TABLES

FED SUP CLASS
5305

The screws covered by the following dash numbers of MS24637 and MS24638 are cancelled after 25 February 1963. The screws covered by the following dash numbers of MS24641, MS24642 and AN530 are cancelled after 15 August 1963. The screws covered by the following dash numbers of MS24617 and MS24618 are cancelled after 27 August 1969. The screws covered by the following dash numbers of MS24621 and MS24622 are cancelled after 15 May 1975. The cancelled screws cannot always replace the superseding screws and should be used until existing stock is depleted. Use only the superseding screws of MS51861 for design and engineering. Replacement shall be in accordance with these tables.

TABLE II

DASH NUMBERS						
CANCELLED					SUPERSEDING	
AN530	MS24617	MS24621	MS24637	MS24641	MS51861	
---	---	1	---	1	**	
2-3	2R3	2	---	2	1	
2-4	2R4	3	---	3	2	
---	---	4	---	4	3	
---	---	5	---	5	4	
---	---	7	---	10	**	
4-4	4R4	8	1	11	12	
---	---	9	---	12	**	
4-6	4R6	10	2	13	14	
4-8	4R8	11	3	14	15	
---	---	12	4	---	16	
---	---	14	5	---	17	
---	---	15	---	21	**	
6-4	6R4	16	10	22	22	
---	---	17	---	23	**	
6-6	6R6	18	11	24	24	
6-8	6R8	19	12	25	25	
6-10	6R10	20	13	26	26	
6-12	6R12	21	14	27	27	
6-14	6R14	22	15	---	28	
6-16	6R16	23	16	---	29	
6-20	6R20	24	---	---	**	
6-24	6R24	27	---	34	**	
---	---	28	---	35	**	
8-6	8R6	29	22	36	34	
8-8	8R8	30	23	37	35	
8-10	8R10	31	24	38	36	
8-12	8R12	32	25	39	37	
8-14	8R14	33	26	40	38	
8-16	8R16	34	27	41	39	
8-20	8R20	35	28	42	40	
8-24	8R24	36	29	---	41	
8-28	8R28	37	---	---	**	
8-32	8R32	38	---	---	**	
8-36	8R36	39	---	---	**	
8-40	8R40	40	---	---	**	
---	---	41	---	46	**	
---	---	42	---	47	**	
10-6	10R6	43	33	48	44	
10-8	10R8	44	34	49	45	
10-10	10R10	45	35	50	46	
10-12	10R12	46	36	51	47	
10-14	10R14	47	37	52	48	
10-16	10R16	48	38	53	49	
10-20	10R20	49	39	54	50	
10-24	10R24	50	40	55	51	
10-28	10R28	51	41	56	52	
10-32	10R32	52	42	57	53	
10-36	10R36	53	---	---	**	
10-40	10R40	---	---	---	**	
---	---	41	---	---	**	
---	---	42	45	---	**	
---	---	43	46	---	**	
---	---	44	47	---	**	
---	---	45	48	---	**	
---	---	46	49	---	**	
---	---	47	50	---	**	
---	---	48	51	---	**	
---	---	54	---	60	**	
---	---	55	56	61	65	
14-10	14R10	56	57	62	66	
14-12	14R12	57	58	63	67	
14-14	14R14	58	59	64	68	
14-16	14R16	59	60	65	69	
14-20	14R20	60	61	66	70	
14-24	14R24	61	62	67	71	
14-28	14R28	62	63	68	72	
14-32	14R32	63	64	69	73	
14-36	14R36	64	---	---	74	
14-40	14R40	65	---	---	75	

** NO REPLACEMENT

P.A. WC	TITLE	MILITARY STANDARD
Other Cust YD 82	SCREW, TAPPING-THREAD FORMING, TYPE AB, PAN HEAD, CROSS-RECESSED	MS51861
PROCUREMENT SPECIFICATION FF-S-107	SUPERSEDES SEE NOTE 10 PAGE 1	SHEET 2 OF 3

DD FORM 672-1 (Coordinated)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

REVIEWER EAJS, MI, NS, PA, WV
USER AT EL, GL, MC, ME, MU, OS

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

APPROVED 27 AUG 1969 REVISED (A) FOR CHANGES SEE SHEET 1

(A)
TABLE III

FED. SUP CLASS
5305

DASH NUMBERS						
CANCELLED					SUPERSEDING	
AN530	MS24618	MS24622	MS24638	MS24642	MS51861	
---	---	1	---	1	**	
C2-3	C2R3	1	2	2	1C	
C2-4	C2R4	2	3	3	2C	
---	---	3	4	4	3C	
---	---	4	5	5	4C	
---	---	7	---	10	**	
C4-4	C4R4	8	8	11	12C	
---	---	9	9	12	13C	
C4-6	C4R6	10	10	13	14C	
C4-8	C4R8	11	11	14	15C	
---	---	12	---	4	16C	
---	---	13	---	5	17C	
---	---	14	---	21	**	
C6-4	C6R4	16	15	22	22C	
---	---	17	16	23	23C	
C6-6	C6R6	18	17	24	24C	
C6-8	C6R8	19	18	25	25C	
C6-10	C6R10	20	19	26	26C	
C6-12	C6R12	21	20	27	27C	
C6-14	C6R14	22	21	15	28C	
C6-16	C6R16	23	22	16	29C	
C6-20	C6R20	---	23	---	**	
C6-24	C6R24	---	24	---	**	
---	---	27	---	34	**	
---	---	27	28	35	33C	
C8-6	C8R6	28	29	36	34C	
C8-8	C8R8	29	30	37	35C	
C8-10	C8R10	30	31	38	36C	
C8-12	C8R12	31	32	39	37C	
C8-14	C8R14	32	33	40	38C	
C8-16	C8R16	33	34	41	39C	
C8-20	C8R20	34	35	42	40C	
C8-24	C8R24	35	36	29	41C	
C8-28	C8R28	---	37	---	**	
C8-32	C8R32	---	38	---	**	
C8-36	C8R36	---	39	---	**	
C8-40	C8R40	---	40	---	**	
---	---	---	66	46	**	
---	---	41	---	47	**	
C10-6	C10R6	39	42	33	44C	
C10-8	C10R8	40	43	34	45C	
C10-10	C10R10	41	44	35	46C	
C10-12	C10R12	42	45	36	47C	
C10-14	C10R14	43	46	37	48C	
C10-16	C10R16	44	47	38	49C	
C10-20	C10R20	45	48	39	50C	
C10-24	C10R24	46	49	40	51C	
C10-28	C10R28	47	50	41	52C	
C10-32	C10R32	48	51	42	53C	
C10-36	C10R36	---	52	---	**	
C10-40	C10R40	---	53	---	**	
---	---	49	---	---	**	
---	---	50	---	45	**	
---	---	51	---	46	**	
---	---	52	---	47	**	
---	---	53	---	48	**	
---	---	54	---	49	**	
---	---	55	---	50	**	
---	---	56	---	51	**	
---	---	---	54	60	**	
---	---	58	55	56	61	
C14-10	C14R10	59	56	57	62	
C14-12	C14R12	60	57	58	63	
C14-14	C14R14	61	58	59	64	
C14-16	C14R16	62	59	60	65	
C14-20	C14R20	63	60	61	66	
C14-24	C14R24	64	61	62	67	
C14-28	C14R28	65	62	63	68	
C14-32	C14R32	66	63	64	69	
C14-36	C14R36	---	64	---	74C	
C14-40	C14R40	---	65	---	75C	

** NO REPLACEMENT

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

REVIEWER EA,IS,MI,NS,PA,WV
USER AT,EL,G,MC,ME,MJ,OS

APPROVED 27 AUG 1969 REVISED (A) FOR CHANGES SEE SHEET 1

P.A. WC Other Cust YD 82	TITLE SCREW, TAPPING-THREAD FORMING, TYPE AB, PAN HEAD, CROSS-RECESSED	MILITARY STANDARD
PROCUREMENT SPECIFICATION FF-S-107	SUPERSEDES: SEE NOTE 10 PAGE 1	MS51861
		SHEET 3 OF 3