


TABLE I. DASH NUMBERS.

DASH NO	A	TEMPER
001	.188	1/2 H
003	.250	1/2 H
005	.312	1/2 H

REQUIREMENTS:

- MATERIAL.** COPPER BASE ALLOY 360 (UNS C36000), AS SPECIFIED IN PROCUREMENT DOCUMENT.
- LENGTH.** STANDARD LENGTH OF HEXAGON WIRE IS 10 FEET MINIMUM, 12 FEET MAXIMUM.
- FORMING PROCESS.** COLD WORKED - CODE "C".
- PART NUMBER.** THE PART NUMBER CONSISTS OF THE BASIC MS NUMBER, PLUS A FORMING PROCESS CODE, PLUS A DASH NUMBER FROM TABLE I.

EXAMPLE: MS52003C001



- MARKING.** COPPER AND COPPER BASE ALLOYS SHALL BE MARKED IN ACCORDANCE WITH FED-STD-185 WITH THE EXCEPTION THAT A PART NUMBER FROM THIS MILITARY STANDARD SHALL BE INCLUDED AS PART OF THE IDENTIFICATION MARKING.

NOTES:

- ALL DIMENSIONS ARE IN INCHES.
- REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BIDS, OR REQUEST FOR PROPOSAL, EXCEPT THE REFERENCED ADOPTED INDUSTRY DOCUMENTS SHALL GIVE THE DATE OF THE ISSUE ADOPTED.
- FOR DESIGN FEATURE PURPOSES THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN.

USER ACTIVITIES:

REVIEWER ACTIVITIES:  
AIR FORCE - 84  
DLA - IS

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

REVISED  
APPROVED 25 OCT 84

P.A. MR	INTERNATIONAL INTEREST	TITLE WIRE, NONELECTRICAL, HEXAGON, COPPER BASE ALLOY 360	MILITARY STANDARD
Other Cust SH 99			MS52003
PROCUREMENT SPECIFICATION QQ-B-626	SUPERSEDES:		PAGE 1 OF 1