


TABLE I. DASH NUMBERS.

DASH NO	A	B	TEMPER
001	.125	.625	1/2 H
003	.129	12.000	1/2 H
005	.188	1.500	1/2 H
007	.250	.500	1/2 H
009	.250	1.250	1/2 H
011	.250	1.500	1/2 H
013	.250	3.000	1/2 H
015	.250	4.000	1/2 H
017	.258	12.000	1/2 H
019	.375	1.000	1/2 H
021	.750	12.000	1/2 H
023	1.000	2.000	1/2 H
025	1.000	12.000	1/2 H

## REQUIREMENTS:

1. **MATERIAL.** COPPER BASE ALLOY 268 (UNS C26800), AS SPECIFIED IN PROCUREMENT DOCUMENT.
2. **LENGTH.** STANDARD LENGTH OF FLAT BAR IS 10 FEET MINIMUM, 12 FEET MAXIMUM.
3. **FORMING PROCESS.** ROLLED - CODE "R".
4. **PART NUMBER.** THE PART NUMBER CONSISTS OF THE BASIC MS NUMBER, PLUS A FORMING PROCESS CODE, PLUS A DASH NUMBER FROM TABLE I.

EXAMPLE: MS52010R001



5. **MARKING.** COPPER AND COPPER BASE ALLOYS SHALL BE MARKED IN ACCORDANCE WITH FED-STD-185 WITH THE EXCEPTION THAT A PART NUMBER FROM THIS MILITARY STANDARD SHALL BE INCLUDED AS PART OF THE IDENTIFICATION MARKING.

## NOTES:

1. ALL DIMENSIONS ARE IN INCHES.
2. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BIDS, OR REQUEST FOR PROPOSAL, EXCEPT THE REFERENCED ADOPTED INDUSTRY DOCUMENTS SHALL GIVE THE DATE OF THE ISSUE ADOPTED.
3. FOR DESIGN FEATURE PURPOSES THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN.

REVISED  
APPROVED 25 OCT 84

P.A. Other Cust	MR SH 99	INTERNATIONAL INTEREST	TITLE  <b>BAR, METAL, FLAT, COPPER BASE ALLOY 268</b>	<b>MILITARY STANDARD</b>
PROCUREMENT SPECIFICATION QQ-B-613, QQ-B-626			SUPERSEDES:	<b>MS52010</b>
PAGE			OF	

36

USER ACTIVITIES:

REVIEWER ACTIVITIES:  
AIR FORCE-84  
DLA-IS

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.