



TABLE I. DASH NUMBERS.

DASH NO	A	B	C	TEMPER
001	.250	24	48	1/2 H
003	.312	24	48	1/2 H
005	.375	24	48	1/2 H
007	.500	24	48	1/2 H
009	.625	24	48	1/2 H
011	.750	24	48	1/2 H
013	1.000	24	24	1/2 H

REQUIREMENTS:

1. MATERIAL. COPPER BASE ALLOY 353 (UNS C35300), AS SPECIFIED IN PROCUREMENT DOCUMENT.
2. FORMING PROCESS. ROLLED - CODE "R".
3. PART NUMBER. THE PART NUMBER CONSISTS OF THE BASIC MS NUMBER, PLUS A FORMING PROCESS CODE, PLUS A DASH NUMBER FROM TABLE I.

EXAMPLE: MS52035R001

DASH NUMBER FROM TABLE I

ROLLED (SEE REQUIREMENT 2)

BASIC MS NUMBER

4. MARKING. COPPER AND COPPER BASE ALLOYS SHALL BE MARKED IN ACCORDANCE WITH FED-STD-185 WITH THE EXCEPTION THAT A PART NUMBER FROM THIS MILITARY STANDARD SHALL BE INCLUDED AS PART OF THE IDENTIFICATION MARKING.

NOTES:

1. ALL DIMENSIONS ARE IN INCHES.
2. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BIDS, OR REQUEST FOR PROPOSAL, EXCEPT THE REFERENCED ADOPTED INDUSTRY DOCUMENTS SHALL GIVE THE DATE OF THE ISSUE ADOPTED.
3. FOR DESIGN FEATURE PURPOSES THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN.

P.A.	MR	INTERNATIONAL INTEREST	TITLE	MILITARY STANDARD
Other Cust	SH		PLATE, METAL, COPPER BASE ALLOY 353	MS52035
	99			
PROCUREMENT SPECIFICATION	QQ-B-613	SUPERSEDES:		PAGE OF

USER ACTIVITIES:

REVIEWER ACTIVITIES:
AIR FORCE - 84
DLA - IS

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.