



TABLE I. DASH NUMBERS.

DASH NO	A	B	TEMPER	FINISH
001	.0010	6.000	1/2 HARD	REGULAR BRIGHT
003	.0015	6.000	1/2 HARD	REGULAR BRIGHT
005	.0020	6.000	1/2 HARD	REGULAR BRIGHT
007	.0030	6.000	1/2 HARD	REGULAR BRIGHT
009	.0050	6.000	1/2 HARD	REGULAR BRIGHT
011	.0060	6.000	1/2 HARD	REGULAR BRIGHT
013	.0070	6.000	1/2 HARD	REGULAR BRIGHT
015	.0100	6.000	1/2 HARD	REGULAR BRIGHT
017	.0110	6.000	1/2 HARD	REGULAR BRIGHT
019	.0140	6.000	1/2 HARD	REGULAR BRIGHT
021	.0160	6.000	1/2 HARD	REGULAR BRIGHT
023	.0180	6.000	1/2 HARD	REGULAR BRIGHT
025	.0190	6.000	1/2 HARD	REGULAR BRIGHT
027	.0312	.750	1/2 HARD	MATTE
029	.0625	.500	1/2 HARD	MATTE
031	.1250	.500	1/2 HARD	MATTE
033	.1250	.625	1/2 HARD	MATTE
035	.1250	1.000	1/2 HARD	MATTE
037	.1250	1.250	1/2 HARD	MATTE
039	.1250	1.375	1/2 HARD	MATTE
041	.1250	1.500	1/2 HARD	MATTE
043	.1250	1.750	1/2 HARD	MATTE
045	.1250	2.000	1/2 HARD	MATTE
047	.1250	3.000	1/2 HARD	MATTE
049	.1250	3.500	1/2 HARD	MATTE
051	.1250	6.000	1/2 HARD	MATTE
053	.1875	.500	1/2 HARD	MATTE
055	.1875	.625	1/2 HARD	MATTE
057	.1875	1.000	1/2 HARD	MATTE
059	.1875	4.000	1/2 HARD	MATTE

USER ACTIVITIES:

REVIEWER ACTIVITIES:  
AIR FORCE-84

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

P.A. Other Cust	MR AS 99	INTERNATIONAL INTEREST	TITLE <b>STRIP, METAL, LOW CARBON STEEL (1010) COLD ROLLED</b>	<b>MILITARY STANDARD MS52038</b>
PROCUREMENT SPECIFICATION <b>ASTM A109-83</b>		SUPERSEDES:		PAGE 1 OF 2

USER ACTIVITIES:

REVIEWER ACTIVITIES:  
AIR FORCE-84

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

FED SUP CLASS  
9515

## REQUIREMENTS:

1. MATERIAL. STEEL, CARBON, GRADE 1010 (UNS G10100) AS SPECIFIED IN ASTM A109-83.
2. LENGTH. STANDARD LENGTH OF STRIP IS 10 FEET MINIMUM 12 FEET MAXIMUM.
3. FORMING PROCESS. COLD ROLLED.
4. FINISH. AS SPECIFIED IN TABLE I.
5. TEMPER. AS SPECIFIED IN TABLE I.
6. PART NUMBER. THE PART NUMBER CONSISTS OF THE BASIC MS NUMBER, PLUS A DASH NUMBER FROM TABLE I.

EXAMPLE: MS52038-007

DASH NUMBER FROM TABLE I

BASIC MS NUMBER

7. MARKING. LOW CARBON STEEL SHALL BE MARKED IN ACCORDANCE WITH FED-STD-183 WITH THE EXCEPTION THAT A PART NUMBER FROM THIS MILITARY STANDARD SHALL BE INCLUDED AS PART OF THE IDENTIFICATION MARKING.

## NOTES:

1. ALL DIMENSIONS ARE IN INCHES.
2. ALL METAL STRIPS SHALL HAVE A NATURAL MILL EDGE.
3. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BIDS, OR REQUEST FOR PROPOSAL, EXCEPT THE REFERENCED ADOPTED INDUSTRY DOCUMENTS SHALL GIVE THE DATE OF THE ISSUE ADOPTED.
4. FOR DESIGN FEATURE PURPOSES THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN.

APPROVED 28 NOV 84  
REVISED

P.A. Other Cust	MR AS 99	INTERNATIONAL INTEREST	TITLE STRIP, METAL, LOW CARBON STEEL (1010) COLD ROLLED	MILITARY STANDARD MS52038
PROCUREMENT SPECIFICATION ASTM A109-83		SUPERSEDES:		PAGE 2 OF 2

DD FORM 672-1 (COORDINATED)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

9515-0466