

THIS MILITARY STANDARD HAS BEEN APPROVED BY THE DEPARTMENT OF DEFENSE AND IS MANDATORY FOR USE BY ALL DEPARTMENTS AND AGENCIES OF THE DEPARTMENT OF DEFENSE. SELECTION FOR ALL NEW ENGINEERING OR DESIGN APPLICATIONS AND FOR REPETITIVE USE SHALL BE MADE FROM THIS DOCUMENT.

FED. SUP CLASS
1670

SECTION A-A

MS PART NO.	CLOTH	TAPE	THREAD
MS 7009L-1	Cotton duck, type III, 12 oz. or less, color OD-7, MIL-C-419; val dyed, type I, class 1, color OD-7, CDC-D-950	Cotton, type III, 3/4 inch wide, color OD-7, MIL-T-5661	Nylon, type I or II, class 1, size E, color OD-1, V-T-295
MS 7009L-2	Nylon duck, type III, color OD 10C, MIL-C-7214	Nylon, type III, 3/4 inch wide, color OD-7, MIL-T-5661	Nylon type I or II, class 1, size E, color OD-1, V-T-295
MS 7009L-3	Nylon duck, type III, color Sage Green Shade No. 1535, MIL-C-7219	Nylon, type III, 3/4 inch wide, color Sage Green Shade No. 1535, MIL-T-5661	Nylon, type I or II, class 1, size E, color Sage Green Shade No. 1535, V-T-295

STITCHING: STITCH NOT LESS THAN 7 OR MORE THAN 9 STITCHES PER INCH, TYPE 301, FED-STD-751
 DIMENSIONS: DIMENSIONS IN INCHES.
 TOLERANCES: 1/16 INCH $\pm 1/32$
 MORE THAN 1/16 BUT LESS THAN 2 INCHES $\pm 1/16$
 MORE THAN 2 INCHES $\pm 1/8$

NOTES:
 1. DIP EXPOSED END OF COTTON TAPE APPROXIMATELY 1/4 INCH INTO A MELTED MIXTURE OF APPROXIMATELY 50% PARAFFIN AND 50% BEESWAX. TEMPERATURE OF MIXTURE 180°F $\pm 20^\circ$.
 2. SEAR EXPOSED END OF NYLON TAPE.
 3. FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN.
 4. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BIDS.

P.A. ARMY - CL Other Cmt NAVY-AS USAF - 11	TITLE POCKET, PARACHUTE PACK, LOG RECORD AND MANUAL	MILITARY STANDARD MS 70094
PROCUREMENT SPECIFICATION NONE	SUPERSEDES AN-570	SHEET 1 OF 1

APPROVED 1 FEB 1965 REVISED 2 4 JUNE 71

DD FORM 672-1 (Coordinate)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

M453