


ARMY-AV  
NAVY-MC  
USER ACTIVITIES:

USAF-82  
REVIEWER ACTIVITIES:

AMSC N/A  
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.  
This military standard is approved for use by all Departments and Agencies of the Department of Defense.  
Selection for all new engineering and design applications and for repetitive use shall be made from this document.

FED. SUP CLASS  
1670



## SNAP ASSEMBLY

MS PART NO.	DESCRIPTION
MS 70121-1	WITH EAR ON GUARD (AS SHOWN)
MS 70121-2	WITHOUT EAR ON GUARD

© REDRAWN; REVISED: "MS PART NO." IN TABLE, WAS "MS DASH NO.", NOTE 3.  
ADDED: SHEET 5.

P. A. ARMY-GL Other Cust NAVY-AS USAF-99	INTERNATIONAL INTEREST	TITLE SNAP, CONNECTOR - PARACHUTE CHEST TYPE PACK	MILITARY STANDARD MS 70121
PROCUREMENT SPECIFICATION MIL-H-7195	SUPERSEDES: MS 70121-1 SUPERSEDES USAF 47D3138 MS 70121-2 SUPERSEDES USAF 47D3138-1	SHEET 1 OF 5	

DD FORM 672-1 (COORDINATED)  
1 MAY 73

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE


PROJECT NO. 1670-0716

APPROVED  
REVISED  
30 APRIL 1986

ARMY-AV  
NAVY-MC  
USER ACTIVITIES

REVIEWER ACTIVITIES: USAF-82

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.



30 APRIL 1965


REVISED

APPROVED

USER ACTIVITIES: ARMY-AV  
NAVY-MC

REVIEWER ACTIVITIES: USAF-82


This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.



USER ACTIVITIES: ARMY-AV  
NAVY-MC

REVIEWER ACTIVITIES: USAF-82

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

FED. SUP CLASS  
1670

## NOTE:

WHEN GUARD WITH EAR IS REQUIRED FOR -1 ASSEMBLY, SILVER BRAZE EAR TO GUARD TO CLOSE ALL OPENINGS AROUND EDGES OF JOINT BETWEEN PARTS. USE SILVER BRAZING ALLOY IN ACCORDANCE WITH MIL-B-7883. PARTS MAY BE SPOT WELDED TO INSURE ALIGNMENT DURING BRAZING OPERATION.

## GUARD ASSEMBLY

(SHOWN WITH EAR)

## NOTES:

1. MATERIAL: HOOK - STEEL, MIL-S-5626; OPTIONAL - MIL-S-6049, MIL-S-6050.  
GUARD AND EAR - STEEL, QQ-S-698, TEMPER AND FINISH OPTIONAL.  
SPRINGS, SHORT AND LONG - STEEL, 1095 PER MIL-S-7947 OR CRES TYPE 301 OR 302.  
RIVET - CORROSION-RESISTANT STEEL, MS 20427F4-4.  
CORROSION-RESISTANT STEEL, MS 20613-SC12.  
CARBON STEEL, MS 20427-SC10.
2. HEAT TREATMENT: HOOK - HEAT TREAT TO 160,000 TO 180,000 LBS/SQ. IN. TENSILE STRENGTH PER MIL-H-6875.  
SPRINGS, SHORT AND LONG - HT 1095 TO SPRING TEMPER PER MIL-H-6875 AFTER FORMING PRETEMPER CRES PER AMS 5546.
3. FINISH: HOOK, GUARD ASSEMBLY - CADMIUM PLATE, QQ-P-416 CLASS 1, TYPE I OR IMMERSION ZINC FLAKE/CHROMATE DISPERSION COATING PER MIL-C-87115, CLASS 3.
4. SURFACE ROUGHNESS:  $\sqrt{125}$  MAX, IN ACCORDANCE WITH AMERICAN NATIONAL STANDARD, ANSI B46.1.
5. DIMENSIONS: DIMENSIONS IN INCHES UNLESS OTHERWISE SPECIFIED HEREIN.  
TOLERANCES: DECIMALS  $\pm .03$ , ANGLES  $\pm 2^\circ$ .
6. REMOVE ALL BURRS AND SHARP EDGES.
7. PROOFLOAD: SNAP ASSEMBLY SHALL BE SUBJECTED TO THE PROOFLOAD SPECIFIED AND INDICATED BY ARROWS IN ACCORDANCE WITH THE PROCUREMENT SPECIFICATION.
8. GUARD ASSEMBLY SHALL PASS A .359 DIA. ROUND INTO HOOK.
9. FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN.
10. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.

© REDRAWN, REVISED NOTE 3; REVISED NOTE 1.

P. A. ARMY-GL Other Cust NAVY-AS USAF-99	INTERNATIONAL INTEREST	TITLE SNAP, CONNECTOR, PARACHUTE CHEST TYPE PACK	MILITARY STANDARD MS 70121
PROCUREMENT SPECIFICATION MIL-H-7195	SUPERSEDES: -1 SUPERSEDES USAF 47D3138 -2 SUPERSEDES USAF 47D3138-1	SHEET 4 OF 5	

DD FORM 672-1 (COORDINATED)  
1 MAY 73

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

30 APRIL 1986  
REVISED ©  
APPROVED

FED. SUP CLASS



1670

# END ITEM EXAMINATION DIMENSION - FUNCTION TEST

ARMY-AV  
NAVY-MC  
USER ACTIVITIES:

USAF-82  
REVIEWER ACTIVITIES:

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.



CRITICAL DIMENSIONS: AS SHOWN

CRITICAL FUNCTIONAL TESTS: SNAP HOOK ASSEMBLY SHALL PASS FREELY OVER A .359 DIA. BAR.

© THIS SHEET ADDED.

P. A. ARMY-GL Other Cost NAVY-AS USAF-99	INTERNATIONAL INTEREST	TITLE SNAP, CONNECTOR, PARACHUTE CHEST TYPE PACK	MILITARY STANDARD	
			MS	70121
PROCUREMENT SPECIFICATION MIL-H-7195	SUPERSEDES:	-1 SUPERSEDES USAF 47D3138 -2 SUPERSEDES USAF 47D3138-1	SHEET	5 OF 5

DD FORM 672-1 (COORDINATED)  
1 MAY 73

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

REVISED 30 APRIL 1986

APPROVED