

INCH-POUND

MS75009H  
AMENDMENT 1  
7 July 2003

## DETAIL SPECIFICATION SHEET

## BRACKET ASSEMBLY, RESISTOR (POWER TYPE)

This amendment forms a part of MS75009H, dated 6 August 2001, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 5

TABLE; delete and substitute:

Pan head machine screw dash no. <u>1</u> /	Threaded rod dash no. <u>1</u> /	Dimensions		
		L <u>2</u> / (approx)		Screw thread
		Screw	Rod	
-18	-10	3.750	4.250	.164-32 UNC-2A (number 8)
-19	-11	4.760	5.250	
-20	-12	6.750	7.250	
-21	-13	8.750	9.250	.190-32 UNF-2A (number 10)
-22	-14	11.250	11.750	
-23	-15	12.750	13.250	

1/ The dash number added to the MS military-standard number constitutes the MS PIN; for example: MS75009-1.

2/ When assembled, not less than 1 1/2 threads nor more than 0.38 inch of thread shall extend beyond each nut.

Custodians:  
Army - CR  
Navy - EC  
Air Force - 11

Preparing activity:  
DLA - CC

Review activities:  
Army - AR  
Navy - AS, MC, OS

(Project 5905-1695)