

MILITARY SPECIFICATION SHEET

HEADSET - MICROPHONE,
H-172A AIC

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the headset-microphone described herein shall consist of this document and the latest issue of Military Specification MIL-H-83511.





FIGURE 1 Headset-microphone

MIL-H-83511'5

TABLE 1

Frequency in Hz	Response	Variation
300 - 500	4	± 1.2
500 - 2 000	4	4
2,000 - 4,500	0	4



NOTES

1. **ITEM IDENTIFICATION** The Headset-Microphone H-172A/AIC is a single earphone headset-microphone assembly with a transistorized microphone amplifier located in one earcup which is perforated to provide ambient listening. The assembly incorporates a quick-disconnect cord assembly. The quick disconnect provides a means to attach a switch and cord to the output connector for termination of the headset-microphone assembly.
2. **ATTACHMENT PROVISIONS** The earcup containing the earphone and the earcup containing the transistorized amplifier for the microphone shall be suspended by yokes from the headband, to allow quick adjustment and suitable pressure to the user.

FIGURE 2 Test circuit (microphone amp)




FIGURE 3 Wiring diagram (H-172A/AIC)

MIL-H-83511/5

REQUIREMENTS

Design and construction See figure 1.

Earphone 1 required, Roanwell Corp. P/N 10357 or equal.

General configuration In accordance with "1 H 3341"

Nominal diameter 2 inches (50.8 mm).

Depth 0.45 inch (11.4 mm).

Frequency response range 100 to 4,500 Hz.

Frequency response Maximum deviation from dB output ± 3 dB at 1,000 Hz and 600 ohms

Sensitivity The sensitivity of the earphone at ground level shall exhibit the following characteristics

<u>Frequency range</u>	<u>Decibels (reference level of 0.002 dynes/cm²)</u>
100 to 200 Hz	103 to 112
200 to 1,000 Hz	105 to 112
1,000 to 4,500 Hz	103 to 119

Harmonic distortion The harmonic distortion in the acoustic output of the earphone shall be no more than 5 percent over the audio frequency range of 300 to 3,500 Hz

Impedance 600 \pm 60 ohms at 1,000 Hz.

Microphone M-87/AIC, per MIL-M-26542

Cord data

Amplifier to terminal of main cord 16 inches (408.4 mm).

Terminal to U-384/U Main cord 10 inches (254.0 mm)

U-385/U to Switch 26 inches (660.4 mm).

Switch to connector 51 inches (1295.4 mm).

Specification MIL-C-55668 Type 2, 5 conductor tinsel rubber jacket.

Bar switch In accordance with MIL-H-83511.

Switch and housing

Type Bar actuated four position (to be supplied with clothing clip) Switch is interchangeable with bar switch used on H-182/PI Hdset/Mic Astrocom Electronics P/N 10235 or equal.

Belt (clothing) clip Roanwell Corp. P/N 20860 or equal.

Microphone amplifier Roanwell Corp. P/N 10374 or equal such as AM3578.

Output impedance Operates satisfactorily into input microphone circuit of Radio Control Unit C-1138/UR.

Frequency response 300 to 4,500 Hz.

Interchangeability This headset-microphone assembly is completely interchangeable with Navy type H-172/U headset-microphone assembly

Switch The output of the microphone shall be transferred to the output connector by means of a four position switch. The switch shall be made of polycarbonate (Lexan G.E. #101-701 or equal), and comply with specification L-P-303 It shall be watertight when assembled, and marked to show the four positions of the bar.

Contact sequence: The switch shall provide operation in the following sequence.

- a. Position "0" Switch not depressed OFF position.
- b. Position "1" Closed half-way, non-locking for "push-to-talk" telephone.
- c. Position "2" Closed half-way, pushed forward, for "lock-on" telephone.
- d. Position "3" Closed all the way, non-locking for radio.

Switch details: The switch mechanism shall be made as follows.

- a. Position "0" Without any pressure at all on the switch, the contact gap of 0.020 inch minimum.
- b. Positions "1 and 2". The open contact shall have a gap of 0.015 inch, minimum, the closed contact shall develop a pressure of 15 grams, minimum, and have a contact resistance not over 0.05 ohm.
- c. Position "3" Both contacts shall be closed, and the total pressure developed shall be 25 grams, minimum. The individual contact resistance shall not be over 0.05 ohm.
- d. Positions "1 and 2". The force required to maintain these positions when exerted on the flat part of the bar, at the beginning of the radius, shall be from one to one and one-half pounds.
- e. Position "3" The force required to maintain this position shall be from one to two and one-half pounds.
- f. Insulation resistance The insulation resistance, as measured with 500 volts, alternating current, rms, between any open contacts, terminals, or other metallic parts shall be less than 10 megohms.
- g. Life test The switch shall withstand 200,000 operating cycles

Clothes clip: The clothes clip shall be of the alligator design, and be provided with corrugated rubber jaws. The pressure developed at the tip when the jaws are parallel to each other shall be from three to four pounds.

Test for clothes clip pressure: The pressure developed between the tips of the jaws when parallel, shall be determined in any manner, and by any equipment, which is capable of effecting this measurement with no more than ten percent error.

Microphone transistorized amplifier

Operating temperature: The transistorized amplifier shall operate in temperatures between - 0 to +50 degrees centigrade.

Output impedance: The output impedance of the amplifier shall be such that it operates satisfactorily into the input microphone circuit of Radio Control Unit C-1138 A/UR or equivalent circuit (see test circuit).

Frequency response: The output of the microphone amplifier at 1,000 Hz when connected to the test circuit shall be 30 +5 dB above a zero reference level of one millivolt, the input shall be 28 dynes per square centimeter (103 dB relative to 0.0002 dynes/cm²) applied 1/4 inch from the microphone. A dip between 1,100 and 1,700 Hz not more than 150 Hz wide and not to exceed the lower limits by more than 7-1/2 dB is allowable.

- a. Response variates - After the environmental tests, the microphone amplifier shall not vary more than 4 dB from its initial response at any frequency between 300 and 4,500 Hertz

Intermodulation distortion: Intermodulation distortion tests shall be performed on the microphone amplifier using two tones at 700 and 1,000 Hz., each tone to be equal in sound pressure levels relative to 0.002 dynes/cm² at the output of the microphone amplifier the total harmonic and intermodulation products shall not be greater than 35 dB below the output level of the total test tones with an input sound pressure level of 103 dB and not greater than 32 dB below the level of the total output test tones with an input sound pressure of 110 dB.

- a. Distortion variation - After environmental tests the variations of harmonics and intermodulation products shall not be greater than 35 dB below the level of test tones with an input of 103 dB and 30 dB below the level of the other test tone inputs with an input of 106 dB

41 11 815175

Custodians

Army - EL

Navy - EC

Air Force - 85

Review activities

Army -

Navy -

Air Force - 99

DLA - ES

User activities

Army -

Navy - MC

Air Force -

Preparing activity

Air Force - 83

(Project 5965-0160-5)

FOLD

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE \$300

POSTAGE AND FEES PAID
DEPARTMENT OF AIR FORCE
DOD 318



WFLG/LOIE
WPAFB, OH 45433

FOLD

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER (Number) AND TITLE

MIL-H-83511/5 Headset, Microphone H-172A/AIC

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

AFLC/LOIE
WPAFB, OH 45433

☐ VENDOR ☐ USER ☐ MANUFACTURER

1 ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW

A GIVE PARAGRAPH NUMBER AND WORDING

B RECOMMENDED WORDING CHANGE

C REASON FOR RECOMMENDED CHANGE(S)

2 REMARKS

SUBMITTED BY (Printed or typed name and address — Optional)

TELEPHONE NO

DATE