



REVIEWER: CL, IS, ME, MI
USER: AT, AV

DASH NUMBER	SIZE	OUTSIDE DIMENSIONS (APPROX)	WEIGHT PER DOZEN (APPROX LBS)	(A) BREAKING LOAD MIN
(A) 21	3/16	1-1/4 x 3/4	3/8	2600
1	1/4	1-1/2 x 1	3/4	4500
2	5/16	1-11/16 x 1-3/16	1	6800
3	3/8	2-1/16 x 1-3/8	2	9300
4	7/16	2-3/8 x 1-1/2	3-1/8	12500
5	1/2	2-5/8 x 1-3/4	4-1/2	16500
6	9/16	3 x 1-15/16	6-5/8	20500
7	5/8	3-5/16 x 2-3/16	9	25000
(A) 8	11/16	3-1/2 x 2-5/16	11	29300
9	3/4	3-7/8 x 2-1/2	14-1/2	35400
10	7/8	4-1/2 x 2-15/16	20-1/4	48000
11	1	5 x 3-1/4	29	62000
12	1-1/8	5-5/8 x 3-1/2	40	78000
(A) 22	1-1/4	6-1/8 x 4	53-1/2	96000

(A) *CANCELLED IN PART after 5 December 1975. No other superseding standard. See RR-C-271 for superseding links.

NOTES:

- (A) 1. **MATERIAL:** Forged carbon steel in accordance with Grade C of RR-C-271.
- (A) 2. **PROTECTIVE COATING:** Zinc coating, hot-dip galvanised, in accordance with ASTM A153 or electro deposited in accordance with QQ-Z-325, type II, class 3.
3. **DIMENSIONS:** All dimensions are in inches unless otherwise specified.
4. **PART NUMBER:** The MS part number consists of the MS number plus the dash number.
Example: MS87008-1.
5. Referenced documents shall be of the issue in effect on date of invitations for bid.
6. For design feature purposes this standard takes precedence over procurement documents referenced herein.

APPROVED 1 JULY 63 REVISED (A) 5 DEC 75

P.A. Other Cast	4C -2 SH	TITLE LINK, CHAIN- CONNECTING OR REPAIR	MILITARY STANDARD MS87008
PROCUREMENT SPECIFICATION RR-C-271		SUPERSEDES: SDDY1	SHEET 1 OF 1