


## USER SYMBOLS:

## REVIEWER SYMBOLS:

AF - 99  
ARMY - ME

"Review/user information is current as of the date of this document.  
For future coordination of changes to this document, draft circulation  
should be based on the information in the current NODISS."

This military standard is approved for use by all Departments  
B. Agencies of the Department of Defense. Selection for all new  
engineering and design applications and for repetitive use shall  
be made from this document.



## -101 ASSEMBLY

(FOR NOTES SEE SHEET 8)

© DENOTES CHANGES

-2 SUB-ASSY (REF)  
(STRAP & COVER)-4 SUB-ASSY (REF)  
(FILLER CASE)

-28 (REF)

## SECTION B-B

(BOTH ENDS)

-2 SUB-ASSY

-4 SUB-ASSY  
(FILLER CASE)-3 SUB-ASSY  
(FILLER CASE)

## SECTION A-A

FED. SUP CLASS  
4240

P.A. NAVY - AS Other Cust AF - 99 ARMY - ME	INTERNAT- IONAL INTEREST *	TITLE  SLING SURVIVOR'S RESCUE	MILITARY STANDARD	
			MS90380	
PROCUREMENT SPECIFICATION MIL-R-8592	SUPERSEDES:  BUWEPS DWG 60A138H2		SHEET 1	OF 9

DD FORM 672-1 (Coordinated)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

PROJECT NO. 4240-0496  
\*PLATE NO. 1532

APPROVED 24 JUN 65 REVISED (B) 9 SEPT 77 (C) 15 DECEMBER 1980



FED. SUP CLASS  
4240




USER SYMBOLS:

REVIEWER SYMBOLS:

AF - 99  
ARMY - ME

"Review/user information is current as of the date of this document.  
For future coordination of changes to this document, draft circulation  
should be based on the information in the current DODISS."

This military standard is approved for use by all Departments  
B. Agencies of the Department of Defense. Selection for all new  
engineering and design applications and for repetitive use shall  
be made from this document.

-3 FILLER CASE SUB-ASSY-5 SUSPENSION STRAP SUB-ASSYSECTION J-J

MATERIAL: FOR -9 FIBROUS GLASS BATTING IAW MIL-B-2766.

FOR -10 COTTON MUSLIN CLOTH IAW CCC-C-446 TYPE I, CLASS I.

FOR -12 AND -27 NYLON WEBBING IAW MIL-W-4088, TYPE X AND TYPE XII RESPECTIVELY,  
NATURAL WHITE.

P. A. NAVY - AS Other Cust AF - 99 ARMY - ME	INTERNAT- IONAL INTEREST *	TITLE  SLING SURVIVOR'S RESCUE	MILITARY STANDARD  MS90380
PROCUREMENT SPECIFICATION MIL-R-8592	SUPERSEDES  BUWPS DWG 60A138H2	SHEET 3	OF 9



USER SYMBOL:

REVIEWER SYMBOLS:

AF - 99  
ARMY - ME

"Review/user information is current as of the date of this document.  
For future coordination of changes to this document, draft circulation  
should be based on the information in the current DD0133."


This military standard is approved for use by all Departments  
& Agencies of the Department of Defense. Selection for all new  
engineering and design applications and for repetitive use shall  
be made from this document.

P.A. NAVY - AS Other Cust AF - 99 ARMY - ME		INTERNATIONAL INTEREST *	TITLE  SLING SURVIVOR'S RESCUE	MILITARY STANDARD <b>MS90380</b>
PROCUREMENT SPECIFICATION MIL-R-8592		SUPERSEDES: BUWEPS DWG 60A138H2		SHEET 5 OF 9

DD FORM 672-1 (Coordinated)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

PLATE NO. 27065

FED. SUP CLASS  
4240


APPROVED 24 JUN 65 REVISED (B) FOR CHANGES SEE SHEETS 1 THRU 9 (C) SEE SHEETS 2 &amp; 9

This military standard is approved for use by all Departments & Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.


"Review/user information is current as of the date of this document. For future coordination of changes to this document, draft circulation should be based on the information in the current 000155."

REVIEWER SYMBOLS:  
AF - 99  
ARMY - ME


USER SYMBOLS:




SECTION M-M



SECTION L-L



SECTION P-P



SECTION N-N

MATERIAL: FOR -20 & -29 CLOTH CONFORMING TO MIL-C-10799, TYPE II, CL 3 (SEE NOTE 9).  
FOR -8 BINDING TAPE SEE SHEET 2  
FOR -28 TAPE CONFORMING TO MIL-T-5038, TYPE II (SIZE 1 x 17-1/4)

FED. SUP CLASS  
4240

P.A. NAVY - AS Other Cust AF - 99 ARMY - ME	INTERNAT- IONAL INTEREST *	TITLE  SLING SURVIVOR'S RESCUE	MILITARY STANDARD  MS90380
PROCUREMENT SPECIFICATION MIL-R-8592	SUPERSEDES:  BUWPS DWG 60A138H2	SHEET 6 OF 9	




USER SYMBOLS:

REVIEWER SYMBOLS:


AF - 99  
ARMY - ME

"Review/user information is current as of the date of this document.  
For future coordination of changes to this document, draft circulation  
should be based on the information in the current DODISS."

This military standard is approved for use by all Departments  
& Agencies of the Department of Defense. Selection for all new  
engineering and design applications and for repetitive use shall  
be made from this document.



MATERIAL: FOR -21 CLOTH CONFORMING TO MIL-C-10799, TYPE II, CLASS 3 (SEE NOTE 9)



MATERIAL: FOR -24 CLOTH CONFORMING TO MIL-C-10799, TY II, CL 3  
(SEE NOTE 9)

P.A. NAVY - AS Other Cust AF - 99 ARMY - ME	INTERNAT- IONAL INTEREST *	TITLE  SLING SURVIVOR'S RESCUE	MILITARY STANDARD  MS90380
PROCUREMENT SPECIFICATION MIL-R-8592	SUPERSEDES:  BUWEP DWG 60A138H2	SHEET 8 OF 9	



FED. SUP CLASS  
4240

## USER SYMBOLS:

## REVIEWER SYMBOLS:

AF - 99  
ARM - ME

"Review/user information is current as of the date of this document.  
For future coordination of changes to this document, draft circulation  
should be based on the information in the current DD155."

This military standard is mandatory for use by all Departments  
& Agencies of the Department of Defense. Selection for all new  
engineering and design applications and for repetitive use shall  
be made from this document.

## NOTES:

1. MATERIAL: SHALL BE AS SPECIFIED FOR APPLICABLE PART NO. EXCEPT -25 (THREAD) TO BE NYLON, V-T-295, CLASS 1, TYPE II, SIZE NO. 6 AND -26 (THREAD) TO BE NYLON V-T-295, CLASS 1, TYPE II SIZE NO. F (SEE NOTES 2, 3 AND 4.)
2. ALL STITCHING SHALL BE TYPE 301 AS DESCRIBED IN FED. STD 751, -25 TO BE 4 TO 6 STITCHES PER INCH (SEE NOTE1), -26 TO BE 6 TO 8 STITCHES PER INCH(SEE NOTE1).
3. OPTIONAL: THREAD SIZE NO. 5.
4. THREAD TO BE SAGE GREEN OR COLOR TO MATCH FABRIC.
5. DIMENSIONS IN INCHES, UNLESS OTHERWISE SPECIFIED. TOLERANCES: FRACTIONS 0 TO 1/2 INCL.  $\pm 1/32$ , OVER 1/2 TO 1 IN. INCL.  $\pm 1/16$ , OVER 1 IN. TO 5 IN. INCL.  $\pm 1/8$ , AND OVER 5 IN.  $\pm 1/4$ .
6. -22 and -23 SHALL CONFORM TO V-F-106, TYPE 1, STYLE 3, SIZE MH, SHORT TAB PULL, LENGTH AS REQUIRED (SEE SHEET 7). METAL PARTS TO BE CHROME ALLOY STAINLESS STEEL OR BRASS, AND TAPE TO BE WATER REPELLANT AND MILDEW RESISTANT, COLOR SAGE GREEN, NO. 1519.
7. SEAR ENDS OF STRAPS TO PREVENT FRAYING, AVOID FORMING SHARP EDGES.
8. ALL EXPOSED ENDS OF STITCHING SHALL BE BACKSTITCHED NOT LESS THAN 1/2 INCH. THREAD BREAKS SHALL BE STITCHED BACK OF BREAK A MINIMUM OF 1/2 INCH.
9. -19, -20, -21, -24 SHALL BE COLOR YELLOW, COLOR NO. 33538 OF FED STD 595.
10. ENDS OF -15 AND -16 SHALL BE COLOR BRIGHT RED, COLOR NO. 11105 OF FED STD 595.
11. SLING SHALL BE MANUFACTURED IN ACCORDANCE WITH MIL-R-8592/3.

- \* CERTAIN PROVISIONS OF THIS STANDARD ARE THE SUBJECT OF INTERNATIONAL STANDARDIZATION AGREEMENT ASCC AIR STD 51/1 "THE USE OF HORSE COLLAR (STROP) TYPE HELICOPTER HOISTING GEAR" AND STANAG 3295 "HORSE COLLAR (STROP) TYPE HELICOPTER HOISTING GEAR." WHEN REVISION, OR CANCELLATION OF THIS STANDARD IS PROPOSED WHICH WILL EFFECT OR VIOLATE THE INTERNATIONAL AGREEMENT CONCERNED, THE PREPARING ACTIVITY WILL TAKE APPROPRIATE RECONCILIATION ACTION THROUGH INTERNATIONAL STANDARDIZATION CHANNELS, INCLUDING DEPARTMENTAL STANDARDIZATION OFFICES, IF REQUIRED.

FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER  
PROCUREMENT DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL  
BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.

P.A. NAVY - AS Other Cust AF - 99 ARMY - ME	TITLE SLING SURVIVOR'S RESCUE	MILITARY STANDARD MS90380
PROCUREMENT SPECIFICATION MIL-R-8592	SUPERSEDES: BUWEPs DWG 60A138H2	SHEET 9 OF 9

DD FORM 1 SEP 71 672-1 (Coordinated)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

PLATE NO. 17709

APPROVED 24 JAN 65 REVISED FOR C.A. 'ES SEE SHEETS 1 THRU 9 FOR C.A. 'ES SEE SHEET 2 &amp; 9

