


NOTICE - REVIEW/USER INFORMATION IS CURRENT AS OF DATE OF THIS DOCUMENT. FOR FUTURE COORDINATION OF CHANGES TO THIS DOCUMENT, BIDDING CIRCULATION SHOULD BE BASED ON THE INFORMATION IN THE CURRENT EDITION.

USER INTEREST:
ARMY - AV
NAVY - AS, CG, MC
AF - 17

REVIEW INTEREST:
ARMY - MJ, EL, M1
NAVY - AS, BH
AF - 11, 85

This military standard is approved by the Department of Defense and is mandatory for use by all Departments & Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.



MS90402-2
(4 REQ'D)

SEE TABLE I AND II

MS35337-78
(4 REQ'D)

TABLE I - CLAMPING DISC					
DASH NO.	B DIA +.0008 -.0000	C DIA	"D" OD +.000 -.003	E	F RADIUS
-1	.6250	.812	1.156	.412	.277
-2	.8750	1.100	1.531	.569	.461
-3	.9375	1.250	1.844	.659	.959

NOTES:

1. MATERIAL: CLAMPING DISC -1, -2 AND -3; STEEL, CORROSION RESISTING, QQ-S-766, CLASS 410, CONDITION A. (COLD FINISH).
2. FINISH: CLAMPING DISC -1, -2 AND -3; PASSIVATE IN ACCORDANCE WITH QQ-P-35, TYPE II OR III.
3. HEAT TREATMENT: HEAT 1800° - 1825° F, QUENCH IN OIL, DRAW TO ROCKWELL C 30 - 35 APPROX. DRAW TEMP 950° F.
4. REMOVE ALL BURRS AND BREAK ALL SHARP EDGES.
5. DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED TOLERANCES: DECIMALS ±.005. INTERPRET DIMENSIONING AND TOLERANCING IN ACCORDANCE WITH MIL-STD-8.
6. EACH CLAMPING DISC ASSEMBLY SHALL INCLUDE MS90402-2 (4 REQUIRED) AND MS35337-78 (4 REQUIRED).

FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.

P.A. NAVY - AS Other Cont ARMY - MJ NAVY - AS AF - 11	TITLE CLAMPING DISC ASSEMBLY	MILITARY STANDARD MS90400
PROCUREMENT SPECIFICATION NOTE	SUPERSEDES: BUORD 677030, 677031, 677032, 854459, 854460, 854461.	SHEET 1 OF 2

DD FORM 672-1 (Coordinated)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE. W68

PLATE NO. 15120

APPROVED 6 JUNE 1967 REVISED

NOTICE - REVIEW/USER INFORMATION IS CURRENT AS OF DATE OF THIS DOCUMENT. FOR FUTURE COORDINATION OF CHANGES TO THIS DOCUMENT, DRAFT CIRCULATION SHOULD BE BASED ON THE INFORMATION IN THE CURRENT EDITIONS.

USAR INTEREST:
ARMY - AV
NAVY - AS, CG, MC
AF - 17

REVIEWER INTEREST:
ARMY - MJ, EL, MI
NAVY - AS, SE
AF - 11, 85

This military standard is approved by the Department of Defense and is mandatory for use by all Departments & Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.




TABLE II - GEAR DATA

DATA	DARK NO.		
	-1	-2	-3
TOOTH FORM	FULL DEPTH THIN INVOLUTE	FULL DEPTH THIN INVOLUTE	FULL DEPTH THIN INVOLUTE
PRESSURE ANGLE	20°	20°	20°
NO. OF TEETH	72	96	116
DIAMETRAL PITCH	64	64	64
PITCH DIA (DATUM)	1.125	1.500	1.813
ROOT DIA (MAX)	1.096	1.456	1.771
BACKLASH	+.0015 -.0010	+.0015 -.0010	+.0015 -.0010

APPROVED 6 JUNE 1967 REVISED

P.A. NAVY - AS

Other Cast
ARMY - MJ
NAVY - AS
AF - 11

PROCUREMENT SPECIFICATION
FOR

TITLE

CLAMPING DISC ASSEMBLY

SUPERSEDES:
BORD 677030, 677031, 677032, 854459, 854460, 854461

MILITARY STANDARD

MS90400

SHEET 2

DD FORM 672-1 (Coordinated)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE. W68

PLATE NO. 15320