


FED SUP CLASS
5950

RATINGS

Style	LT10
Grade	1
Class	A
Temperature rise	15°C
Ambient temperature	90°C
Operating temperature	-55° to +105°C
Dielectric withstanding	700 volts rms for a minimum of 60 sec
Voltage (sea level)	
Dielectric withstanding	180 volts rms for a minimum of 60 sec
Voltage (reduced barometric pressure)	
Terminal pull	5 pounds
Altitude	70,000 feet
Weight	1.5 grams max (A)

LT

Dimensions in inches with metric equivalents (mm) in parentheses.

	Minimum	Maximum
A	205 (5.21)	.225 (5.72)
B	550 (13.97)	.570 (14.48)
C	1.250 (31.75)	1.625 (41.28)
D	.026 (.66)	.030 (.76)

ELECTRICAL CHARACTERISTICS (INITIAL)

Dash no 1/	Type designation	Inductance $\pm 5\%$	Q min	Test frequency	Self-resonant frequency, min	DC resistance maximum	Rated DC Current
		μH		MHz	MHz	ohms	mA
-01	LT10K037	1100	60	25	2.8	21.0	78
-02	LT10K038	1200	60	25	2.7	22.0	76
03	LT10K039	1300	60	25	2.6	23.0	75
-04	LT10K040	1500	65	25	2.4	25.0	72
-05	LT10K041	1600	65	25	2.3	26.0	70
-06	LT10K042	1800	65	25	2.2	28.0	68
-07	LT10K043	2000	65	25	2.1	29.0	67
-08	LT10K044	2200	70	25	2.0	30.0	66
-09	LT10K045	2400	70	25	1.9	31.0	64
-10	LT10K046	2700	70	25	1.8	33.0	62
-11	LT10K047	3000	70	25	1.7	35.0	61
-12	LT10K048	3300	70	25	1.6	38.0	58
-13	LT10K049	3600	70	25	1.5	40.0	57

1/ The dash number added to the MS military standard number constitutes the MS part number, example, MS90540-01. (A) denotes changes

P A ARMY-EL Other Cust AF-80 NAVY-EC	International Interest	TITLE (A) COILS, RADIO FREQUENCY, MOLDED, FIXED, SUBMINIATURE (IRON CORE) TYPES LT10K037 TO LT10K049 INCL	MILITARY STANDARD		
			MS90540		
Procurement Specification MIL-C-15305		SUPERSEDES	PAGE	1	OF 2

DD FORM 672 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

5950-0454-3

This military standard is mandatory for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

Reviewer activities: Army MI, SL
Navy
Air Force 11, 17, 80
DSA-ES

User activities: Army WC, SL, MU
Navy AS, MC, SH, OS
Air Force 19

APPROVED 15 Jun 65 REVISED (A) 1 Jun 73

P A Army-EL Other Cust AF-80 Navy-EC	International Interest	TITLE COILS, RADIO FREQUENCY, MOLDED, FIXED, SUBMINIATURE (IRON CORE) TYPES LT10K037 TO LT10K049 INCL	MILITARY STANDARD
			MS90540
Procurement Specification MIL-C-15306		SUPERSEDES	PAGE 2 OF 2

SPECIFICATION ANALYSIS SHEET		Form Approved Budget Bureau No 22-R255
<p>INSTRUCTIONS This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.</p>		
<p>SPECIFICATION M390540 COILS, RADIO FREQUENCY, MOLDED, FIXED, SUBMINIATURE (IRON CORE) TYPES LT10K037 TO LT10F046 INCL</p>		
<p>ORGANIZATION</p>		
<p>CITY AND STATE</p>		<p>CONTRACT NUMBER</p>
<p>MATERIAL PROCURED UNDER A</p> <p><input type="checkbox"/> DIRECT GOVERNMENT CONTRACT <input type="checkbox"/> SUBCONTRACT</p>		
<p>1 HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?</p> <p>A GIVE PARAGRAPH NUMBER AND WORDING</p>		
<p>B RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES</p>		
<p>2 COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID</p>		
<p>3 IS THE SPECIFICATION RESTRICTIVE?</p> <p><input type="checkbox"/> YES <input type="checkbox"/> NO (If "yes", in what way?)</p>		
<p>4 REMARKS (Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)</p>		
<p>SUBMITTED BY (Printed or typed name and activity - Optional)</p>		<p>DATE</p>

To detach this form, cut along this line

DD FORM 1426
1 JAN 66

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED

ESC-FM 1068-68

FOLD

Department of the Army
Headquarters
U.S. Army Electronics Command
Fort Monmouth, New Jersey 07703

POSTAGE AND FEES PAID

OFFICIAL BUSINESS

Commanding General
U.S. Army Electronics Command
ATTN: AMSEL-RD-WD
Fort Monmouth, New Jersey 07703

To detach this form, cut along this line

FOLD