


FED. SUP CLASS  
5315



DASH NO.	LENGTH	DIAMETER	NO. PER LB. (APPROX)
-1	1	.162	150
-2	1 1/2	.1205	190
-3	2	.162	79
-4	3	.162	54

1. Foundry nails shall be diamond point, large flat thin head, smooth shank, bright steel wire nails.
2. Dimensions are in inches.
3. For design feature purposes, this standard takes precedence over procurement documents referenced herein.
4. Referenced documents shall be of the issue in effect on date of invitation for bid.
5. The MS part number consists of the MS number plus the dash number.

NOTICE—When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility, nor any obligation whatsoever, and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

This military standard is approved by the Department of Defense and is mandatory on all activities. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

APPROVED 18 DEC 1962 REVISED

P.A. DOCKS	TITLE	MILITARY STANDARD
Other Cust GE MOA	NAILS, FOUNDRY	MS 90716
Procurement Specification	SUPERSEDES:	SHEET 1 OF 1