



TABLE 1 DASH NUMBERS AND DIMENSIONS

TACK, CUT							
DASH NUMBER			COMM. DES.	ØA	ØH (APPROX.)	L ± 1/32	NO./LB (APPROX.)
STEEL BLUED	STEEL ZINC COATED	COPPER					
1			2	046	156	1/4	7390
2		13	3	049	171	3/8	2286 ^{1/2} 2820 ^{1/2}
3			4	054	187	7/16	1732
4	9	14	6	058	187	1/2	1588 ^{1/2} 1760 ^{2/3} 1570 ^{3/4}
5			8	062	218	9/16	1400
6	10	15	10	064	250	5/8	1178 ^{1/2} 1200 ^{2/3} 1010 ^{3/4}
7	11	16	14	069	281	3/4	901 ^{1/2} 800 ^{2/3} 720 ^{3/4}
8	12	17	18	078	281	7/8	665 ^{1/2} 640 ^{2/3} 560 ^{3/4}
		18	22	083	.312	1	430

- 1/ STEEL, BLUED
2/ STEEL, ZINC COATED
3/ COPPER

Ⓐ ENTIRE STANDARD REVISED

P A ARMY - AR Other Cost NAVY - YD AIR FORCE-99	INTERNATIONAL INTEREST	TITLE TACK, CUT	MILITARY STANDARD	
			MS90722	
PROCUREMENT SPECIFICATION FF-T-1813		SUPERSEDES	PAGE 1	OF 2

DISTRIBUTION STATEMENT A Approved for public release, distribution is unlimited.
This military standard is approved for use by all Departments and Agencies of the Department of Defense.
No restriction for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

AMSC N/A

DD FORM 1, 672-1 (COORDINATED)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

5315 - 0429

APPROVED 18 DEC 62
REVISED Ⓐ 25 JAN 88

REVIEWER ACTIVITIES: CIVIL, AMERICAN COMMUNITY ACTIVITIES
ARMY-CE, ME GSA - FSS
NAVY-SA
AIR FORCE -82

USER ACTIVITIES
ARMY-AM, MI
NAVY-AS, MC, SH

REVIEWER ACTIVITIES
 ARMY-CE, ME
 NAVY-SA
 AIR FORCE-82

This military standard is approved for use by all Departments and Agencies of the Department of Defense
 Selection for all new engineering and design applications and for repetitive use shall be made from this
 document when applicable

USER ACTIVITIES
 ARMY-AI, MI
 NAVY-AS, MC, SH

		FED SUP CLASS 5315	
<p>REQUIREMENTS:</p> <ol style="list-style-type: none"> 1. <u>MATERIAL</u> CUT TACK SHALL BE MANUFACTURED FROM STEEL OR COPPER IN ACCORDANCE WITH PROCUREMENT SPECIFICATION 2. <u>CHARACTERISTICS</u> CUT TACK SHALL HAVE FLAT HEAD AND SIDE POINT, IN ACCORDANCE WITH PROCUREMENT SPECIFICATION 3. <u>PROTECTIVE COATING AND SURFACE TREATMENT</u> CUT TACK SHALL BE BLUED IN ACCORDANCE WITH PROCUREMENT SPECIFICATION OR ZINC COATED IN ACCORDANCE WITH ASTM B633, TYPE 11, CLASS FE/ZNL3, LUSTER BRIGHT 4. <u>PART NUMBER</u> THE PART NUMBER SHALL CONSIST OF THE BASIC MS NUMBER FOLLOWED BY A DASH NUMBER FROM TABLE 1 <p>EXAMPLE MS90722-10</p> <p>└── DASH NUMBER</p> <p>└── BASIC MS NUMBER</p> <p>MS90722-10 INDICATES- TACK, COMM. DES 10, 5/8 LONG, STEEL, ZINC COATED</p> <p>NOTES</p> <ol style="list-style-type: none"> 1. ALL DIMENSIONS ARE IN INCHES 2. IN THE EVENT OF CONFLICT BETWEEN THE TEXT OF THIS STANDARD AND THE REFERENCES CITED HEREIN, THE TEXT OF THIS STANDARD SHALL TAKE PRECEDENCE 3. REFERENCED GOVERNMENT (OR NON-GOVERNMENT) DOCUMENTS OF THE ISSUE LISTED IN THAT ISSUE OF THE DEPARTMENT OF DEFENSE INDEX OF SPECIFICATIONS AND STANDARDS (DODISS) SPECIFIED IN THE SOLICITATION FORM A PART OF THIS STANDARD TO THE EXTENT SPECIFIED HEREIN 			
PA ARMY-AR Other Cost NAVY-YD AIR FORCE-99	INTERNATIONAL INTEREST	TITLE TACK, CUT	MILITARY STANDARD MS90722
PROCUREMENT SPECIFICATION FF-T-1813	SUPSEDES	PAGE 2 OF 2	