

INCH-POUND

MS9198D
w/AMENDMENT 1
17 May 2011


SUPERSEDING
MS9198D
12 February 2010

DETAIL SPECIFICATION SHEET

NUT, TUBE COUPLING-CRES SAE-AMS5646

This specification is approved for use by all Departments and Agencies
of the Department of Defense .

The requirements for acquiring the product described herein shall consist of this specification sheet.



Inches	mm
.005	0.13
.010	0.25
.015	0.38

FIGURE 1. Nut, tube coupling.

MS9198D
w/AMENDMENT 1

Dash number	Tube OD inches (mm)	Thread T SAE-AS8879	A diameter inches (mm) +.003 (0.08) -.000	B inches (mm) ±.015 (0.38)	C diameter inches (mm) ±.005 (0.13)
-02	.125 (3.18)	.3125 - 24UNJF -3B	.180 (4.57)	.435 (11.05)	.425 (10.80)
-03	.188 (4.78)	.3750 - 24UNJF -3B	.242 (6.15)	.452 (11.48)	.490 (12.45)
-04	.250 (6.35)	.4375 - 20UNJF -3B	.305 (7.75)	.467 (11.86)	.550 (13.97)
-05	.313 (7.95)	.5000 - 20UNJF -3B	.374 (9.50)	.440 (11.18)	.615 (15.62)
-06	.375 (9.53)	.5625 - 18UNJF - 3B	.440 (11.18)	.467 (11.86)	.678 (17.22)
-07	.438 (11.13)	.6250 - 18UNJF -3B	.502 (12.75)	.493 (12.52)	.740 (18.80)
-08	.500 (12.70)	.7500 - 16UNJF - 3B	.570 (14.48)	.493 (12.52)	.865 (21.97)
-09	.562 (14.27)	.8125 - 16UNJ - 3B	.634 (16.10)	.493 (12.52)	.927 (23.55)
-10	.625 (15.88)	.8750 - 14UNJF - 3B	.698 (17.73)	.617 (15.67)	.990 (25.15)
-11	.688 (17.48)	1.000 - 12UNJF - 3B	.770 (19.56)	.588 (14.94)	1.115 (28.32)
-12	.750 (19.05)	1.0625 - 12UNJ - 3B	.834 (21.18)	.588 (14.94)	1.180 (29.97)
-14	.875 (22.23)	1.1875 - 12UNJ - 3B	.961 (24.41)	.615 (15.62)	1.320 (33.53)
-16	1.000 (25.40)	1.3125 - 12UNJ - 3B	1.089 (27.66)	.652 (16.56)	1.433 (36.40)
-18	1.125 (28.58)	1.500 - 12UNJF - 3B	1.217 (30.91)	.680 (17.27)	1.620 (41.15)
-20	1.250 (31.75)	1.6250 - 12UNJ - 3B	1.347 (34.21)	.727 (18.47)	1.745 (44.32)
-24	1.500 (38.10)	1.8750 - 12UNJ - 3B	1.617 (41.07)	.880 (22.35)	1.995 (50.67)
-28	1.750 (44.45)	2.2500 - 12UNJ - 3B	1.890 (48.01)	.930 (23.62)	2.410 (61.21)
-32	2.000 (50.80)	2.500 - 12UNJ - 3B	2.167 (55.04)	1.060 (26.92)	2.660 (67.56)
-40	2.500 (63.50)	3.000 - 12UNJ - 3B	2.667 (67.74)	.860 (21.84)	3.200 (81.28)
-48	3.000 (76.20)	3.500 - 12UNJ - 3B	3.180 (80.77)	.910 (23.11)	3.700 (93.98)

FIGURE 1. Nut, tube coupling - Continued.

MS9198D
w/AMENDMENT 1

Dash number	D diameter inches (mm)	E inches (mm)	F diameter inches (mm)	H inches (mm) +.030 (0.76) -.000
-02	.438 (11.13)	.430 - .439 (10.92) - (11.15)	.272 - .280 (6.91) - (7.11)	.312 (7.92)
-03	.500 (12.70)	.492 - .502 (12.50) - (12.75)	.334 - .342 (8.48) - (8.69)	.375 (9.53)
-04	.562 (14.27)	.553 - .564 (14.05) - (14.33)	.388 - .397 (9.86) - (10.08)	.438 (11.13)
-05	.625 (15.88)	.616 - .627 (15.65) - (15.93)	.451 - .459 (11.46) - (11.66)	.500 (12.70)
-06	.688 (17.48)	.679 - .690 (17.25) - (17.53)	.508 - .517 (12.90) - (13.13)	.562 (14.27)
-07	.750 (19.05)	.741 - .752 (18.82) - (19.10)	.570 - .579 (14.48) - (14.71)	.625 (15.88)
-08	.875 (22.23)	.865 - .877 (21.97) - (22.28)	.689 - .698 (17.50) - (17.73)	.750 (19.05)
-09	.937 (23.80)	.928 - .940 (23.57) - (23.88)	.751 - .760 (19.08) - (19.30)	.812 (20.62)
-10	1.000 (25.40)	.990 - 1.002 (25.15) - (25.45)	.805 - .815 (20.45) - (20.70)	.875 (22.23)
-11	1.125 (28.58)	1.114 - 1.127 (28.30) - (28.63)	.918 - .930 (23.32) - (23.62)	1.000 (25.40)
-12	1.250 (31.75)	1.239 - 1.252 (31.47) - (31.80)	.981 - .991 (24.92) - (25.17)	1.062 (26.97)
-14	1.375 (34.93)	1.364 - 1.377 (34.65) - (34.98)	1.106 - 1.116 (28.09) - (28.35)	1.188 (30.18)
-16	1.500 (38.10)	1.489 - 1.502 (37.82) - (38.15)	1.231 - 1.241 (31.27) - (31.52)	1.312 (33.32)
-18	1.750 (44.45)	1.738 - 1.752 (44.15) - (44.50)	1.419 - 1.429 (36.04) - (36.30)	1.500 (38.10)
-20	1.812 (46.02)	1.800 - 1.814 (45.72) - (46.08)	1.544 - 1.554 (39.22) - (39.47)	1.625 (41.28)
-24	2.125 (53.98)	2.113 - 2.127 (53.67) - (54.03)	1.794 - 1.804 (45.57) - (45.82)	1.875 (47.63)
-28	2.500 (63.50)	2.487 - 2.502 (63.17) - (63.55)	2.169 - 2.179 (55.09) - (55.35)	2.250 (57.15)
-32	2.750 (69.85)	2.737 - 2.752 (69.52) - (69.90)	2.419 - 2.429 (61.44) - (61.70)	2.500 (63.50)
-40	3.250 (82.55)	3.237 - 3.252 (82.22) - (82.60)	2.919 - 2.929 (74.14) - (74.40)	3.000 (76.20)
-48	3.812 (96.82)	3.798 - 3.814 (96.47) - (96.88)	3.419 - 3.429 (86.84) - (87.10)	3.500 (88.90)

FIGURE 1. Nut, tube coupling - Continued.

MS9198D
w/AMENDMENT 1

Dash number	J min	K max inches (mm)	L inches (mm) ±.005 (0.13)	M inches (mm)	N inches (mm)
-02	.491 (12.47)	.425 (10.80)	.575 (14.61)	.650 (16.51)	.045 (1.14) - .050 (1.27)
-03	.561 (14.25)	.441 (11.20)	.592 (15.04)	.667 (16.94)	.057 (1.45) - .062 (1.57)
-04	.631 (16.03)	.482 (12.24)	.607 (15.42)	.682 (17.32)	
-05	.703 (17.86)	.482 (12.24)	.610 (15.49)	.690 (17.53)	.065 (1.65) - .075 (1.91)
-06	.775 (19.69)	.535 (13.59)	.637 (16.18)	.742 (18.85)	
-07	.846 (21.49)	.536 (13.61)	.663 (16.84)	.768 (19.51)	
-08	.987 (25.07)	.569 (14.45)	.723 (18.36)	.828 (21.03)	
-09	1.059 (26.90)	.569 (14.45)	.723 (18.36)	.828 (21.03)	
-10	1.130 (28.70)	.667 (16.94)	.817 (20.75)	.927 (23.55)	
-11	1.271 (32.28)	.738 (18.75)	.868 (22.05)	.968 (24.59)	
-12	1.414 (35.92)	.738 (18.75)	.868 (22.05)	.968 (24.59)	
-14	1.556 (39.52)	.765 (19.43)	.915 (23.24)	1.015 (25.78)	
-16	1.699 (43.15)	.786 (19.96)	.962 (24.43)	1.062 (26.97)	
-18	1.985 (50.42)	.800 (20.32)	.990 (25.15)	1.120 (28.45)	
-20	2.054 (52.17)	.810 (20.57)	1.017 (25.83)	1.167 (29.64)	
-24	2.411 (61.24)	.937 (23.80)	1.170 (29.72)	1.320 (33.53)	
-28	2.838 (72.09)	.945 (24.00)	1.170 (29.72)	1.370 (34.80)	
-32	3.123 (79.32)	1.050 (26.67)	1.300 (33.02)	1.500 (38.10)	
-40	3.693 (93.80)	.850 (21.59)	1.100 (27.94)	1.300 (33.02)	
-48	4.334 (110.08)	.900 (22.86)	1.150 (29.21)	1.350 (34.29)	

FIGURE 1. Nut, tube coupling - Continued.

MS9198D
w/AMENDMENT 1

Dash number	Q min	W inches (mm)	X inches (mm) ±.005 (0.13)	
-02	.300 (7.62)	.535 (13.59)	.180 (4.57)	- .190 (4.83)
-03	.316 (8.03)	.552 (14.02)	.210 (5.33)	- .220 (5.59)
-04	.332 (8.43)	.567 (14.40)	.245 (6.22)	- .255 (6.48)
-05	.332 (8.43)	.565 (14.35)	.280 (7.11)	- .290 (7.37)
-06	.367 (9.32)	.592 (15.04)	.310 (7.87)	- .320 (8.13)
-07	.368 (9.35)	.618 (15.70)	.336 (8.53)	- .356 (9.04)
-08	.383 (9.73)	.648 (16.46)	.400 (10.16)	- .420 (10.67)
-09	.383 (9.73)	.668 (16.97)	.427 (10.85)	- .447 (11.35)
-10	.453 (11.51)	.777 (19.74)	.465 (11.81)	- .485 (12.32)
-11	.488 (12.40)	.818 (20.78)	.520 (13.21)	- .540 (13.72)
-12	.488 (12.40)	.818 (20.78)	.580 (14.73)	- .600 (15.24)
-14	.515 (13.08)	.865 (21.97)	.645 (16.38)	- .665 (16.89)
-16	.536 (13.61)	.912 (23.16)	.715 (18.16)	- .735 (18.67)
-18	.550 (13.97)	.945 (24.00)	.840 (21.34)	- .860 (21.84)
-20	.560 (14.22)	.967 (24.56)	.890 (22.61)	- .910 (23.11)
-24	.687 (17.45)	1.100 (27.94)	1.040 (26.42)	- 1.060 (26.92)
-28	.695 (17.65)	1.170 (29.72)	1.255 (31.88)	- 1.275 (32.39)
-32	.800 (20.32)	1.300 (33.02)	1.395 (35.43)	- 1.415 (35.94)
-40	.600 (15.24)	1.100 (27.94)	1.680 (42.67)	- 1.700 (43.18)
-48	.650 (16.51)	1.150 (29.21)	2.000 (50.80)	- 2.020 (51.31)

FIGURE 1. Nut, tube coupling - Continued.

MS9198D
w/AMENDMENT 1

NOTES:

1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Tolerances linear dimensions ± 0.010 inch (0.25 mm) angular dimensions $\pm 5^\circ$.
4. Surface texture unless otherwise specified shall be 125μ inches ($3.17\mu\text{m}$) except hex, reference ASME B46.1.
5. Diameters A and F shall be concentric to thread PD within .004 inch (0.010 mm) FIM. Diameter C and hexagon E shall be concentric to thread PD within .010 inch (0.25 mm) FIM.
6. Break Sharp edges .003 - .015 inch (0.08 - 0.38 mm) unless otherwise specified. Fillets .005 - .020 inch (0.13 - 0.51 mm) RAD or chamfer.
7. Multiple marking permissible provided positive identification is shown. Parts shall be marked before threading.
8. For design features purposes, this standard takes precedence over documents referenced herein.

FIGURE 1. Nut, tube coupling - Continued.

REQUIREMENTS:


Dimensions and configurations: See figure 1.

Material: Steel, corrosion and heat-resistant in accordance with SAE-AMS5646.

Parts shall be fluorescent penetrate inspected in accordance with ASTM E1417.

Cleaning: Parts shall be degreased and immersed for not less than 20 minutes in a solution of 1 volume of nitric acid (specific gravity = 1.42) and 9 volumes of water at room temperature.

PIN:



PIN Example:

MS9198-08 identifies a nut tube coupling .500 inch (0.13 mm) tube.

Do not use unassigned PIN's.

The approximate weight for each fitting is shown in table I.

MS9198D
w/AMENDMENT 1

TABLE I. Approximate weight.

Dash number	Approximate weight lb/100 (kg/100)		Dash number	Approximate weight lb/100 (kg/100)
-02	1.210 (0.55)		-11	7.859 (3.56)
-03	1.475 (0.67)		-12	9.907 (4.49)
-04	1.830 (0.83)		-14	12.164 (5.52)
-05	2.600 (1.18)		-16	13.637 (6.19)
-06	2.920 (1.32)		-18	19.830 (8.99)
-07	3.422 (1.55)		-20	20.016 (9.08)
-08	4.680 (2.12)		-24	27.093 (12.29)
-09	5.314 (2.41)		-28	41.710 (18.92)
-10	6.310 (2.86)		-32	49.000 (22.23)
			-40	60.621 (27.50)
			-48	78.529 (35.62)

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Referenced documents. This document references the following:

ASME B46.1
ASTM E1417
SAE-AS478
SAE-AS8879
SAE-AMS5646

CONCLUDING MATERIAL

Custodians:
Army - MI
Navy - AS
Air Force - 99
DLA - CC

Preparing activity:
DLA - CC

(Project 4730-2011-003)

Review activities:
Navy - MC
Air Force - 71

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at <https://assist.daps.dla.mil>.