

USER ACTIVITIES:

REVIEWER ACTIVITIES:
DLA - IS

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.




TABLE I. DASH NUMBERS AND DIMENSIONS

DASH NO.	L	K	APPROX WEIGHT LB/100	DASH NO.	L	K	APPROX WEIGHT LB/100	DASH NO.	L	K	APPROX WEIGHT LB/100
-04	.625	.088-.108	3.42	-22	1.750	.690-.750	6.44	-40	4.000	2.940-3.000	12.47
-05	.688	.088-.108	3.58	-23	1.875	.815-.875	6.77	-41	4.125	3.065-3.125	12.80
-06	.750	.088-.108	3.74	-24	2.000	.940-1.000	7.11	-42	4.250	3.190-3.250	13.13
-07	.812	.088-.108	3.90	-25	2.125	1.065-1.125	7.44	-43	4.375	3.315-3.375	13.46
-08	.875	.088-.108	4.07	-26	2.250	1.190-1.250	7.78	-44	4.500	3.440-3.500	13.89
-09	.938	.088-.108	4.24	-27	2.375	1.315-1.375	8.11	-45	4.625	3.565-3.625	14.23
-10	1.000	.088-.108	4.41	-28	2.500	1.440-1.500	8.44	-46	4.750	3.690-3.750	14.56
-11	1.062	.088-.108	4.58	-29	2.625	1.565-1.625	8.78	-47	4.875	3.815-3.875	14.89
-12	1.125	.125-.145	4.75	-30	2.750	1.690-1.750	9.12	-48	5.000	3.940-4.000	15.23
-13	1.188	.128-.188	4.91	-31	2.875	1.815-1.875	9.46	-49	5.125	4.065-4.125	15.57
-14	1.250	.190-.250	5.08	-32	3.000	1.940-2.000	9.80	-50	5.250	4.190-4.250	15.90
-15	1.312	.252-.312	5.25	-33	3.125	2.065-2.125	10.13	-51	5.375	4.315-4.375	16.23
-16	1.375	.315-.375	5.43	-34	3.250	2.190-2.250	10.47	-52	5.500	4.440-4.500	16.56
-17	1.438	.378-.438	5.60	-35	3.375	2.315-2.375	10.80	-53	5.625	4.565-4.625	16.89
-18	1.500	.440-.500	5.76	-36	3.500	2.440-2.500	11.14	-54	5.750	4.690-4.750	17.23
-19	1.562	.502-.562	5.93	-37	3.625	2.565-2.625	11.47	-55	5.875	4.815-4.875	17.57
-20	1.625	.565-.625	6.10	-38	3.750	2.690-2.750	11.80	-56	6.000	4.940-5.000	17.91
-21	1.688	.628-.688	6.27	-39	3.875	2.815-2.875	12.14				

① ENTIRE STANDARD REVISED


P.A. NAVY - AS Other Cust	INTERNATIONAL INTEREST	TITLE BOLT, MACHINE-STEEL, DIFFUSED NICKEL- CADMIUM PLATED, DOUBLE HEXAGON EXTEND- ED WASHER HEAD, .375-24 UNJF-3A	MILITARY STANDARD MS9211
PROCUREMENT SPECIFICATION AMS 7459	SUPERSEDES		PAGE 1 OF 2

APPROVED 10 DEC 63 REVISED (A) 27 MAY 88

REQUIREMENTS:

1. MATERIAL: STEEL IN ACCORDANCE WITH AMS 6304 (UNS K14675).
2. HARDNESS: ROCKWELL C42-46.
3. FINISH: DIFFUSED NICKEL-CADMIUM PLATE IN ACCORDANCE WITH AMS 2416. DIMENSIONS SPECIFIED ARE AFTER PLATING. CONTACT POINTS PERMISSIBLE. PD MAY BE REDUCED .0012 MAX BEFORE PLATING.
4. MAGNETIC PARTICLE INSPECTION: MAGNETIC PARTICLE INSPECTION IN ACCORDANCE WITH AMS 2640 BEFORE PLATING.
5. THREADS: THREADS IN ACCORDANCE WITH MIL-S-8879. INCOMPLETE THREADS NOT TO ENTER FILLET.
6. DIMENSIONING AND TOLERANCING: DIMENSIONING AND TOLERANCING SHALL BE IN ACCORDANCE WITH ANSI Y14.5M.
7. MARKING: MARK PART NUMBER AND MANUFACTURER'S IDENTIFICATION IN ACCORDANCE WITH AS 478, CLASS A.
8. EDGES: BREAK SHARP EDGES .003-.015 UNLESS OTHERWISE SPECIFIED.
9. SURFACE TEXTURE: SURFACE TEXTURE IN ACCORDANCE WITH ANSI/ASME B46.1. UNLESS OTHERWISE SPECIFIED, SURFACE TO BE 125 MICROINCHES EXCEPT UPSET HEAD.
10. TOLERANCES: UNLESS OTHERWISE SPECIFIED, TOLERANCES SHALL BE FOR LINEAR DIMENSIONS $\pm .010$, ANGULAR DIMENSION $\pm 5^\circ$.
11. PART NUMBER: THE PART NUMBER SHALL CONSIST OF THE BASIC MS NUMBER FOLLOWED BY A DASH NUMBER FROM TABLE I.

EXAMPLE: MS9211-04



MS9211-04 INDICATES - BOLT, MACHINE - STEEL AMS 6304, DIFFUSED NICKEL-CADMIUM PLATED, DOUBLE HEXAGON EXTENDED WASHER HEAD, .375-24 UNJF-3A x .625 LONG.

NOTES:

1. ALL DIMENSIONS ARE IN INCHES.
2. DO NOT USE UNASSIGNED PART NUMBERS.
3. IN THE EVENT OF A CONFLICT BETWEEN THE TEXT OF THIS STANDARD AND THE REFERENCES CITED HEREIN, THE TEXT OF THIS STANDARD SHALL TAKE PRECEDENCE.
4. REFERENCED GOVERNMENT (OR NON-GOVERNMENT) DOCUMENTS OF THE ISSUE LISTED IN THAT ISSUE OF THE DEPARTMENT OF DEFENSE INDEX OF SPECIFICATIONS AND STANDARDS (DODISS) SPECIFIED IN THE SOLICITATION FORM A PART OF THIS STANDARD TO THE EXTENT SPECIFIED HEREIN.
5. THIS STANDARD WAS DEVELOPED COOPERATIVELY WITH THE SAE AEROSPACE PROPULSION DIVISION.
6. AS AND AMS ARE SAE PUBLICATIONS.

USER ACTIVITIES:

REVIEWER ACTIVITIES:
DLA - IS

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

P.A. NAVY - AS Other Cust	INTERNATIONAL INTEREST	TITLE BOLT, MACHINE-STEEL, DIFFUSED NICKEL- CADMIUM PLATED, DOUBLE HEXAGON EXTEND- ED WASHER HEAD, .375-24 UNJF-3A	MILITARY STANDARD MS9211
PROCUREMENT SPECIFICATION AMS 7459	SUPERSEDES	PAGE 2	OF 2