

INCH-POUND

MS9298A  
AMENDMENT 1  
8 July 2003

MILITARY STANDARD

BOLT, MACHINE-STEEL AMS 6322, BLACK OXIDE, DRILLED  
1 HOLE, HEXAGON HEAD, .4375-20 UNJF-3A

This amendment forms a part of MS9298A, dated 26 October 1972, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Bolt illustration view at the right: Delete "MIL-S-8879" from ".4375-20 UNJF-3A SPEC MIL-S-8879" and substitute "AS8879".

For view A enlarged view: Add "(SEE NOTE 15)" after ".648 DIA MIN BEARING SURFACE".

Add the word "NOTES:" above note 1.

Note 9: Delete "AMS 7452" and substitute "AS7452".

Note 11: Delete "AS291" and substitute "ASME B46.1".

Add new note: "15. BEARING SURFACE: BEARING SURFACE SHALL BE FLAT AND WASHER FACED. DIAMETER OF BEARING SURFACE SHALL BE EQUAL TO THE MAXIMUM WIDTH ACROSS FLATS WITHIN A TOLERANCE OF MINUS 10% IN ACCORDANCE WITH ASME B18.2.1"

Custodians:  
Navy -AS  
DLA-IS

Preparing Activity:  
DLA-IS

(Project 5306-2710)