


**MS9487**FED. SUP CLASS  
5305

(A) MARK PART NUMBER AND MANUFACTURERS IDENTIFICATION PER AS 478 CLASS A



.106  
.094

32

L

K

.016

.020  
.010 R

32

(A)

.137 DIA

.138-40 UNJF-3A

(A) MIL-8-8879

32

CHAMFER APPROX .025 X 45°

THIS SURFACE MUST BE SQUARE WITH SHANK WITHIN .003 FIR

CHAMFER 30° TO .250 DIAMETER

SECTION THROUGH THREAD PROFILE

.210 DIA MIN

HEARING SURFACE

VIEW A ENLARGED

(A)

.260 DIA MAX

PART NUMBER	L	K	APPROX WEIGHT LB/100	PART NUMBER	L	K	APPROX WEIGHT LB/100
MS9487-02	.250	.058-.078	.25				
MS9487-03	.312	.058-.078	.28				
MS9487-04	.375	.058-.078	.31				
MS9487-05	.438	.058-.078	.33				
MS9487-06	.500	.058-.078	.36				
MS9487-07	.562	.058-.078	.38				
MS9487-08	.625	.058-.099	.41				
MS9487-09	.688	.102-.162	.44				
MS9487-10	.750	.164-.224	.46				
MS9487-11	.812	.226-.286	.49				
MS9487-12	.875	.289-.349	.51				
MS9487-13	.938	.352-.412	.54				
MS9487-14	1.000	.414-.474	.57				
MS9487-15	1.062	.476-.536	.59				
MS9487-16	1.125	.539-.599	.62				
MS9487-17	1.188	.602-.662	.64				
MS9487-18	1.250	.664-.724	.67				
MS9487-19	1.312	.726-.786	.69				
MS9487-20	1.375	.789-.849	.72				
MS9487-21	1.438	.852-.912	.75				
MS9487-22	1.500	.914-.974	.77				
MS9487-23	1.562	.976-1.036	.80				
MS9487-24	1.625	1.039-1.099	.82				
MS9487-25	1.688	1.102-1.162	.85				
MS9487-26	1.750	1.164-1.224	.87				
MS9487-27	1.812	1.226-1.286	.90				
MS9487-28	1.875	1.289-1.349	.92				
MS9487-29	1.938	1.352-1.412	.95				
MS9487-30	2.000	1.414-1.474	.97				

- (A) 1. SHANK SHALL BE STRAIGHT WITHIN .003 TOTAL PER INCH OF SCREW LENGTH.  
 2. THE CONCENTRICITY OF THREAD PD IN RELATION TO THE SHANK SHALL BE WITHIN .006 FIR.  
 3. THE CONCENTRICITY OF THE SHANK IN RELATION TO THE WASHER FACE DIAMETER AND HEXAGON SHALL BE WITHIN .009 FIR.  
 4. INCOMPLETE THREADS NOT TO ENTER FILLET.  
 5. MATERIAL: CORROSION AND HEAT RESISTANT STEEL AMS 5731.  
 6. MANUFACTURING SPECIFICATION: AMS 7477.  
 7. FLUORESCENT PENETRANT INSPECTION PER AMS 2645.  
 8. SURFACE TEXTURE: USAS B46.1-1962 UNLESS OTHERWISE SPECIFIED SURFACES TO BE 125 MICROINCHES EXCEPT HEXAGON  
 9. BREAK SHARP EDGES .003-.015 UNLESS OTHERWISE SPECIFIED.  
 10. DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: LINEAR DIMENSIONS  $\pm .010$ , ANGULAR DIMENSIONS  $\pm 5^\circ$ .  
 11. DO NOT USE UNASSIGNED PART NUMBERS.

(A) AS & AMS ARE SOCIETY OF AUTOMOTIVE ENGINEERS, INC. PUBLICATIONS.  
 (A) THIS STANDARD WAS DEVELOPED COOPERATIVELY WITH THE MILITARY SERVICES BY THE SAE AEROSPACE PART STANDARDS DIVISION

This military standard is approved by the Department of Defense and is mandatory on all activities. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A. USAP - 11 Other Cust	INTERATIONAL INTEREST ASCC AIR STD 17/2	TITLE (A) SCREW, MACHINE - HEXAGON HEAD, FULL SHANK, AMS 5731, .138-40 UNJF-3A	MILITARY STANDARD <b>MS9487</b>
PROCUREMENT SPECIFICATION	SUPERSEDES:	SHEET 1 OF 1	

DD FORM 672-1 (Coordinated)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

☆ U. S. GOVERNMENT PRINTING OFFICE: 1970-393-093/S-3727

REVISED (A) 17 Nov 69

APPROVED 5 May 1965