

<div style="float: left; width: 150px; font-size: 2em; font-weight: bold; transform: rotate(-90deg); transform-origin: left top;">MS9492</div> <div style="clear: both;"></div>				<div style="float: right; width: 150px; text-align: center;"> FED SUP CLASS 5306 </div>																																																																																																																																																																																																																																							
VIEW A ENLARGED				SECTION THROUGH THREAD PROFILE																																																																																																																																																																																																																																							
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>PART NUMBER</th> <th>L</th> <th>K</th> <th>APPROX WEIGHT LB/100</th> </tr> </thead> <tbody> <tr><td>MS9492-04</td><td>.625</td><td>.088-.108</td><td>3.64</td></tr> <tr><td>MS9492-05</td><td>.688</td><td>.088-.108</td><td>3.84</td></tr> <tr><td>MS9492-06</td><td>.750</td><td>.088-.108</td><td>4.03</td></tr> <tr><td>MS9492-07</td><td>.812</td><td>.088-.108</td><td>4.22</td></tr> <tr><td>MS9492-08</td><td>.875</td><td>.088-.108</td><td>4.42</td></tr> <tr><td>MS9492-09</td><td>.938</td><td>.088-.108</td><td>4.62</td></tr> <tr><td>MS9492-10</td><td>1.000</td><td>.088-.108</td><td>4.81</td></tr> <tr><td>MS9492-11</td><td>1.062</td><td>.088-.108</td><td>5.00</td></tr> <tr><td>MS9492-12</td><td>1.125</td><td>.088-.125</td><td>5.20</td></tr> <tr><td>MS9492-13</td><td>1.188</td><td>.128-.188</td><td>5.39</td></tr> <tr><td>MS9492-14</td><td>1.250</td><td>.190-.250</td><td>5.58</td></tr> <tr><td>MS9492-15</td><td>1.312</td><td>.252-.312</td><td>5.78</td></tr> <tr><td>MS9492-16</td><td>1.375</td><td>.315-.375</td><td>5.98</td></tr> <tr><td>MS9492-17</td><td>1.438</td><td>.378-.438</td><td>6.17</td></tr> <tr><td>MS9492-18</td><td>1.500</td><td>.440-.500</td><td>6.37</td></tr> <tr><td>MS9492-19</td><td>1.562</td><td>.502-.562</td><td>6.56</td></tr> <tr><td>MS9492-20</td><td>1.625</td><td>.565-.625</td><td>6.76</td></tr> <tr><td>MS9492-21</td><td>1.688</td><td>.628-.688</td><td>6.95</td></tr> <tr><td>MS9492-22</td><td>1.750</td><td>.690-.750</td><td>7.15</td></tr> <tr><td>MS9492-23</td><td>1.812</td><td>.815-.875</td><td>7.54</td></tr> <tr><td>MS9492-24</td><td>2.000</td><td>.940-1.000</td><td>7.93</td></tr> <tr><td>MS9492-25</td><td>2.125</td><td>1.065-1.125</td><td>8.32</td></tr> <tr><td>MS9492-26</td><td>2.250</td><td>1.190-1.250</td><td>8.70</td></tr> <tr><td>MS9492-27</td><td>2.375</td><td>1.315-1.375</td><td>9.09</td></tr> <tr><td>MS9492-28</td><td>2.500</td><td>1.440-1.500</td><td>9.48</td></tr> <tr><td>MS9492-29</td><td>2.625</td><td>1.565-1.625</td><td>9.87</td></tr> <tr><td>MS9492-30</td><td>2.750</td><td>1.690-1.750</td><td>10.26</td></tr> </tbody> </table>				PART NUMBER	L	K	APPROX WEIGHT LB/100	MS9492-04	.625	.088-.108	3.64	MS9492-05	.688	.088-.108	3.84	MS9492-06	.750	.088-.108	4.03	MS9492-07	.812	.088-.108	4.22	MS9492-08	.875	.088-.108	4.42	MS9492-09	.938	.088-.108	4.62	MS9492-10	1.000	.088-.108	4.81	MS9492-11	1.062	.088-.108	5.00	MS9492-12	1.125	.088-.125	5.20	MS9492-13	1.188	.128-.188	5.39	MS9492-14	1.250	.190-.250	5.58	MS9492-15	1.312	.252-.312	5.78	MS9492-16	1.375	.315-.375	5.98	MS9492-17	1.438	.378-.438	6.17	MS9492-18	1.500	.440-.500	6.37	MS9492-19	1.562	.502-.562	6.56	MS9492-20	1.625	.565-.625	6.76	MS9492-21	1.688	.628-.688	6.95	MS9492-22	1.750	.690-.750	7.15	MS9492-23	1.812	.815-.875	7.54	MS9492-24	2.000	.940-1.000	7.93	MS9492-25	2.125	1.065-1.125	8.32	MS9492-26	2.250	1.190-1.250	8.70	MS9492-27	2.375	1.315-1.375	9.09	MS9492-28	2.500	1.440-1.500	9.48	MS9492-29	2.625	1.565-1.625	9.87	MS9492-30	2.750	1.690-1.750	10.26	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>PART NUMBER</th> <th>L</th> <th>K</th> <th>APPROX WEIGHT LB/100</th> </tr> </thead> <tbody> <tr><td>MS9492-31</td><td>2.875</td><td>1.815-1.875</td><td>10.65</td></tr> <tr><td>MS9492-32</td><td>3.000</td><td>1.940-2.000</td><td>11.04</td></tr> <tr><td>MS9492-33</td><td>3.125</td><td>2.065-2.125</td><td>11.43</td></tr> <tr><td>MS9492-34</td><td>3.250</td><td>2.190-2.250</td><td>11.82</td></tr> <tr><td>MS9492-35</td><td>3.375</td><td>2.315-2.375</td><td>12.21</td></tr> <tr><td>MS9492-36</td><td>3.500</td><td>2.440-2.500</td><td>12.60</td></tr> <tr><td>MS9492-37</td><td>3.625</td><td>2.565-2.625</td><td>12.99</td></tr> <tr><td>MS9492-38</td><td>3.750</td><td>2.690-2.750</td><td>13.38</td></tr> <tr><td>MS9492-39</td><td>3.875</td><td>2.815-2.875</td><td>13.77</td></tr> <tr><td>MS9492-40</td><td>4.000</td><td>2.940-3.000</td><td>14.16</td></tr> <tr><td>MS9492-41</td><td>4.125</td><td>3.065-3.125</td><td>14.55</td></tr> <tr><td>MS9492-42</td><td>4.250</td><td>3.190-3.250</td><td>14.94</td></tr> <tr><td>MS9492-43</td><td>4.375</td><td>3.315-3.375</td><td>15.33</td></tr> <tr><td>MS9492-44</td><td>4.500</td><td>3.440-3.500</td><td>15.72</td></tr> <tr><td>MS9492-45</td><td>4.625</td><td>3.565-3.625</td><td>16.11</td></tr> <tr><td>MS9492-46</td><td>4.750</td><td>3.690-3.750</td><td>16.50</td></tr> <tr><td>MS9492-47</td><td>4.875</td><td>3.815-3.875</td><td>16.89</td></tr> <tr><td>MS9492-48</td><td>5.000</td><td>3.940-4.000</td><td>17.28</td></tr> <tr><td>MS9492-49</td><td>5.125</td><td>4.065-4.125</td><td>17.67</td></tr> <tr><td>MS9492-50</td><td>5.250</td><td>4.190-4.250</td><td>18.06</td></tr> <tr><td>MS9492-51</td><td>5.375</td><td>4.315-4.375</td><td>18.45</td></tr> <tr><td>MS9492-52</td><td>5.500</td><td>4.440-4.500</td><td>18.84</td></tr> <tr><td>MS9492-53</td><td>5.625</td><td>4.565-4.625</td><td>19.22</td></tr> <tr><td>MS9492-54</td><td>5.750</td><td>4.690-4.750</td><td>19.61</td></tr> <tr><td>MS9492-55</td><td>5.875</td><td>4.815-4.875</td><td>20.00</td></tr> <tr><td>MS9492-56</td><td>6.000</td><td>4.940-5.000</td><td>20.39</td></tr> <tr><td>MS9492-57</td><td>1 812</td><td>752-.812</td><td>7 35</td></tr> <tr><td>MS9492-58</td><td>1 938</td><td>878-.938</td><td>7 74</td></tr> </tbody> </table>				PART NUMBER	L	K	APPROX WEIGHT LB/100	MS9492-31	2.875	1.815-1.875	10.65	MS9492-32	3.000	1.940-2.000	11.04	MS9492-33	3.125	2.065-2.125	11.43	MS9492-34	3.250	2.190-2.250	11.82	MS9492-35	3.375	2.315-2.375	12.21	MS9492-36	3.500	2.440-2.500	12.60	MS9492-37	3.625	2.565-2.625	12.99	MS9492-38	3.750	2.690-2.750	13.38	MS9492-39	3.875	2.815-2.875	13.77	MS9492-40	4.000	2.940-3.000	14.16	MS9492-41	4.125	3.065-3.125	14.55	MS9492-42	4.250	3.190-3.250	14.94	MS9492-43	4.375	3.315-3.375	15.33	MS9492-44	4.500	3.440-3.500	15.72	MS9492-45	4.625	3.565-3.625	16.11	MS9492-46	4.750	3.690-3.750	16.50	MS9492-47	4.875	3.815-3.875	16.89	MS9492-48	5.000	3.940-4.000	17.28	MS9492-49	5.125	4.065-4.125	17.67	MS9492-50	5.250	4.190-4.250	18.06	MS9492-51	5.375	4.315-4.375	18.45	MS9492-52	5.500	4.440-4.500	18.84	MS9492-53	5.625	4.565-4.625	19.22	MS9492-54	5.750	4.690-4.750	19.61	MS9492-55	5.875	4.815-4.875	20.00	MS9492-56	6.000	4.940-5.000	20.39	MS9492-57	1 812	752-.812	7 35	MS9492-58	1 938	878-.938	7 74
PART NUMBER	L	K	APPROX WEIGHT LB/100																																																																																																																																																																																																																																								
MS9492-04	.625	.088-.108	3.64																																																																																																																																																																																																																																								
MS9492-05	.688	.088-.108	3.84																																																																																																																																																																																																																																								
MS9492-06	.750	.088-.108	4.03																																																																																																																																																																																																																																								
MS9492-07	.812	.088-.108	4.22																																																																																																																																																																																																																																								
MS9492-08	.875	.088-.108	4.42																																																																																																																																																																																																																																								
MS9492-09	.938	.088-.108	4.62																																																																																																																																																																																																																																								
MS9492-10	1.000	.088-.108	4.81																																																																																																																																																																																																																																								
MS9492-11	1.062	.088-.108	5.00																																																																																																																																																																																																																																								
MS9492-12	1.125	.088-.125	5.20																																																																																																																																																																																																																																								
MS9492-13	1.188	.128-.188	5.39																																																																																																																																																																																																																																								
MS9492-14	1.250	.190-.250	5.58																																																																																																																																																																																																																																								
MS9492-15	1.312	.252-.312	5.78																																																																																																																																																																																																																																								
MS9492-16	1.375	.315-.375	5.98																																																																																																																																																																																																																																								
MS9492-17	1.438	.378-.438	6.17																																																																																																																																																																																																																																								
MS9492-18	1.500	.440-.500	6.37																																																																																																																																																																																																																																								
MS9492-19	1.562	.502-.562	6.56																																																																																																																																																																																																																																								
MS9492-20	1.625	.565-.625	6.76																																																																																																																																																																																																																																								
MS9492-21	1.688	.628-.688	6.95																																																																																																																																																																																																																																								
MS9492-22	1.750	.690-.750	7.15																																																																																																																																																																																																																																								
MS9492-23	1.812	.815-.875	7.54																																																																																																																																																																																																																																								
MS9492-24	2.000	.940-1.000	7.93																																																																																																																																																																																																																																								
MS9492-25	2.125	1.065-1.125	8.32																																																																																																																																																																																																																																								
MS9492-26	2.250	1.190-1.250	8.70																																																																																																																																																																																																																																								
MS9492-27	2.375	1.315-1.375	9.09																																																																																																																																																																																																																																								
MS9492-28	2.500	1.440-1.500	9.48																																																																																																																																																																																																																																								
MS9492-29	2.625	1.565-1.625	9.87																																																																																																																																																																																																																																								
MS9492-30	2.750	1.690-1.750	10.26																																																																																																																																																																																																																																								
PART NUMBER	L	K	APPROX WEIGHT LB/100																																																																																																																																																																																																																																								
MS9492-31	2.875	1.815-1.875	10.65																																																																																																																																																																																																																																								
MS9492-32	3.000	1.940-2.000	11.04																																																																																																																																																																																																																																								
MS9492-33	3.125	2.065-2.125	11.43																																																																																																																																																																																																																																								
MS9492-34	3.250	2.190-2.250	11.82																																																																																																																																																																																																																																								
MS9492-35	3.375	2.315-2.375	12.21																																																																																																																																																																																																																																								
MS9492-36	3.500	2.440-2.500	12.60																																																																																																																																																																																																																																								
MS9492-37	3.625	2.565-2.625	12.99																																																																																																																																																																																																																																								
MS9492-38	3.750	2.690-2.750	13.38																																																																																																																																																																																																																																								
MS9492-39	3.875	2.815-2.875	13.77																																																																																																																																																																																																																																								
MS9492-40	4.000	2.940-3.000	14.16																																																																																																																																																																																																																																								
MS9492-41	4.125	3.065-3.125	14.55																																																																																																																																																																																																																																								
MS9492-42	4.250	3.190-3.250	14.94																																																																																																																																																																																																																																								
MS9492-43	4.375	3.315-3.375	15.33																																																																																																																																																																																																																																								
MS9492-44	4.500	3.440-3.500	15.72																																																																																																																																																																																																																																								
MS9492-45	4.625	3.565-3.625	16.11																																																																																																																																																																																																																																								
MS9492-46	4.750	3.690-3.750	16.50																																																																																																																																																																																																																																								
MS9492-47	4.875	3.815-3.875	16.89																																																																																																																																																																																																																																								
MS9492-48	5.000	3.940-4.000	17.28																																																																																																																																																																																																																																								
MS9492-49	5.125	4.065-4.125	17.67																																																																																																																																																																																																																																								
MS9492-50	5.250	4.190-4.250	18.06																																																																																																																																																																																																																																								
MS9492-51	5.375	4.315-4.375	18.45																																																																																																																																																																																																																																								
MS9492-52	5.500	4.440-4.500	18.84																																																																																																																																																																																																																																								
MS9492-53	5.625	4.565-4.625	19.22																																																																																																																																																																																																																																								
MS9492-54	5.750	4.690-4.750	19.61																																																																																																																																																																																																																																								
MS9492-55	5.875	4.815-4.875	20.00																																																																																																																																																																																																																																								
MS9492-56	6.000	4.940-5.000	20.39																																																																																																																																																																																																																																								
MS9492-57	1 812	752-.812	7 35																																																																																																																																																																																																																																								
MS9492-58	1 938	878-.938	7 74																																																																																																																																																																																																																																								
<ol style="list-style-type: none"> 1. SHANK SHALL BE STRAIGHT WITHIN .0025 TOTAL PER INCH OF SHANK LENGTH. 2. THE CONCENTRICITY OF THREAD PD IN RELATION TO THE SHANK SHALL BE WITHIN .006 FIR. 3. THE CONCENTRICITY OF THE SHANK IN RELATION TO THE WASHER FACE DIAMETER AND HEXAGON SHALL BE WITHIN .017 FIR. 4. INCOMPLETE THREADS NOT TO ENTER FILLET. 5. MATERIAL CORROSION AND HEAT RESISTANT STEEL AMS 5731. 6. MANUFACTURING SPECIFICATION AMS 7477. 7. FLUORESCENT PENETRANT INSPECTION PFR AMS 2645. 8. SURFACE TEXTURE: USAS B46 1-1962 UNLESS OTHERWISE SPECIFIED SURFACES TO BE 125 MICROINCHES EXCEPT HEXAGON 9. BREAK SHARP EDGES .003-.015 UNLESS OTHERWISE SPECIFIED 10. DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: LINEAR DIMENSIONS ± .010, ANGULAR DIMENSIONS ± 5°. 11. DO NOT USE UNASSIGNED PART NUMBERS. 				<div style="float: right; width: 150px; text-align: center;"> REVISED 17 Nov 69 APPROVED 5 MAY 1965 </div>																																																																																																																																																																																																																																							
<p>AS & AMS ARE SOCIETY OF AUTOMOTIVE ENGINEERS, INC. PUBLICATIONS</p> <p>THIS STANDARD WAS DEVELOPED COOPERATIVELY WITH THE MILITARY SERVICES BY THE SAE AEROSPACE PART STANDARDS DIVISION</p>				MILITARY STANDARD <div style="font-size: 2em; font-weight: bold;">MS9492</div>																																																																																																																																																																																																																																							
P.A. 11AF - 11 Other Cast Army - AV Navy - AS		INTERATIONAL INTEREST ASSC AIR STD 17/2		TITLE BOLT, MACHINE - HEXAGON HEAD, FULL SHANK, AMS 5731, 375-24 UNJF-3A		SHEET 1 OF 1																																																																																																																																																																																																																																					
PROCUREMENT SPECIFICATION M.M.S.				SUPERSEDES:																																																																																																																																																																																																																																							

 User activities
 Review activities
 Army - AC, RL
 USAF - B2, B5

This military standard is approved by the Department of Defense and is mandatory on all activities. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

DD FORM 672-1 (Coordinated)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE