



PART NO.	L	K	APPROX WEIGHT LB/100	PART NO.	L	K	APPROX WEIGHT LB/100	PART NO.	L	K	APPROX WEIGHT LB/100
MS9570-03	.750	.105-.125	7.54	MS9570-22	2.125	.815-.875	14.00	MS9570-40	4.375	3.065-3.125	24.89
MS9570-04	.812	.105-.125	7.83	MS9570-23	2.250	.940-1.000	14.61	MS9570-41	4.500	3.190-3.250	25.50
MS9570-05	.875	.105-.125	8.12	MS9570-24	2.375	1.065-1.125	15.21	MS9570-42	4.625	3.315-3.375	26.11
MS9570-06	.938	.105-.125	8.41	MS9570-25	2.500	1.190-1.250	15.82	MS9570-43	4.750	3.440-3.500	26.71
MS9570-07	1.000	.105-.125	8.70	MS9570-26	2.625	1.315-1.375	16.42	MS9570-44	4.875	3.565-3.625	27.32
MS9570-08	1.062	.105-.125	8.99	MS9570-27	2.750	1.440-1.500	17.01	MS9570-45	5.000	3.690-3.750	27.92
MS9570-09	1.125	.105-.125	9.28	MS9570-28	2.875	1.565-1.625	17.61	MS9570-46	5.125	3.815-3.875	28.53
MS9570-10	1.188	.105-.125	9.57	MS9570-29	3.000	1.690-1.750	18.22	MS9570-47	5.250	3.940-4.000	29.13
MS9570-11	1.250	.105-.125	9.86	MS9570-30	3.125	1.815-1.875	18.83	MS9570-48	5.375	4.065-4.125	29.74
MS9570-12	1.312	.105-.125	10.15	MS9570-31	3.250	1.940-2.000	19.43	MS9570-49	5.500	4.190-4.250	30.35
MS9570-13	1.375	.105-.125	10.45	MS9570-32	3.375	2.065-2.125	20.04	MS9570-50	5.625	4.315-4.375	30.95
MS9570-14	1.438	.128-.188	10.74	MS9570-33	3.500	2.190-2.250	20.65	MS9570-51	5.750	4.440-4.500	31.56
MS9570-15	1.500	.190-.250	11.04	MS9570-34	3.625	2.315-2.375	21.26	MS9570-52	5.875	4.565-4.625	32.16
MS9570-16	1.562	.252-.312	11.33	MS9570-35	3.750	2.440-2.500	21.86	MS9570-53	6.000	4.690-4.750	32.77
MS9570-17	1.625	.315-.375	11.63	MS9570-36	3.875	2.565-2.625	22.47	MS9570-54	1.812	.502-.562	12.52
MS9570-18	1.688	.378-.438	11.92	MS9570-37	4.000	2.690-2.750	23.07	MS9570-55	1.938	.628-.688	13.11
MS9570-19	1.750	.440-.500	12.22	MS9570-38	4.125	2.815-2.875	23.68				
MS9570-20	1.875	.565-.625	12.81	MS9570-39	4.250	2.940-3.000	24.29				
MS9570-21	2.000	.690-.750	13.41								

1. SHAFT SHALL BE STRAIGHT WITHIN .002 TOTAL PER INCH OF BOLT LENGTH.
2. THE CONCENTRICITY OF THREAD PD IN RELATION TO THE SHANK SHALL BE WITHIN .006 FIR.
3. THE CONCENTRICITY OF THE SHANK IN RELATION TO THE WASHER FACE DIAMETER AND DOUBLE HEXAGON OD SHALL BE WITHIN .012 FIR.
4. INCOMPLETE THREADS NOT TO ENTER FILLET.
5. MATERIAL: CORROSION AND HEAT RESISTANT STEEL AMS 5731.
6. MANUFACTURING SPECIFICATION: AMS 7477.
7. FLUORESCENT PENETRANT INSPECTION PER AMS 2645.
8. SURFACE TEXTURE: USAS B46.1-1962 UNLESS OTHERWISE SPECIFIED, SURFACES TO BE 125 MICROINCHES EXCEPT UPPER HEAD.
9. BREAK SHARP EDGES .003-.015 UNLESS OTHERWISE SPECIFIED.
10. DIMENSION IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: LINEAR DIMENSIONS $\pm .010$, ANGULAR DIMENSIONS $\pm 5^\circ$.
11. DO NOT USE UNASSIGNED PART NUMBERS.

© REINSTATED AFTER 27 JUN 84

AS & AMS ARE SOCIETY OF AUTOMOTIVE ENGINEERS, INC. PUBLICATIONS.
THIS STANDARD WAS DEVELOPED COOPERATIVELY WITH THE MILITARY SERVICES BY THE SAE AEROSPACE PART STANDARDS DIVISION.

P.A. AS Other Cust AV 99	TITLE BOLT, MACHINE - DOUBLE HEXAGON EXTENDED WASHER HEAD, DRILLED, PD SHANK, AMS5731, 500-20 UNJF-3A	MILITARY STANDARD MS9570
PROCUREMENT SPECIFICATION SUPERSEDES:	PAGE 1 OF 1	

User activities:

Review activities:
AIR FORCE-82
DLA-15

This military standard is approved by the Department of Defense and is mandatory on all activities. Selection for all new engineering and design applications and for repetitive use shall be made from this document.