


MS9731 (ASG)

PART NO.	L	K	APPROX WEIGHT LB/100
MS9731-02	.250	.062-.082	.42
MS9731-03	.312	.062-.082	.45
MS9731-04	.375	.062-.082	.46
MS9731-05	.435	.062-.082	.51
MS9731-06	.500	.062-.082	.55
MS9731-07	.562	.062-.082	.57
MS9731-08	.625	.062-.082	.60
MS9731-09	.688	.062-.110	.63
MS9731-10	.750	.112-.172	.66
MS9731-11	.812	.174-.234	.68
MS9731-12	.875	.237-.297	.71
MS9731-13	.938	.300-.360	.74
MS9731-14	1.000	.362-.422	.77
MS9731-15	1.062	.424-.484	.80
MS9731-16	1.125	.487-.547	.83

PART NO.	L	K	APPROX WEIGHT LB/100
MS9731-17	1.188	.550-.610	.86
MS9731-18	1.250	.612-.672	.89
MS9731-19	1.312	.674-.734	.92
MS9731-20	1.375	.737-.797	.95
MS9731-21	1.438	.800-.860	.98
MS9731-22	1.500	.862-.922	1.01
MS9731-23	1.562	.924-.984	1.04
MS9731-24	1.625	.987-1.047	1.06
MS9731-25	1.688	1.050-1.110	1.10
MS9731-26	1.750	1.112-1.172	1.12
MS9731-27	1.812	1.174-1.234	1.15
MS9731-28	1.875	1.237-1.297	1.18
MS9731-29	2.000	1.362-1.422	1.24

Review activities:

USAF - 02, 65

This military standard is approved by the Department of the Air Force and the Naval Air Systems Command and is mandatory for use by these activities. All other military activities are required to employ this standard where suitable.

- SHANK SHALL BE STRAIGHT WITHIN .003 PER INCH OF SCREW LENGTH.
- THE RUNOUT OF THREAD PD IN RELATION TO THE SHANK SHALL BE WITHIN .006 FIR.
- THE RUNOUT OF THE SHANK IN RELATION TO THE WASHER FACE DIAMETER AND DOUBLE HEXAGON OD SHALL BE WITHIN .005 FIR.
- INCOMPLETE THREADS NOT TO ENTER FILLET.
- MATERIAL: CRCS AMS 5643.
- HARDNESS: ROCKWELL C32-39.
- MANUFACTURING SPECIFICATION: AMS 7474.
- FLUORESCENT PENETRANT INSPECTION PER AMS 2645.
- SURFACE TEXTURE: USAS B46.1-1962. UNLESS OTHERWISE SPECIFIED, SURFACES TO BE 125 MICROINCHES EXCEPT UPSET HEAD.
- BREAK SHARP EDGES .003-.015 UNLESS OTHERWISE SPECIFIED.
- DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: LINEAR DIMENSIONS $\pm .010$, ANGULAR DIMENSIONS $\pm 5^\circ$.
- DO NOT USE UNASSIGNED PART NUMBERS.

AS & AMS ARE SOCIETY OF AUTOMOTIVE ENGINEERS, INC. PUBLICATIONS.

THIS STANDARD WAS DEVELOPED COOPERATIVELY WITH THE MILITARY SERVICES BY THE SAE AEROSPACE PART STANDARDS DIV.

P.A. USAF - 11

Other Cust
Navy - AS

TITLE

SCREW, MACHINE - DOUBLE HEXAGON EXTENDED
WASHER HEAD, PD SHANK, CRCS AMS 5643, .164-36 UNJF-3A

MILITARY STANDARD

MS9731 (ASG)

PROCUREMENT SPECIFICATION

SUPERSEDES:

SHEET 1 OF 1

DD FORM 672-1 (Limited coordination)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

5305 - F012
U. S. GOVERNMENT PRINTING OFFICE: 1966 - 341-516/A-5343

APPROVED 3 Mar 69 REVISED