


MS9733 (ASG)

MARK PART NO. AND MANUFACTURER'S IDENTIFICATION PER AS 478 CLASS A

FED SUP CLASS
5306WRENCHING CONFIGURATION
PER AS 870 FOR
THIS DISTANCE

.144 MIN

5° MAX

.150 DIA

CHAMFER
28°-32° TO
.312 DIA

.015 R MAX

32

303

.168

.060 MIN

.025 R

.015

32

140° MIN

.232 DIA

.222 DIA

35° MIN TO ROOT
OF DOUBLE HEXAGONTHIS SURFACE MUST BE SQUARE
WITH SHANK WITHIN .003 FIR.

32

MAXIMUM 2
INCOMPLETE
THREADS
(SEE NOTE
4)CHAMFER
.031 X 45°
APPROX.250-28 UNJF-3A
MIL-S-8879SECTION THRU
THREAD PROFILE

PART NO.	L	K	APPROX WEIGHT LB/100	PART NO.	L	K	APPROX WEIGHT LB/100	PART NO.	L	K	APPROX WEIGHT LB/100
MS9733-04	.375	.079-.099	1.28	MS9733-25	1.688	.878-.938	2.77	MS9733-46	4.125	3.315-3.375	5.53
MS9733-05	.438	.079-.099	1.35	MS9733-26	1.750	.940-1.000	2.84	MS9733-47	4.250	3.440-3.500	5.67
MS9733-06	.500	.079-.099	1.42	MS9733-27	1.812	1.002-1.062	2.91	MS9733-48	4.375	3.565-3.625	5.81
MS9733-07	.562	.079-.099	1.50	MS9733-28	1.875	1.065-1.125	2.96	MS9733-49	4.500	3.690-3.750	5.96
MS9733-08	.625	.079-.099	1.57	MS9733-29	2.000	1.190-1.250	3.12	MS9733-50	4.625	3.815-3.875	6.10
MS9733-09	.688	.079-.099	1.64	MS9733-30	2.125	1.315-1.375	3.27	MS9733-51	4.750	3.940-4.000	6.24
MS9733-10	.750	.079-.099	1.71	MS9733-31	2.250	1.440-1.500	3.41	MS9733-52	4.875	4.065-4.125	6.38
MS9733-11	.812	.079-.099	1.78	MS9733-32	2.375	1.565-1.625	3.55	MS9733-53	5.000	4.190-4.250	6.52
MS9733-12	.875	.079-.125	1.85	MS9733-33	2.500	1.690-1.750	3.69	MS9733-54	5.125	4.315-4.375	6.66
MS9733-13	.938	.128-.188	1.92	MS9733-34	2.625	1.815-1.875	3.83	MS9733-55	5.250	4.440-4.500	6.81
MS9733-14	1.000	.190-.250	1.99	MS9733-35	2.750	1.940-2.000	3.97	MS9733-56	5.375	4.565-4.625	6.95
MS9733-15	1.062	.252-.312	2.06	MS9733-36	2.875	2.065-2.125	4.12	MS9733-57	5.500	4.690-4.750	7.09
MS9733-16	1.125	.315-.375	2.13	MS9733-37	3.000	2.190-2.250	4.26	MS9733-58	5.625	4.815-4.875	7.23
MS9733-17	1.188	.378-.438	2.20	MS9733-38	3.125	2.315-2.375	4.40	MS9733-59	5.750	4.940-5.000	7.37
MS9733-18	1.250	.440-.500	2.27	MS9733-39	3.250	2.440-2.500	4.54	MS9733-60	5.875	5.065-5.125	7.51
MS9733-19	1.312	.502-.562	2.34	MS9733-40	3.375	2.565-2.625	4.68	MS9733-61	6.000	5.190-5.250	7.66
MS9733-20	1.375	.565-.625	2.42	MS9733-41	3.500	2.690-2.750	4.82				
MS9733-21	1.438	.628-.688	2.49	MS9733-42	3.625	2.815-2.875	4.96				
MS9733-22	1.500	.690-.750	2.56	MS9733-43	3.750	2.940-3.000	5.11				
MS9733-23	1.562	.752-.812	2.63	MS9733-44	3.875	3.065-3.125	5.25				
MS9733-24	1.625	.815-.875	2.70	MS9733-45	4.000	3.190-3.250	5.39				

- SHANK SHALL BE STRAIGHT WITHIN .003 PER INCH OF BOLT LENGTH
- THE RUNOUT OF THREAD PD IN RELATION TO THE SHANK SHALL BE WITHIN .006 FIR
- THE RUNOUT OF THE SHANK IN RELATION TO THE WASHER FACE DIAMETER AND DOUBLE HEXAGON OD SHALL BE WITHIN .007 FIR.
- INCOMPLETE THREADS NOT TO ENTER FILLET.
- MATERIAL. CRES AMS 5643.
- HARDNESS: ROCKWELL C32-38
- MANUFACTURING SPECIFICATION AMS 7474.
- FLUORESCENT PENETRANT INSPECTION PER AMS 2645.
- SURFACE TEXTURE. USAS B46.1-1962. UNLESS OTHERWISE SPECIFIED, SURFACES TO BE 125 MICROINCHES EXCEPT UPSET HEAD.
- BREAK SHARP EDGES .003-.015 UNLESS OTHERWISE SPECIFIED
- DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: LINEAR DIMENSIONS ±.010, ANGULAR DIMENSIONS ±5°.
- DO NOT USE UNASSIGNED PART NUMBERS.

AS & AMS ARE SOCIETY OF AUTOMOTIVE ENGINEERS, INC. PUBLICATIONS.

THIS STANDARD WAS DEVELOPED COOPERATIVELY WITH THE MILITARY SERVICES BY THE SAE AEROSPACE PART STANDARDS DIV.

P.A. USAF - 11	TITLE	MILITARY STANDARD
Other Cust	BOLT, MACHINE - DOUBLE HEXAGON EXTENDED	MS9733 (ASG)
Navy - AS	WASHER HEAD, PD SHANK, CRES AMS 5643, 250-28 UNJF-3A	
PROCUREMENT SPECIFICATION	SUPERSEDES	SHEET 1 OF 1

DD FORM 672-1 (Limited coordination)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

106 - FOLD

U. S. GOVERNMENT PRINTING OFFICE: 1969-341-510/A-5361

Review activities:
USAF - 82, 85

This military standard is approved by the Department of the Air Force and the Naval Air Systems Command and is mandatory for use by these activities. All other military activities are required to employ this standard where suitable.

REVISED
3 Mar 69
APPROVED