Downloaded from http://www.everyspec.com

FED. SUP CLASS
5315

MS9848 (ASG)



PART NO.	A	L	APPROX WEIGHT LB/100
MS9848-08	.617	.804	3.630
MS9848-09	.679	.866	3.870
MS9848-11	.741	.729	4.220
MS9848-12	.804	.791	4.870
MS9848-13	.767	.854	4.819
MS9848-14	.825	.916	5.256
MS9848-15	.892	.979	5.690
MS9848-16	.954	1.041	5.940
MS9848-17	1.017	1.104	6.290
MS9848-18	1.079	1.166	6.630
MS9848-19	1.142	1.229	6.880
MS9848-20	1.204	1.291	7.220
MS9848-21	1.267	1.354	7.870
MS9848-22	1.329	1.416	8.000
MS9848-23	1.392	1.479	8.270
MS9848-24	1.454	1.541	8.710
MS9848-25	1.517	1.604	9.050
MS9848-26	1.579	1.666	9.490
MS9848-27	1.642	1.729	9.750
MS9848-28	1.704	1.791	10.090
MS9848-29	1.767	1.854	10.440
MS9848-30	1.829	1.916	10.790
MS9848-31	1.892	1.979	11.120
MS9848-32	1.954	2.041	11.470
MS9848-33	2.017	2.104	11.820
MS9848-34	2.079	2.166	12.166
MS9848-35	2.142	2.229	12.490
MS9848-36	2.204	2.291	12.850
MS9848-37	2.267	2.354	13.200
MS9848-38	2.329	2.416	13.530
MS9848-39	2.392	2.479	13.890
MS9848-40	2.454	2.541	14.210
MS9848-41	2.517	2.604	14.580
MS9848-42	2.579	2.666	14.920
MS9848-43	2.642	2.729	15.220
MS9848-44	2.704	2.791	15.615
MS9848-45	2.767	2.854	15.960
MS9848-46	2.829	2.916	16.310
MS9848-47	2.892	2.979	16.630
MS9848-48	2.954	3.041	16.990
MS9848-49	3.017	3.104	17.340

Review activities: DLAY - 82, 85

This military standard is approved by the Department of the Air Force and the Bureau of Naval Weapons and is mandatory for use by those activities. All other military activities are required to apply this standard where suitable.

NOTES:
1. MATERIAL: AMS 5616.
2. HARDNESS: ROCKWELL C40-50.
3. FLUORESCENT PENETRANT INSPECTION PER AMS2645.
4. HEAD DIA TO BE CONCENTRIC WITH SHANK DIA, WITHIN .003 FIM.
5. SURFACE TEXTURE: ASA B46.1 1962, UNLESS OTHERWISE SPECIFIED, SURFACES TO BE 125 MICROINCHES.
6. BREAK SHARP EDGES .003-.015.
7. DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: LINEAR DIMENSIONS ±.010, ANGULAR DIMENSIONS ±1°
8. DO NOT USE UNASSIGNED PART NUMBERS.

AS & AMS ARE SOCIETY OF AUTOMOTIVE ENGINEERS, INC. PUBLICATIONS.
THIS STANDARD WAS DEVELOPED COOPERATIVELY WITH THE MILITARY SERVICES BY THE SAE AEROSPACE PROPULSION DIVISION.

APPROVED 29 Feb 68 REVISED

P.A. USAF - 11	TITLE	MILITARY STANDARD
Other Cust NAVY - AS	PIN, STRAIGHT, HEADED .4999 DIAMETER, AMS5616	MS9848 (ASG)
PROCUREMENT SPECIFICATION NONE	SUPERSEDES	SHEET 1 OF 1

DD FORM 672-1 (Related coordinate) ASG use only

★ U.S. GOVERNMENT PRINTING OFFICE: 1968-310-845/4