

MS9926 (ASG)				FED. SUP CLASS 5306																																																																																																																																																																																																																																																			
				<p>1. SHANK SHALL BE STRAIGHT WITHIN .0025 PER INCH OF BOLT LENGTH.</p> <p>2. THE CONCENTRICITY OF THREAD PD IN RELATION TO THE SHANK SHALL BE WITHIN .006 FIR.</p> <p>3. THE CONCENTRICITY OF THE SHANK IN RELATION TO THE WASHER FACE DIAMETER AND DOUBLE HEXAGON OD SHALL BE WITHIN .009 FIR.</p> <p>4. INCOMPLETE THREADS NOT TO ENTER FILLET.</p> <p>5. MATERIAL: STEEL AMS 6322.</p> <p>6. HARDNESS: ROCKWELL C26-32.</p> <p>7. FINISH: CADMIUM PLATE AMS 2400. DIMENSIONS SPECIFIED ARE AFTER PLATING.</p> <p>8. MANUFACTURING SPECIFICATION: AMS 7452 EXCEPT HEAD SHALL BE UPSET.</p> <p>9. HEAD TO SHANK FILLET SHALL BE COLD WORKED.</p> <p>10. MAGNETIC PARTICLE INSPECTION PER AMS 2640 AFTER PLATING.</p> <p>11. SURFACE TEXTURE: USAS B46.1-1962. UNLESS OTHERWISE SPECIFIED, SURFACES TO BE 125 MICROINCHES EXCEPT UPSET HEAD.</p> <p>12. BREAK SHARP EDGES .003-.015 UNLESS OTHERWISE SPECIFIED.</p> <p>13. DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: LINEAR DIMENSIONS <math>\pm .010</math>, ANGULAR DIMENSIONS <math>\pm 5^\circ</math>.</p> <p>14. DO NOT USE UNASSIGNED PART NUMBERS.</p>																																																																																																																																																																																																																																																			
<table border="1"> <thead> <tr> <th>PART NO.</th> <th>L</th> <th>K</th> <th>APPROX WEIGHT LB/100</th> </tr> </thead> <tbody> <tr><td>MS9926-03</td><td>.562</td><td>.088-.108</td><td>3.17</td></tr> <tr><td>MS9926-04</td><td>.625</td><td>.088-.108</td><td>3.34</td></tr> <tr><td>MS9926-05</td><td>.688</td><td>.088-.108</td><td>3.51</td></tr> <tr><td>MS9926-06</td><td>.750</td><td>.088-.108</td><td>3.68</td></tr> <tr><td>MS9926-07</td><td>.812</td><td>.088-.108</td><td>3.84</td></tr> <tr><td>MS9926-08</td><td>.875</td><td>.088-.108</td><td>4.01</td></tr> <tr><td>MS9926-09</td><td>.938</td><td>.088-.108</td><td>4.18</td></tr> <tr><td>MS9926-10</td><td>1.000</td><td>.088-.108</td><td>4.35</td></tr> <tr><td>MS9926-11</td><td>1.062</td><td>.088-.108</td><td>4.51</td></tr> <tr><td>MS9926-12</td><td>1.125</td><td>.088-.125</td><td>4.68</td></tr> <tr><td>MS9926-13</td><td>1.188</td><td>.128-.188</td><td>4.85</td></tr> <tr><td>MS9926-14</td><td>1.250</td><td>.190-.250</td><td>5.02</td></tr> <tr><td>MS9926-15</td><td>1.312</td><td>.252-.312</td><td>5.18</td></tr> <tr><td>MS9926-16</td><td>1.375</td><td>.315-.375</td><td>5.35</td></tr> <tr><td>MS9926-17</td><td>1.438</td><td>.378-.438</td><td>5.52</td></tr> <tr><td>MS9926-18</td><td>1.500</td><td>.440-.500</td><td>5.69</td></tr> <tr><td>MS9926-19</td><td>1.562</td><td>.502-.562</td><td>5.87</td></tr> <tr><td>MS9926-20</td><td>1.625</td><td>.565-.625</td><td>6.03</td></tr> <tr><td>MS9926-21</td><td>1.688</td><td>.628-.688</td><td>6.23</td></tr> <tr><td>MS9926-22</td><td>1.750</td><td>.690-.750</td><td>6.36</td></tr> <tr><td>MS9926-23</td><td>1.812</td><td>.752-.812</td><td>6.53</td></tr> <tr><td>MS9926-24</td><td>1.875</td><td>.815-.875</td><td>6.70</td></tr> </tbody> </table>				PART NO.	L	K	APPROX WEIGHT LB/100	MS9926-03	.562	.088-.108	3.17	MS9926-04	.625	.088-.108	3.34	MS9926-05	.688	.088-.108	3.51	MS9926-06	.750	.088-.108	3.68	MS9926-07	.812	.088-.108	3.84	MS9926-08	.875	.088-.108	4.01	MS9926-09	.938	.088-.108	4.18	MS9926-10	1.000	.088-.108	4.35	MS9926-11	1.062	.088-.108	4.51	MS9926-12	1.125	.088-.125	4.68	MS9926-13	1.188	.128-.188	4.85	MS9926-14	1.250	.190-.250	5.02	MS9926-15	1.312	.252-.312	5.18	MS9926-16	1.375	.315-.375	5.35	MS9926-17	1.438	.378-.438	5.52	MS9926-18	1.500	.440-.500	5.69	MS9926-19	1.562	.502-.562	5.87	MS9926-20	1.625	.565-.625	6.03	MS9926-21	1.688	.628-.688	6.23	MS9926-22	1.750	.690-.750	6.36	MS9926-23	1.812	.752-.812	6.53	MS9926-24	1.875	.815-.875	6.70	<table border="1"> <thead> <tr> <th>PART NO.</th> <th>L</th> <th>K</th> <th>APPROX WEIGHT LB/100</th> </tr> </thead> <tbody> <tr><td>MS9926-25</td><td>1.938</td><td>.878-.938</td><td>6.70</td></tr> <tr><td>MS9926-26</td><td>2.000</td><td>.940-1.000</td><td>7.04</td></tr> <tr><td>MS9926-27</td><td>2.125</td><td>1.065-1.125</td><td>7.37</td></tr> <tr><td>MS9926-28</td><td>2.250</td><td>1.190-1.250</td><td>7.71</td></tr> <tr><td>MS9926-29</td><td>2.375</td><td>1.315-1.375</td><td>8.04</td></tr> <tr><td>MS9926-30</td><td>2.500</td><td>1.440-1.500</td><td>8.37</td></tr> <tr><td>MS9926-31</td><td>2.625</td><td>1.565-1.625</td><td>8.71</td></tr> <tr><td>MS9926-32</td><td>2.750</td><td>1.690-1.750</td><td>9.05</td></tr> <tr><td>MS9926-33</td><td>2.875</td><td>1.815-1.875</td><td>9.38</td></tr> <tr><td>MS9926-34</td><td>3.000</td><td>1.940-2.000</td><td>9.72</td></tr> <tr><td>MS9926-35</td><td>3.125</td><td>2.065-2.125</td><td>10.05</td></tr> <tr><td>MS9926-36</td><td>3.250</td><td>2.190-2.250</td><td>10.39</td></tr> <tr><td>MS9926-37</td><td>3.375</td><td>2.315-2.375</td><td>10.73</td></tr> <tr><td>MS9926-38</td><td>3.500</td><td>2.440-2.500</td><td>11.06</td></tr> <tr><td>MS9926-39</td><td>3.625</td><td>2.565-2.625</td><td>11.40</td></tr> <tr><td>MS9926-40</td><td>3.750</td><td>2.690-2.750</td><td>11.73</td></tr> <tr><td>MS9926-41</td><td>3.875</td><td>2.815-2.875</td><td>12.07</td></tr> <tr><td>MS9926-42</td><td>4.000</td><td>2.940-3.000</td><td>12.40</td></tr> <tr><td>MS9926-43</td><td>4.125</td><td>3.065-3.125</td><td>12.74</td></tr> <tr><td>MS9926-44</td><td>4.250</td><td>3.190-3.250</td><td>13.07</td></tr> <tr><td>MS9926-45</td><td>4.375</td><td>3.315-3.375</td><td>13.41</td></tr> </tbody> </table>				PART NO.	L	K	APPROX WEIGHT LB/100	MS9926-25	1.938	.878-.938	6.70	MS9926-26	2.000	.940-1.000	7.04	MS9926-27	2.125	1.065-1.125	7.37	MS9926-28	2.250	1.190-1.250	7.71	MS9926-29	2.375	1.315-1.375	8.04	MS9926-30	2.500	1.440-1.500	8.37	MS9926-31	2.625	1.565-1.625	8.71	MS9926-32	2.750	1.690-1.750	9.05	MS9926-33	2.875	1.815-1.875	9.38	MS9926-34	3.000	1.940-2.000	9.72	MS9926-35	3.125	2.065-2.125	10.05	MS9926-36	3.250	2.190-2.250	10.39	MS9926-37	3.375	2.315-2.375	10.73	MS9926-38	3.500	2.440-2.500	11.06	MS9926-39	3.625	2.565-2.625	11.40	MS9926-40	3.750	2.690-2.750	11.73	MS9926-41	3.875	2.815-2.875	12.07	MS9926-42	4.000	2.940-3.000	12.40	MS9926-43	4.125	3.065-3.125	12.74	MS9926-44	4.250	3.190-3.250	13.07	MS9926-45	4.375	3.315-3.375	13.41	<table border="1"> <thead> <tr> <th>PART NO.</th> <th>L</th> <th>K</th> <th>APPROX WEIGHT LB/100</th> </tr> </thead> <tbody> <tr><td>MS9926-46</td><td>4.500</td><td>3.440-3.500</td><td>13.74</td></tr> <tr><td>MS9926-47</td><td>4.625</td><td>3.565-3.625</td><td>14.08</td></tr> <tr><td>MS9926-48</td><td>4.750</td><td>3.690-3.750</td><td>14.42</td></tr> <tr><td>MS9926-49</td><td>4.875</td><td>3.815-3.875</td><td>14.75</td></tr> <tr><td>MS9926-50</td><td>5.000</td><td>3.940-4.000</td><td>15.09</td></tr> <tr><td>MS9926-51</td><td>5.125</td><td>4.065-4.125</td><td>15.42</td></tr> <tr><td>MS9926-52</td><td>5.250</td><td>4.190-4.250</td><td>15.76</td></tr> <tr><td>MS9926-53</td><td>5.375</td><td>4.315-4.375</td><td>16.10</td></tr> <tr><td>MS9926-54</td><td>5.500</td><td>4.440-4.500</td><td>16.43</td></tr> <tr><td>MS9926-55</td><td>5.625</td><td>4.565-4.625</td><td>16.77</td></tr> <tr><td>MS9926-56</td><td>5.750</td><td>4.690-4.750</td><td>17.10</td></tr> <tr><td>MS9926-57</td><td>5.875</td><td>4.815-4.875</td><td>17.44</td></tr> <tr><td>MS9926-58</td><td>6.000</td><td>4.940-5.000</td><td>17.77</td></tr> </tbody> </table>				PART NO.	L	K	APPROX WEIGHT LB/100	MS9926-46	4.500	3.440-3.500	13.74	MS9926-47	4.625	3.565-3.625	14.08	MS9926-48	4.750	3.690-3.750	14.42	MS9926-49	4.875	3.815-3.875	14.75	MS9926-50	5.000	3.940-4.000	15.09	MS9926-51	5.125	4.065-4.125	15.42	MS9926-52	5.250	4.190-4.250	15.76	MS9926-53	5.375	4.315-4.375	16.10	MS9926-54	5.500	4.440-4.500	16.43	MS9926-55	5.625	4.565-4.625	16.77	MS9926-56	5.750	4.690-4.750	17.10	MS9926-57	5.875	4.815-4.875	17.44	MS9926-58	6.000	4.940-5.000	17.77
PART NO.	L	K	APPROX WEIGHT LB/100																																																																																																																																																																																																																																																				
MS9926-03	.562	.088-.108	3.17																																																																																																																																																																																																																																																				
MS9926-04	.625	.088-.108	3.34																																																																																																																																																																																																																																																				
MS9926-05	.688	.088-.108	3.51																																																																																																																																																																																																																																																				
MS9926-06	.750	.088-.108	3.68																																																																																																																																																																																																																																																				
MS9926-07	.812	.088-.108	3.84																																																																																																																																																																																																																																																				
MS9926-08	.875	.088-.108	4.01																																																																																																																																																																																																																																																				
MS9926-09	.938	.088-.108	4.18																																																																																																																																																																																																																																																				
MS9926-10	1.000	.088-.108	4.35																																																																																																																																																																																																																																																				
MS9926-11	1.062	.088-.108	4.51																																																																																																																																																																																																																																																				
MS9926-12	1.125	.088-.125	4.68																																																																																																																																																																																																																																																				
MS9926-13	1.188	.128-.188	4.85																																																																																																																																																																																																																																																				
MS9926-14	1.250	.190-.250	5.02																																																																																																																																																																																																																																																				
MS9926-15	1.312	.252-.312	5.18																																																																																																																																																																																																																																																				
MS9926-16	1.375	.315-.375	5.35																																																																																																																																																																																																																																																				
MS9926-17	1.438	.378-.438	5.52																																																																																																																																																																																																																																																				
MS9926-18	1.500	.440-.500	5.69																																																																																																																																																																																																																																																				
MS9926-19	1.562	.502-.562	5.87																																																																																																																																																																																																																																																				
MS9926-20	1.625	.565-.625	6.03																																																																																																																																																																																																																																																				
MS9926-21	1.688	.628-.688	6.23																																																																																																																																																																																																																																																				
MS9926-22	1.750	.690-.750	6.36																																																																																																																																																																																																																																																				
MS9926-23	1.812	.752-.812	6.53																																																																																																																																																																																																																																																				
MS9926-24	1.875	.815-.875	6.70																																																																																																																																																																																																																																																				
PART NO.	L	K	APPROX WEIGHT LB/100																																																																																																																																																																																																																																																				
MS9926-25	1.938	.878-.938	6.70																																																																																																																																																																																																																																																				
MS9926-26	2.000	.940-1.000	7.04																																																																																																																																																																																																																																																				
MS9926-27	2.125	1.065-1.125	7.37																																																																																																																																																																																																																																																				
MS9926-28	2.250	1.190-1.250	7.71																																																																																																																																																																																																																																																				
MS9926-29	2.375	1.315-1.375	8.04																																																																																																																																																																																																																																																				
MS9926-30	2.500	1.440-1.500	8.37																																																																																																																																																																																																																																																				
MS9926-31	2.625	1.565-1.625	8.71																																																																																																																																																																																																																																																				
MS9926-32	2.750	1.690-1.750	9.05																																																																																																																																																																																																																																																				
MS9926-33	2.875	1.815-1.875	9.38																																																																																																																																																																																																																																																				
MS9926-34	3.000	1.940-2.000	9.72																																																																																																																																																																																																																																																				
MS9926-35	3.125	2.065-2.125	10.05																																																																																																																																																																																																																																																				
MS9926-36	3.250	2.190-2.250	10.39																																																																																																																																																																																																																																																				
MS9926-37	3.375	2.315-2.375	10.73																																																																																																																																																																																																																																																				
MS9926-38	3.500	2.440-2.500	11.06																																																																																																																																																																																																																																																				
MS9926-39	3.625	2.565-2.625	11.40																																																																																																																																																																																																																																																				
MS9926-40	3.750	2.690-2.750	11.73																																																																																																																																																																																																																																																				
MS9926-41	3.875	2.815-2.875	12.07																																																																																																																																																																																																																																																				
MS9926-42	4.000	2.940-3.000	12.40																																																																																																																																																																																																																																																				
MS9926-43	4.125	3.065-3.125	12.74																																																																																																																																																																																																																																																				
MS9926-44	4.250	3.190-3.250	13.07																																																																																																																																																																																																																																																				
MS9926-45	4.375	3.315-3.375	13.41																																																																																																																																																																																																																																																				
PART NO.	L	K	APPROX WEIGHT LB/100																																																																																																																																																																																																																																																				
MS9926-46	4.500	3.440-3.500	13.74																																																																																																																																																																																																																																																				
MS9926-47	4.625	3.565-3.625	14.08																																																																																																																																																																																																																																																				
MS9926-48	4.750	3.690-3.750	14.42																																																																																																																																																																																																																																																				
MS9926-49	4.875	3.815-3.875	14.75																																																																																																																																																																																																																																																				
MS9926-50	5.000	3.940-4.000	15.09																																																																																																																																																																																																																																																				
MS9926-51	5.125	4.065-4.125	15.42																																																																																																																																																																																																																																																				
MS9926-52	5.250	4.190-4.250	15.76																																																																																																																																																																																																																																																				
MS9926-53	5.375	4.315-4.375	16.10																																																																																																																																																																																																																																																				
MS9926-54	5.500	4.440-4.500	16.43																																																																																																																																																																																																																																																				
MS9926-55	5.625	4.565-4.625	16.77																																																																																																																																																																																																																																																				
MS9926-56	5.750	4.690-4.750	17.10																																																																																																																																																																																																																																																				
MS9926-57	5.875	4.815-4.875	17.44																																																																																																																																																																																																																																																				
MS9926-58	6.000	4.940-5.000	17.77																																																																																																																																																																																																																																																				
<p>AS &amp; AMS ARE SOCIETY OF AUTOMOTIVE ENGINEERS, INC. PUBLICATIONS.</p> <p>THIS STANDARD WAS DEVELOPED COOPERATIVELY WITH THE MILITARY SERVICES BY THE SAIC AEROSPACE PART STANDARDS DIVISION.</p>				<p>APPROVED 15 Aug 69 REVISED</p>																																																																																																																																																																																																																																																			
<p>P.A. USAF - 11</p> <p>Other Cust</p> <p>Navy - AS</p>		<p>TITLE</p> <p>BOLT, MACHINE - DOUBLE HEXAGON EXTENDED WASHER HEAD, DRILLED, PD SHANK, STEEL AMS 6322, CADMIUM PLATED, .375-24 UNF-3A</p>		<p>MILITARY STANDARD</p> <p>MS9926 (ASG)</p>																																																																																																																																																																																																																																																			
<p>PROCUREMENT SPECIFICATION</p> <p>NONE</p>		<p>SUPERSEDES</p>		<p>SHEET 1 OF 1</p>																																																																																																																																																																																																																																																			

Review activities:  
USAF - 02, 05

This military standard is approved by the Department of the Air Force and the Bureau of Naval Weapons and is mandatory for use by these activities. All other military activities are required to employ this standard where suitable.

DD FORM 672-1 (Limited coordination)  
ASG use only

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

☆ U. S. GOVERNMENT PRINTING OFFICE: 1969-393-065/5-1795