



National Aeronautics and  
Space Administration

**MEASUREMENT  
SYSTEM  
IDENTIFICATION**

MSFC-SPEC-164

REVISION: D

EFFECTIVE DATE: January 30, 2014

---

**George C. Marshall Space Flight Center**  
Marshall Space Flight Center, Alabama 35812

EM50

MSFC TECHNICAL STANDARD

**CLEANLINESS OF COMPONENTS  
FOR USE IN OXYGEN, FUEL, AND  
PNEUMATIC SYSTEMS,  
SPECIFICATION FOR**

**Approved for Public Release; Distribution is Unlimited**

CHECK THE MASTER LIST—VERIFY THAT THIS IS THE CORRECT VERSION BEFORE USE  
<https://repository.msfc.nasa.gov/docs/multiprogram/MSFC-SPEC-164D>

<b>MSFC Technical Standard EM50</b>		
<b>Title:</b> Cleanliness of Components for Use in Oxygen, Fuel, and Pneumatic Systems, Specification for	<b>Document No.:</b> MSFC-SPEC-164	<b>Revision:</b> D
	<b>Effective Date:</b> January 30, 2014	<b>Page</b> 2 of 27

### DOCUMENT HISTORY LOG

Status (Baseline/ Revision/ Canceled)	Document Revision	Effective Date	Description
Baseline		04/16/1962	Initial Release
Revision	A	10/01/1970	
Revision	B	11/19/1994	
Revision	C	03/01/2010	Complete revision for Constellation and future projects. Will not be imposed on Space Shuttle or International Space Station.
Revision	D	01/30/2014	<p>Revision D release was authorized by the MSFC Technical Standards Document Control Board (DCB) through the Multiprogram Document Management System (MPDMS).</p> <ol style="list-style-type: none"> <li>1) Revise Table I and revise the "default" Table II cleanliness to reflect current practice and understanding of oxygen system particle impact ignition.</li> <li>2) Remove obsolete references to Space Shuttle and Constellation documents and requirements.</li> <li>3) Reduce the required levels of solvent for sampling and lower NVR background requirements to reflect current industry practice and minimize solvent use and processing time.</li> <li>4) Clarify sections on cleanliness testing, packaging, and qualification of alternative test methods.</li> </ol>

<b>MSFC Technical Standard EM50</b>		
<b>Title:</b> Cleanliness of Components for Use in Oxygen, Fuel, and Pneumatic Systems, Specification for	<b>Document No.:</b> MSFC-SPEC-164	<b>Revision:</b> D
	<b>Effective Date:</b> January 30, 2014	<b>Page</b> 3 of 27

## TABLE OF CONTENTS

<b><u>PARAGRAPH</u></b>	<b><u>PAGE</u></b>
<b>1. SCOPE</b>	<b>6</b>
1.1 Cleanliness Levels	6
1.2 Alternate Procedures	6
1.3 Alternate Cleanliness Levels	6
<b>2. APPLICABLE DOCUMENTS</b>	<b>8</b>
2.1 Government	8
2.1.1 Specifications	8
2.1.2 Standards	8
2.1.3 Procedures	8
2.2 Industry	8
<b>3. REQUIREMENTS</b>	<b>9</b>
3.1 General	9
3.2 Cleaning	9
3.2.1 Pre-Cleaning	9
3.2.2 Inspection Prior to Precision Cleaning	9
3.2.3 Precision Cleaning	9
3.2.4 Process Approval	10
3.2.5 Materials	11
3.2.6 Final Rinsing Solution	12
3.3 Detailed Product Cleanliness Requirements	12
3.3.1 Use of Alternate Acceptance Criteria	12
3.3.2 Visual Cleanliness	13
3.3.3 Acidity or Alkalinity	13
3.3.4 Nonvolatile Residue	13
3.3.5 Particulate Contamination	13
3.3.6 Silting	13
3.4 Drying	14
3.4.1 Procedure	14
3.4.2 Drying and Purging Gases	14

<b>MSFC Technical Standard EM50</b>		
<b>Title:</b> Cleanliness of Components for Use in Oxygen, Fuel, and Pneumatic Systems, Specification for	<b>Document No.:</b> MSFC-SPEC-164	<b>Revision:</b> D
	<b>Effective Date:</b> January 30, 2014	<b>Page</b> 4 of 27

3.5 Post-Verification Operations	14
3.6 “Excepted” Components	14
3.7 Field Cleaning	15
3.7.1 Field Cleaning Process Requirements	15
3.8 Ground Test Systems	15
3.8.1 Oxygen Ground Test Systems Operating at 5000 psig or Greater	15
3.8.2 Oxygen Ground Test Systems Operating at Less than 5000 psig	15
<b>4. VERIFICATION</b>	<b>16</b>
4.1 Responsibility for Inspection	16
4.2 Inspection Sample Size/Frequency	16
4.2.1 Visual Inspection	16
4.2.2 Acidity/Alkalinity	16
4.2.3 Particulate/NVR Sample	16
4.2.4 Drying Sample	17
4.3 Acceptance Inspection Procedures	18
4.3.1 Visual Inspection	18
4.3.2 Acidity/Alkalinity Evaluation	18
4.3.3 Particle/NVR Cleanliness Tests	18
4.3.4 Drying Test	20
4.4 Rejection	21
<b>5. PACKAGING</b>	<b>21</b>
5.1 Packaging of Components	21
5.1.1 Application of Tape	21
5.1.2 Packaging of Fluid Line Connections	21
5.1.3 Outer bags	22
5.1.4 Inert Storage Package	22
5.1.5 Prevention of Damage	22
5.1.6 Moisture Barrier	22
5.1.7 Other Packaging Methods	22
5.1.8 Environmental Requirements for Packaging	22
5.1.9 Use of Desiccants	22
5.2 Protection of Tanks and Containers	22
5.3 Packaging Materials	23

<b>MSFC Technical Standard EM50</b>		
<b>Title:</b> Cleanliness of Components for Use in Oxygen, Fuel, and Pneumatic Systems, Specification for	<b>Document No.:</b> MSFC-SPEC-164	<b>Revision:</b> D
	<b>Effective Date:</b> January 30, 2014	<b>Page</b> 5 of 27

5.3.1 Protective Materials and Devices	23
5.3.2 Tape	23
5.3.3 Desiccants	23
5.4 Marking/Identification	23
<b>6. NOTES</b>	<b>24</b>
6.1 Approval of Alternate Verification Procedures	24
6.1.1 Sample Selection	24
6.1.2 Qualification Test for Alternate Verification Test Methods	24
<b>APPENDIX A - ACRONYMS</b>	<b>25</b>
<b>APPENDIX B - DEFINITIONS</b>	<b>26</b>
<b>LIST OF TABLES</b>	
<b>Table I: Classification of Cleanliness .....</b>	<b>7</b>
<b>Table II: Product Cleanliness Requirements .....</b>	<b>10</b>

<b>MSFC Technical Standard EM50</b>		
<b>Title:</b> Cleanliness of Components for Use in Oxygen, Fuel, and Pneumatic Systems, Specification for	<b>Document No.:</b> MSFC-SPEC-164	<b>Revision:</b> D
	<b>Effective Date:</b> January 30, 2014	<b>Page</b> 6 of 27

## 1. SCOPE

This specification establishes surface cleanliness requirements for oxygen, fuel, and pneumatic components used in space vehicle fluid systems and associated ground support equipment (GSE) and test facilities. This specification is not intended to specify cleanliness requirements for composite surfaces used in cryogenic service, but it may be used to specify internal cleanliness requirements for metal-lined composite over-wrapped pressure vessels (COPVs). General cleaning requirements, verification procedures, drying and packaging requirements are provided. Each user shall require sub-tier documents to address processing, system cleanliness, solvent selection, cleanliness verification, and maintenance. An engineering assessment shall be necessary to establish requirements for each system.

### 1.1 Cleanliness Levels

Cleanliness levels for particulate and nonvolatile residue (NVR) are listed in Table 1. Unless otherwise specified, the minimum cleanliness levels for new or re-cleaned systems, subsystems and components are specified in paragraph 3.2 and Table II.

### 1.2 Alternate Procedures

Methods and procedures other than those enumerated in this document may be utilized with prior approval of the NASA procuring activity.

### 1.3 Alternate Cleanliness Levels

For system performance or safety, some propulsion systems, such as hypergolic systems, may require cleanliness levels more stringent than those defined in Table I. When cleanliness levels more stringent than those shown in Table 1 are required, they may be specified on the engineering drawing or specification in accordance with IEST-STD-CC1246, or particulate levels tailored from IEST-STD-CC1246; with cleaning, inspection, and packaging in accordance with this document. When a cleanliness level is required that cannot be defined by one of these specifications, the cleanliness requirement may be explicitly specified on the engineering drawing or specification as a custom cleanliness level. The custom cleanliness level shall state the maximum number of particles allowed per 0.1 m<sup>2</sup> in defined particle size ranges.

<b>MSFC Technical Standard EM50</b>		
<b>Title:</b> Cleanliness of Components for Use in Oxygen, Fuel, and Pneumatic Systems, Specification for	<b>Document No.:</b> MSFC-SPEC-164	<b>Revision:</b> D
	<b>Effective Date:</b> January 30, 2014	<b>Page</b> 7 of 27

**Table I: Classification of Cleanliness**

<u><b>PARTICULATE LEVELS</b></u>		
<u><b>CLASS</b></u>	<u><b>PARTICLE SIZE IN MICRONS</b></u>	<u><b>MAX. NUMBER PER 0.1 m<sup>2</sup></b></u>
I	OBSOLETE	OBSOLETE
II	>1000 700<x≤1000 175<x≤700 NO SILTING	0 40 150
III	>800 NO SILTING	0
III X	>800 175<X≤800 NO SILTING	0 5
IV	>400 NO SILTING	0
IV X	>400 175<x≤400 NO SILTING	0 5
V	VISUALLY CLEAN/NO SILTING	
<u><b>NVR LEVELS</b></u>		
<u><b>LEVEL</b></u>	<u><b>MAXIMUM mg/0.1 m<sup>2</sup></b></u>	
A	1	
B	5	

**NOTE:** For the purpose of this specification 0.1 square meter = 1 square foot.

<b>MSFC Technical Standard EM50</b>		
<b>Title:</b> Cleanliness of Components for Use in Oxygen, Fuel, and Pneumatic Systems, Specification for	<b>Document No.:</b> MSFC-SPEC-164	<b>Revision:</b> D
	<b>Effective Date:</b> January 30, 2014	<b>Page</b> 8 of 27

## 2. APPLICABLE DOCUMENTS

Unless otherwise noted the latest revision of the following documents are applicable to the extent specified herein. In the event of a conflict between the documents referenced herein and the contents of this specification, the content of this specification shall take precedence. Equivalent grades of chemicals may be used upon approval from the NASA procuring activity.

### 2.1 Government

#### 2.1.1 Specifications

MIL-D-3464, Desiccants, Activated, Bagged, Packaging Use and Static Dehumidification

MIL-PRF-27401, Propellant Pressurizing Agent, Nitrogen

#### 2.1.2 Standards

MIL-STD-129, Military Marking for Shipment and Storage

MSFC-STD-246, Standard Design and Operational Criteria for Controlled Environmental Areas

MSFC-STD-3535, Standard for Propellants and Pressurants used for Test and Test Support Activities at SSC and MSFC

#### 2.1.3 Procedures

MSFC-PROC-1832, Sampling and Analysis of Nonvolatile Residue Content on Critical Surfaces

### 2.2 Industry

AMS 3647, Film and Sheet, Polyfluoroethylenepropylene (PFEP)

ASTM E 1216, Standard Practice for Sampling for Particulate Contamination by Tape Lift

ASTM F 303, Standard Practices for Sampling Aerospace Fluids from Components

ASTM F 311, Standard Practice for Processing Aerospace Liquid Samples for Particulate Contamination Analysis Using Membrane Filters

ASTM F 312, Standard Methods for Microscopical Sizing and Counting Particles from Aerospace Fluids on Membrane Filters



<b>MSFC Technical Standard EM50</b>		
<b>Title:</b> Cleanliness of Components for Use in Oxygen, Fuel, and Pneumatic Systems, Specification for	<b>Document No.:</b> MSFC-SPEC-164	<b>Revision:</b> D
	<b>Effective Date:</b> January 30, 2014	<b>Page</b> 9 of 27

ASTM F 331, Standard Test Method for Nonvolatile Residue of Solvent Extract from Aerospace Components (Using Flash Evaporator)

ASTM Manual 36, Oxygen System Design, Materials Selection, Operations, Storage and Transportation

IEST-STD-CC1246, Product Cleanliness Levels and Contamination Control Program

### 3. REQUIREMENTS

#### 3.1 General

All parts, components, assemblies, systems or related equipment for use in space vehicles and related Ground Support Equipment (GSE) and test facility equipment shall be cleaned, inspected, and packaged in accordance with this specification. Assembled parts which may be damaged during the cleaning operation shall be disassembled to a level to permit cleaning. Designs for systems and system components should, where practical, include the capability to remove all valves and components from the system for precision cleaning.

**SAFETY PRECAUTION** – It is the responsibility of all users of this specification to review pertinent Materials Safety Data Sheets (MSDS's) and materials specifications to assure safety of personnel and protection of the environment and facilities in fulfilling the requirements of this document.

#### 3.2 Cleaning

##### 3.2.1 Pre-Cleaning

All significant surfaces of system hardware shall be pre-cleaned to remove dirt, grit, scale, corrosion, grease, oil and other foreign matter prior to any final precision cleaning process. Metallic items shall be surface treated (cleaned, passivated, and/or coated), as applicable, to prevent latent corrosion and contamination. Assembled items that do not lend themselves to this type of treatment shall be treated prior to assembly. Surface treated areas degraded during subsequent fabrication and assembly shall be reprocessed, as required, to restore the original protective finish.

##### 3.2.2 Inspection Prior to Precision Cleaning

Significant surfaces of system hardware which have been pre-cleaned shall be visually free of dirt, grit, scale, corrosion, grease, oil, and foreign objects prior to proceeding to any precision cleaning operation. Scale-free discoloration due to welding or passivation is permitted.

##### 3.2.3 Precision Cleaning

All significant hardware surfaces shall be precision cleaned to meet the cleanliness levels of Table II or as specified on the engineering drawing or component specification. Precision

CHECK THE MASTER LIST VERIFY THAT THIS IS THE CORRECT VERSION BEFORE USE  
<https://repository.msfc.nasa.gov/docs/multiprogram/MSFC-SPEC-164D>

<b>MSFC Technical Standard EM50</b>		
<b>Title:</b> Cleanliness of Components for Use in Oxygen, Fuel, and Pneumatic Systems, Specification for	<b>Document No.:</b> MSFC-SPEC-164	<b>Revision:</b> D
	<b>Effective Date:</b> January 30, 2014	<b>Page</b> 10 of 27

cleaning operations shall be performed in an environment compatible with the component cleanliness requirements to preclude adverse effect on the functional performance. Exemptions may be requested for hardware which due to size or other considerations cannot meet this requirement. As a minimum, cleaning shall be performed in an environment that does not adversely affect the function of the hardware. Cleaning and verification of components to cleanliness levels specifying limits on particles smaller than 150 microns shall be performed under High Efficiency Particulate Air (HEPA) filtered conditions. Reference MSFC-STD-246 for information on HEPA filtration and clean work area facilities. Precision-cleaned articles shall be packaged per Section 5 immediately after verification and drying operations or suitably protected prior to leaving the controlled environment.

**Table II: Product Cleanliness Requirements**

<u>System</u>	<u>Cleanliness Level</u>
LO2/GO2 Systems	
Metallic & Fluorocarbon Components	III A
Metallic Vessels	II B
Non-metallic (except Fluorocarbons)	V
Fuel Systems	
Metallic & Fluorocarbon Components	IV
Metallic Vessels	II
Non-metallic (except Fluorocarbons)	V
Pneumatic and Pressurant Systems (minimum)	
Metallic & Fluorocarbon Components	
Interfacing with Fuel Systems	IV
Interfacing with Oxygen Systems	III A
Metallic Vessels (with downstream interface filter)	
Interfacing with Fuel Systems	II
Interfacing with Oxygen Systems	II A
Non-metallic (except Fluorocarbons)	V

### 3.2.4 Process Approval

Cleaning processes except as noted in 3.2.5 shall be left to the discretion of the user, however, the process shall not be detrimental to hardware being cleaned and process approval shall be obtained from the NASA procuring activity prior to cleaning and handling.

3.2.4.1 To obtain approval, the contractor shall submit to the procuring activity the following information:

<b>MSFC Technical Standard EM50</b>		
<b>Title:</b> Cleanliness of Components for Use in Oxygen, Fuel, and Pneumatic Systems, Specification for	<b>Document No.:</b> MSFC-SPEC-164	<b>Revision:</b> D
	<b>Effective Date:</b> January 30, 2014	<b>Page</b> 11 of 27

- a. Cleanliness levels to be achieved, which shall meet or exceed those specified on the engineering drawing or specification. If the cleanliness level is not specified on the engineering drawing or documentation, the proposed cleanliness level shall be specified in the process document, including analysis and rationale for the selected cleanliness level.
- b. Description of items to be cleaned including identification of materials.
- c. Processing materials, to include as applicable, trade names, specifications, chemical and physical properties, and compatibility information as specified in 3.2.5.
- d. Processing equipment and cleaning procedures to be used.
- e. Quality assurance provisions to be utilized. This shall include in-process control procedures to prevent contamination, latent corrosion, or other degradation of surfaces and opened systems or vessels; and procedures to perform inspections and verify test results.
- f. Controlled environment levels to be maintained for cleaning and handling. MSFC-STD-246 shall be used to evaluate applicable areas.
- g. Packaging methods and materials.
- h. Verification methods and materials.

3.2.4.2. Cleaning processes to be performed on-site at MSFC or MAF shall be reviewed by MSFC Occupational Health Services.

**NOTE:** Documentation from all subcontractors shall be maintained and made available for review by the Government.

### **3.2.5 Materials**

Selection of materials used in processing and verification testing is left to the discretion of the user; however, the fluids shall be compatible with the item being cleaned and capable of removing the most probable contaminants.

3.2.5.1 The following compatibility issues, as applicable, shall be considered and evaluated in the selection of processing materials.

- a. Corrosion
- b. Stress corrosion cracking
- c. Embrittlement
- d. Leaching

<b>MSFC Technical Standard EM50</b>		
<b>Title:</b> Cleanliness of Components for Use in Oxygen, Fuel, and Pneumatic Systems, Specification for	<b>Document No.:</b> MSFC-SPEC-164	<b>Revision:</b> D
	<b>Effective Date:</b> January 30, 2014	<b>Page</b> 12 of 27

- e. Masking of crack-like indications
- f. Residue
- g. Crazing (non-metallics)
- h. Reversion (non-metallics)
- i. Hydrolysis (non-metallics)

**NOTE:** ASTM Manual 36 provides additional guidance for the safe use of oxygen and oxygen systems.

### 3.2.6 Final Rinsing Solution

The final rinsing solution shall meet or exceed the cleanliness requirements for which they are intended and meet the following minimum requirements at the point of use:

3.2.6.1 There shall be no particle greater than 175 $\mu$  in any dimension and no more than 5 particles between 100 and 175  $\mu$  per 500 ml when tested per ASTM F 312. Particle corrections by subtracting the test solvent particle count from the final particle count are not allowed.

3.2.6.2 Nonvolatile residue (NVR) in fluids used to clean surfaces with an NVR requirement shall not be greater than 10 milligrams per 1000 milliliters, as determined by ASTM F 331 or equivalent test method. When the final rinsing fluid is used for verification of surface NVR cleanliness, the NVR shall meet the test fluid requirements of section 4.3.3.1.

3.2.6.3 If water is used as the final rinse fluid it shall meet the requirements of paragraph 3.2.6.1, the minimum specific resistance (maximum conductance) shall be 50,000 ohms/cm, and the pH shall be between 6.0 and 8.0.

**NOTE:** These are minimum final rinsing solution requirements established for cleaning of tanks and large components. Cleaning processes for small components or for components that require cleanliness levels cleaner than shown in Table I may require greater purity levels for the final rinsing solution and this final rinse solution may not be suitable as a verification flush solution.

### 3.3 Detailed Product Cleanliness Requirements

Precision cleaned components and vessels shall be verified to meet applicable cleanliness requirements specified in Table II or as specified on the engineering drawing or component specification. Verification sampling shall be performed in an environment that is compatible with the environment in which cleaning was performed.

#### 3.3.1 Use of Alternate Acceptance Criteria

Alternate verification procedures and/or corresponding cleanliness levels may be used only upon demonstration of equivalence in accordance with 6.1 and upon written approval by the NASA

<b>MSFC Technical Standard EM50</b>		
<b>Title:</b> Cleanliness of Components for Use in Oxygen, Fuel, and Pneumatic Systems, Specification for	<b>Document No.:</b> MSFC-SPEC-164	<b>Revision:</b> D
	<b>Effective Date:</b> January 30, 2014	<b>Page</b> 13 of 27

procuring activity. Supplemental information concerning chemical species of contaminants and their potential reactivity may be useful in determining alternate acceptance criteria.

**CAUTION:** It has been observed that both NVR and particulate levels increase after a system has been exposed to cryogenic media. This increase in contamination levels should be taken into consideration in establishing methods for system verification.

### 3.3.2 Visual Cleanliness

Surfaces of all components that will contact the respective service medium shall be visually free of contaminants such as moisture, corrosion, scale, dirt, oil, grease, wax, gum, accumulations of fiber or silt, and other foreign material when inspected in accordance with 4.3.1. Scale-free discoloration due to welding or passivation is permitted. Discrete particles and fibers that are smaller than the Class limits are acceptable.

3.3.2.1 Surfaces Inaccessible to Visual Inspection. Surfaces inaccessible to visual inspection shall be accepted or rejected based upon 3.3.4 and 3.3.5, provided that adequate measures have been implemented to assure that no foreign object debris is entrapped within the inaccessible area. Borescope/videoscope inspection may be required.

3.3.2.2 Use of Borescope/Videoscope. Care shall be taken when using borescope/videoscope equipment not to introduce contamination into the part or component. Borescope/videoscope equipment contains sensitive optics and care shall be taken in cleaning the equipment such that it is acceptable to use in a clean system. Consult with the manufacturer regarding acceptable solvents and evaluate whether they are compatible with clean systems.

### 3.3.3 Acidity or Alkalinity

Surfaces that have been cleaned or that have come in contact with aqueous or semi-aqueous media or chemical solutions (e.g., caustics, acids, etc.) shall register a pH between 6.0 and 8.0 on completion of the final rinse when evaluated in accordance with 4.3.2.

### 3.3.4 Nonvolatile Residue

Nonvolatile residue, as defined in Appendix C, shall not exceed the limits specified in the engineering documentation when tested in accordance with 4.3.3.

### 3.3.5 Particulate Contamination

Particulate contamination shall not exceed the limits specified in the engineering documentation when tested in accordance with 4.3.3.

### 3.3.6 Silting

Silting, as defined in Appendix B, shall not be permitted.

<b>MSFC Technical Standard EM50</b>		
<b>Title:</b> Cleanliness of Components for Use in Oxygen, Fuel, and Pneumatic Systems, Specification for	<b>Document No.:</b> MSFC-SPEC-164	<b>Revision:</b> D
	<b>Effective Date:</b> January 30, 2014	<b>Page</b> 14 of 27

### 3.4 Drying

#### 3.4.1 Procedure

Components shall be thoroughly dried to remove residual cleaning, rinsing, and/or verification media. Effluent gas shall not exhibit an increase in moisture content greater than 5 PPM or measurable increase in concentration of residual organic solvents when tested in accordance with 4.3.4. Items which do not lend themselves to this type of drying or testing procedure shall be dried and tested in accordance with procedures approved by the NASA procuring activity.

**CAUTION:** Most solvents are not oxygen compatible; it is the user's responsibility to assure removal of these substances prior to packaging or placing hardware into service.

#### 3.4.2 Drying and Purging Gases

Gases used in drying processes shall conform to the following and to cleanliness and quality assurance requirements for gases as specified in MSFC-STD-3535. Condensable hydrocarbon sampling per MSFC-STD-3535 is not required on gas delivery systems that do not contain hydraulic pumps or other components that could be a source of condensable hydrocarbon contamination to the system.

3.4.2.1 Nitrogen. Nitrogen used for drying or purging shall conform to MIL-PRF-27401, type 1, grade B.

3.4.2.2 Air. For drying/purging of tanks/vessels where the use of dry gases is impractical, air shall meet the following minimum requirements:

- a. No particulate matter > 100 microns
- b. Relative humidity – 60% maximum
- c. Hydrocarbon content 15 PPM maximum except 20 PPM when the carbon chain of 5 or above does not exceed 5 PPM.

### 3.5 Post-Verification Operations

Fluids or gases contacting cleaned surfaces after final cleaning or testing for cleanliness, as a minimum, shall meet the requirements for final rinsing fluids per 3.2.6 and drying gases per 3.4.2.

### 3.6 “Excepted” Components

Excepted components shall consist of items and systems that cannot be processed per the requirements of this document. Components that cannot be cleaned and certified using normal procedures or facilities because of size, construction, materials of construction, etc. may be processed as excepted components. Excepted components require written approval of the NASA

<b>MSFC Technical Standard EM50</b>		
<b>Title:</b> Cleanliness of Components for Use in Oxygen, Fuel, and Pneumatic Systems, Specification for	<b>Document No.:</b> MSFC-SPEC-164	<b>Revision:</b> D
	<b>Effective Date:</b> January 30, 2014	<b>Page</b> 15 of 27

procuring activity. These items shall be cleaned as to the intent of this specification as practical and identified as "EXCEPTED" on all tags and documentation.

### **3.7 Field Cleaning**

For ground test systems only, field cleaning shall only be performed when one of the following criteria is met:

- a. The item is a part of a fixed installation and cannot be removed to a remote cleaning site.
- b. Cleaned spare parts are not available and removal to a remote site would unduly impact operations.
- c. The item is precision cleaned and field cleaning is done during the assembly process on-site as an assurance function.

#### **3.7.1 Field Cleaning Process Requirements**

Field cleaning shall be performed using system flow velocities greater than 3 m/s, pressurized spraying, and rapid draining to achieve visual cleanliness. Alternative cleaning methods shall be approved by the NASA procuring activity.

### **3.8 Ground Test Systems**

Ground or facility test equipment for LO<sub>2</sub>, GO<sub>2</sub>, and fuel systems shall be evaluated for cleanliness on a predetermined schedule or upon assessment of need. An engineering evaluation shall be made to identify the component or area to be tested based upon the systems configuration and pressure. As a minimum, the evaluation shall identify the component most likely to accumulate contaminants due to geometry, location, internal surface finish, and other technical considerations.

#### **3.8.1 Oxygen Ground Test Systems Operating at 5000 psig or Greater**

For oxygen systems operating at 5000 psig or greater, the selected component(s) shall be evaluated per 3.3.4 except that a NVR analysis shall not exceed Table 1 Level B (5 mg/0.1 m<sup>2</sup>).

#### **3.8.2 Oxygen Ground Test Systems Operating at Less than 5000 psig**

For oxygen systems operating at less than 5000 psig the following NVR criteria shall apply:

- a. An NVR analysis of Table 1 Level B (5 mg/0.1 m<sup>2</sup>) or greater shall require approval of the organization's Test Director for continued operation.
- b. An NVR analysis of 10 mg/0.1 m<sup>2</sup> or greater shall require the approval of the organization's Director of Safety /Quality Assurance or designated authority with concurrence of applicable Materials and Processes and Test organizations for continued operation.

<b>MSFC Technical Standard EM50</b>		
<b>Title:</b> Cleanliness of Components for Use in Oxygen, Fuel, and Pneumatic Systems, Specification for	<b>Document No.:</b> MSFC-SPEC-164	<b>Revision:</b> D
	<b>Effective Date:</b> January 30, 2014	<b>Page</b> 16 of 27

- c. An NVR analysis of 20 mg/0.1 m<sup>2</sup> or greater shall be cause for discontinued use until the entire system is re-cleaned and verified clean to a minimum of Table I Level B (5 mg/0.1 m<sup>2</sup>).

## **4. VERIFICATION**

### **4.1 Responsibility for Inspection**

The cleaning activity is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the cleaning activity may utilize his own or any other inspection facilities and services acceptable to the NASA procuring activity. Inspection records of examinations and tests shall be kept complete and available to the government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to assure supplies and services conform to specified requirements.

### **4.2 Inspection Sample Size/Frequency**

#### **4.2.1 Visual Inspection**

The sample for the visual inspection test of 4.3.1 shall consist of all cleaned components except as noted. Components, such as small diameter tubing (1/2 inch diameter or less), having limited accessibility to visual examination shall be accepted or rejected on the basis of the inspections of 4.3.2 and 4.3.3.

**NOTE:** Tubing and pipe can pass fluid sample analysis and still fail visual inspection. Depending on the geometry of the part and nature of the contamination, borescope/videoscope inspection or black light may be required.

#### **4.2.2 Acidity/Alkalinity**

Surfaces which have been cleaned and rinsed with aqueous media shall be evaluated in accordance with 4.3.2.

#### **4.2.3 Particulate/NVR Sample**

Except as noted in 4.2.3.1, 4.2.3.2, and 4.2.3.3, the quantitative analysis sample for the test of 4.3.3 shall consist of a minimum of 5% of the items cleaned, but not less than one sample for each group of 20 or less of the items cleaned. The sample shall be selected at random from production items that have been cleaned, examined in accordance with 4.3.1 and found acceptable. The sample shall be selected in a manner that will provide maximum representation of the affected lot. In this context a lot does not necessarily require identical parts but does include all hardware processed in one operation. The test sample and the segment of production that it represents shall be clearly identified as specified by the NASA procuring activity. All items shall be verified visually clean and inspected for silting.



<b>MSFC Technical Standard EM50</b>		
<b>Title:</b> Cleanliness of Components for Use in Oxygen, Fuel, and Pneumatic Systems, Specification for	<b>Document No.:</b> MSFC-SPEC-164	<b>Revision:</b> D
	<b>Effective Date:</b> January 30, 2014	<b>Page</b> 17 of 27

4.2.3.1 **Small Components.** Reliability samples for small components (components having a significant surface area less than 0.1 m<sup>2</sup>) shall consist of a sufficient number of components to make up 0.1 m<sup>2</sup> of surface area. When the total quantity of items procured have a combined surface area less than 0.1 m<sup>2</sup>, a quantity of cleaned items sufficient to make up 0.1 m<sup>2</sup> of surface area shall be used in preparation of the reliability sample or a special test procedure may be used upon written request to and approval by the NASA procuring activity. For particularly small items with a total area significantly less than 0.1m<sup>2</sup>, the criterion is 1 milligram NVR maximum, or equivalent, per 500 ml of verification solvent.

4.2.3.2 **Containers.** All containers shall be submitted for acceptance testing per 4.3.3.

4.2.3.3 **Rigid Tubing.** Reliability of the cleaning procedure for rigid tubing may be determined and the cleaning process qualified as specified herein. After qualification of the procedure and equipment, reliability sampling shall be left to the discretion of the NASA procuring activity. Samples for qualification of the cleaning process shall be selected as follows:

- a. Select a minimum of 5 cleaned tubes with a minimum of 3 feet cumulative length and having a minimum combined significant surface area of 0.1m<sup>2</sup> from each size (diameter) and type tube (material) to be cleaned. Tubes shall have been cleaned in accordance with the exact procedures and utilizing equipment approved in accordance with 3.2.
- b. Evaluate samples in accordance with the tests of 4.3.3, as applicable, to meet requirements of 3.3.3 and 3.3.4.
- c. Upon satisfactory qualification of the cleaning procedure and equipment to meet applicable requirements of 3.3.4 and 3.3.5, periodic spot checks in addition to the inspections of 4.3.1 and 4.3.2 shall be made to insure cleaning procedures continue to be effective.

#### **4.2.4 Drying Sample**

The quantitative analysis reliability sample for 4.3.4 shall consist of a minimum of 5% of items dried, but not less than one sample for each group of 20 or less of items dried. The sample shall be selected at random from production items that have been cleaned, verified and dried in accordance 3.2, 3.3, and 3.4, as applicable. The sample shall be selected in a manner that will provide maximum representation of the affected lot. A lot does not necessarily mean identical parts but does include all hardware processed in one operation. The reliability sample and the segment of production that it represents shall be clearly identified as specified by the NASA procuring activity.

4.2.4.1 **Qualification of Drying Procedure.** Alternately, the reliability of the drying procedure may be established for each hardware configuration, and the drying process qualified as specified herein. After qualification of the procedure and equipment for a specific hardware configuration, reliability sampling shall be left to the discretion of the NASA procuring activity. Samples for qualification of the drying process shall be selected as follows:

<b>MSFC Technical Standard EM50</b>		
<b>Title:</b> Cleanliness of Components for Use in Oxygen, Fuel, and Pneumatic Systems, Specification for	<b>Document No.:</b> MSFC-SPEC-164	<b>Revision:</b> D
	<b>Effective Date:</b> January 30, 2014	<b>Page</b> 18 of 27

- a. Select a minimum of 5 cleaned, verified and dried items of each of the hardware configurations to be qualified. Parts shall have been cleaned and dried in accordance with the same procedures and equipment previously approved in accordance with 3.2, 3.3, and 3.4.
- b. Evaluate samples in accordance with 4.3.4 to meet the requirements of 3.4.1.
- c. Upon satisfactory qualification of the drying procedure for each hardware configuration, the established drying cycle requirements shall be implemented. Periodic spot checks shall be made to insure that drying procedures continue to be effective.

### **4.3 Acceptance Inspection Procedures**

Acceptance inspection shall be performed as specified herein. Alternate acceptance inspection procedures, qualified by the user, shall be approved by the NASA procuring activity.

#### **4.3.1 Visual Inspection**

Surfaces of all components that will contact the respective service medium shall be visually inspected at a distance of 0.6 to 1.2 meters (2 to 4 feet) under a minimum incident light level of 500 lumens/meter<sup>2</sup> (50 foot-candles). An external light, ultraviolet light, or borescope may be required to examine internal surfaces. The presence of contamination shall require test/evaluation to determine acceptance or rejection. Scale-free discoloration of a surface due to welding and passivation shall be permitted.

**NOTE:** When inspection of piece parts at the minimum inspection distance is impractical, closer inspection is permitted. When interior volumes of tanks do not provide sufficient access to physically conduct an inspection within the defined VC range, the inspection shall be conducted at a distance that deviates from the defined range only to the extent required to physically perform the inspection.

#### **4.3.2 Acidity/Alkalinity Evaluation**

External and internal surfaces which have been cleaned with aqueous media shall be tested for pH while the component is still wet from final rinse, or if dry, by wetting the surface of the component with a few drops of water (see 3.2.6). The pH indicating paper or other approved indicator shall be sensitive to the pH range of 6.0 to 8.0.

#### **4.3.3 Particle/NVR Cleanliness Tests**

Hardware shall be tested and accepted for visual inspection per 4.3.1 and acidity/alkalinity per 4.3.2, if applicable, prior to being submitted for tests. Cleaned components selected by the contractor or supplier for tests shall be tested as specified herein. Alternate methods may be used after qualification and written approval by the NASA procuring activity in accordance with 6.1.

4.3.3.1 **Test Fluids.** Test fluids shall be selected by the user, approved by the NASA procuring activity, and shall be specified in the cleaning and verification process instructions. Test fluids

<b>MSFC Technical Standard EM50</b>		
<b>Title:</b> Cleanliness of Components for Use in Oxygen, Fuel, and Pneumatic Systems, Specification for	<b>Document No.:</b> MSFC-SPEC-164	<b>Revision:</b> D
	<b>Effective Date:</b> January 30, 2014	<b>Page</b> 19 of 27

used to verify particulate cleanliness shown in Table I shall meet particle requirements 3.2.6 as a minimum. Test solvents used to verify nonvolatile residue shall have a maximum NVR background level of 3 mg per 100 ml for sampling to level B or 0.4 mg per 100 ml for sampling to Level A. To meet these levels, test fluids may require filtration and/or distillation prior to use. The selected solvent shall be chemically compatible with the component per section 3.2.5 and effective at removing contaminants of concern.

4.3.3.2 Procedure for Obtaining Reliability Sample. Reliability samples for quantitative analyses shall be obtained as follows. The procedure for particle and NVR sampling shall be flushing of the product with an approved solvent in accordance with ASTM F 303. The collected flush sample shall be processed in accordance with ASTM F 311. Hardware shall be thoroughly dried after the flushing operation.

**NOTE:** Where component flushing is impractical, particle count sampling may be performed by the tape lift method in accordance with ASTM E 1216 or an approved equivalent and NVR sampling may be performed by the swab method in accordance with MSFC-PROC-1832 or by sampling with extracted wipers in accordance with a procedure approved by the NASA procuring activity.

- a. Components with Surface Area Less than 0.1 m<sup>2</sup>. Components with surface area less than 0.1 m<sup>2</sup> shall be sampled and analyzed per 4.2.3.1.
- b. Components with Surface Area Between 0.1 and 0.5 m<sup>2</sup>. A 200 ml, nominal, test solution shall be flushed over the significant surfaces of components with surface area between 0.1 and 0.5 m<sup>2</sup> and collected for quantitative analysis per 4.3.3.3.
- c. Components with Surface Area Greater than 0.5 m<sup>2</sup>. The significant surfaces of components with surface area greater than 0.5 m<sup>2</sup> shall be flushed with 100 ml, nominal, of test solvent per 0.1 m<sup>2</sup> of surface area. The test solution shall be collected and thoroughly agitated. A 200 ml sample shall be obtained from the agitated solution for quantitative analysis per 4.3.3.3.
- d. Large Containers. Large containers/vessels shall be verified by a procedure submitted by the user and approved by the NASA procuring activity.
- e. Convolute Flex Hoses. Special attention to cleaning is required for convolute flex hoses. All convolute flex hose components shall be verified as precision-clean in a vertical orientation. For flex hose tube diameters equal to or greater than one inch, verification of precision cleanliness shall be performed by sampling a rinse fluid applied internally through use of a high-pressure nozzle to the entire length of the flex hose. For flex hose tube diameters less than one inch, the use of a high-pressure nozzle is preferred, but verification

<b>MSFC Technical Standard EM50</b>		
<b>Title:</b> Cleanliness of Components for Use in Oxygen, Fuel, and Pneumatic Systems, Specification for	<b>Document No.:</b> MSFC-SPEC-164	<b>Revision:</b> D
	<b>Effective Date:</b> January 30, 2014	<b>Page</b> 20 of 27

may be performed by flushing a rinse fluid through the entire length of the flex hose with flex hose agitation.

4.3.3.3 Quantitative Analysis of Reliability Sample. NVR analysis shall be conducted per ASTM F 331 and particulate analysis shall be conducted per ASTM F 312 test method B. The solvent used for sampling shall be recorded with the test results.

a. Counting of fiber contaminants.

When fibers larger than the maximum allowable non-fiber particle size are counted per table I, counting shall be performed by microscopic analysis or by image analysis with visual inspection of the image to verify that fibers have been accurately interpreted by the image analysis system.

b. Measurement of fiber length.

The length of twisted fibers may be measured, when counting by image analysis, by the use of an opisometer or equivalent on the fiber image or, when counting microscopically, may be approximated by measuring the fiber in segments.

c. Measurement of fiber width.

The width of a fiber shall be measured as the largest apparent projected width or diameter of the fiber.

#### 4.3.4 Drying Test

Reliability of the drying procedure for items subjected to liquids during cleaning or verification sampling procedures shall be determined as follows:

4.3.4.1 Flow pre-filtered drying gas (3.4.2) through or over affected surfaces of the item being tested.

4.3.4.2 For hardware processed with aqueous media, monitor the dew point of the drying gas entering and leaving the affected item to determine presence of moisture on cleaned and dried surfaces. An increase in moisture content of the drying gas of 5 PPM or greater shall necessitate additional drying prior to packaging or application of protective coverings.

4.3.4.3 For hardware processed with halogenated solvents, monitor effluent drying gas with a halogen detector, to determine if affected surfaces are free from residual organic solvents. If no measurable concentrations are indicated by the halogen detector, affected surfaces shall be considered free from excessive residual organic solvents. Any measurable concentration above ambient in the drying gas shall necessitate additional drying prior to packaging or application of protective coverings.

<b>MSFC Technical Standard EM50</b>		
<b>Title:</b> Cleanliness of Components for Use in Oxygen, Fuel, and Pneumatic Systems, Specification for	<b>Document No.:</b> MSFC-SPEC-164	<b>Revision:</b> D
	<b>Effective Date:</b> January 30, 2014	<b>Page</b> 21 of 27

4.3.4.4 For hardware processed with alcohols or other hydrocarbons, monitor the effluent drying gas with a hydrocarbon detector. Any measurable concentration above ambient in the drying gas shall necessitate additional drying before packaging or application of protective coverings.

4.3.4.5 When a flammable solvent is used for cleaning, flushing, or testing of liquid or gaseous oxygen systems or nitrogen tetroxide systems, the residual concentration of flammable solvent shall be verified as within acceptable limits prior to the introduction of flight fluids. This requirement does not apply to solvents used for hand-wiping operations or to piece parts except for assembled components that are required by engineering documentation to have a unit oxygen compatibility test.

- a. After purging with an inert gas, a 24 hour "lockup" of the component or assembly shall be conducted, at a minimum temperature of 15 °C.
- b. The solvent concentration in lockup gas samples shall not exceed 18 PPM when measured as methane or 10 PPM when measured using an instrument calibrated to the specific solvent utilized and capable of detecting 1 PPM.

**NOTE:** The lockup will typically be performed at ambient temperature. For systems with small internal volumes, a clean sampling reservoir may be added to increase the volume of gas in the system.

4.3.4.6 Visual inspection for dryness is allowed where appropriate, provided the user receives approval from the NASA procuring activity.

#### **4.4 Rejection**

FAILURE TO MEET ANY REQUIREMENT OF SECTION 3.0 SHALL BE CAUSE FOR REJECTION.

### **5. PACKAGING**

#### **5.1 Packaging of Components**

All significant surfaces or openings to significant surfaces shall be protected from contamination by double bagging the surfaces or openings with approved coverings (5.3.1), secured by heat sealing, closing with tape (5.3.2), or other approved method.

##### **5.1.1 Application of Tape**

Tape shall not contact or otherwise contaminate significant surfaces and, when feasible, shall not contact other product surfaces cleaned to visibly clean levels.

##### **5.1.2 Packaging of Fluid Line Connections**

<b>MSFC Technical Standard EM50</b>		
<b>Title:</b> Cleanliness of Components for Use in Oxygen, Fuel, and Pneumatic Systems, Specification for	<b>Document No.:</b> MSFC-SPEC-164	<b>Revision:</b> D
	<b>Effective Date:</b> January 30, 2014	<b>Page</b> 22 of 27

Unless impractical due to small component size or shape, unmated fluid line connections shall be individually packaged and integrity sealed to facilitate clean mating operations at the assembly stage.

### **5.1.3 Outer bags**

Protected components shall be placed in visually clean outer bags meeting the requirements of 5.3.1 and shall be sealed with tamper-evident integrity seals.

### **5.1.4 Inert Storage Package**

Interiors of the bags and parts shall be purged with a drying gas meeting the requirements of 3.4.2.1; bags shall be completely sealed to assure an inert storage package.

### **5.1.5 Prevention of Damage**

Sealed bags shall be over packed as necessary to prevent damage during storage and handling.

### **5.1.6 Moisture Barrier**

At least one layer of the packaging system shall be a moisture barrier.

### **5.1.7 Other Packaging Methods**

Other packaging materials compatible with the applicable service media may be used, however, gas purging and over packaging requirements shall be as listed above. If alternate methods are used, prior approval of materials and procedures shall be obtained from the NASA procuring activity.

### **5.1.8 Environmental Requirements for Packaging**

Packaging operations involving cleaned and verified components should be accomplished within the same environmentally controlled area in which verification was performed. However, where impractical to package in the same environment, the environment shall not adversely impact the function of the hardware/component. Outer wrapping and over packing may be performed outside the controlled area.

### **5.1.9 Use of Desiccants**

Desiccants (5.3.3), when required for additional corrosion protection, shall not be placed in such a manner as to contaminate cleaned surfaces. Provisions shall be made for monitoring desiccants prior to use to assure dehydrating effectiveness. Even non-dusting desiccants may be a source of contamination for precision-cleaned components, therefore desiccants placed inside the inner bag or package shall be sealed within a clean water-vapor permeable film. Desiccants shall be packaged with a visual humidity indicator.

## **5.2 Protection of Tanks and Containers**

Immediately after drying, openings shall be covered with approved pre-cleaned dry covers (5.3.1) secured in a manner to prevent detachment or damage during handling, storage, or shipment.

<b>MSFC Technical Standard EM50</b>		
<b>Title:</b> Cleanliness of Components for Use in Oxygen, Fuel, and Pneumatic Systems, Specification for	<b>Document No.:</b> MSFC-SPEC-164	<b>Revision:</b> D
	<b>Effective Date:</b> January 30, 2014	<b>Page</b> 23 of 27

Covers shall be designed to prevent recontamination of tank interior. If exposed to uncontrolled environments, a positive pressure purge shall be maintained until the system is closed.

### **5.3 Packaging Materials**

#### **5.3.1 Protective Materials and Devices**

Protective materials and devices that serve as contamination barriers shall be specified in the cleaning process document.

5.3.1.1 Cleanliness of Materials. Prior to use, protective packaging materials or devices shall be cleaned and dried to a level compatible with the component end item cleanliness requirements.

5.3.1.2 Durability of Materials. Under normal usage, materials or devices shall be lint-free, and shall not delaminate, peel, disintegrate, slough or otherwise deteriorate in a manner that will contaminate the cleaned item.

5.3.1.3 Oxygen Service. Inner packaging materials that protect the wetted surfaces of parts for liquid or gaseous oxygen service shall be compatible with LO<sub>2</sub>/GO<sub>2</sub>. Fluorohalocarbon films such as Aclar 22A, 22C, and 33C, or polyfluoroethylenepropylene (PFEP) film conforming to AMS 3647 are acceptable. This requirement applies to covers for the openings of tanks, feedlines, tubes, valves, and other fluid system components and to the inner bag for components where covers for openings are not used or where the part is to be fully immersed in the service fluid.

#### **5.3.2 Tape**

Tape used for precision-cleaned packaging shall be constructed of materials that do not outgas, shed particulate, or degrade during normal use.

#### **5.3.3 Desiccants**

Desiccants used for packaging of precision-cleaned components shall meet the requirements of MIL-D-3464 Type II (non-dusting).

### **5.4 Marking/Identification**

Unless otherwise specified by the NASA procuring activity, cleaned items shall be identified per MIL-STD-129 with appropriate certification tags and shall contain as a minimum the following information:

- a. Part or identification number.
- b. Contractor identification
- c. Contractor cleaning and packaging procedure identification
- d. Date of cleaning

<b>MSFC Technical Standard EM50</b>		
<b>Title:</b> Cleanliness of Components for Use in Oxygen, Fuel, and Pneumatic Systems, Specification for	<b>Document No.:</b> MSFC-SPEC-164	<b>Revision:</b> D
	<b>Effective Date:</b> January 30, 2014	<b>Page</b> 24 of 27

- e. Title, date, and number of this standard
- f. Service medium or intended use of component
- g. Manufacturer's serial number
- h. Acceptance stamps
- i. Cleanliness level

## 6. NOTES

### 6.1 Approval of Alternate Verification Procedures

Alternate verification procedures may be used only upon qualification and written approval by the NASA procuring activity. For qualification of alternate procedures, the following methodology is required; in all instances statistically significant data shall be provided to the NASA procuring activity before alternative verification methods can be considered.

#### 6.1.1 Sample Selection

Hardware and contaminant(s) must be representative and reasonably reflect worst case configuration/conditions.

#### 6.1.2 Qualification Test for Alternate Verification Test Methods

- a. Prepare a set of non-flight test items of representative hardware and apply representative contaminants. Verify hardware cleanliness on 50% of test items, using the standard test method specified in section 4. An accepted aggressive NVR solvent such as ethyl acetate, cyclohexane, hexane, CFC-113, HCFC-225, or trichloroethylene shall be used for the baseline NVR test method.
- b. Verify hardware cleanliness of the balance of the contaminated test items using the proposed alternative verification test method.
- c. Statistically equate verification equivalence. The mean and variance of the proposed alternate process shall be provided. The contamination level results and variance of the proposed process shall be statistically equivalent to or less than the baseline process. Variance shall be determined from a minimum of seven (7) configuration tests.



<b>MSFC Technical Standard EM50</b>		
<b>Title:</b> Cleanliness of Components for Use in Oxygen, Fuel, and Pneumatic Systems, Specification for	<b>Document No.:</b> MSFC-SPEC-164	<b>Revision:</b> D
	<b>Effective Date:</b> January 30, 2014	<b>Page</b> 25 of 27

## APPENDIX A - ACRONYMS

COPV	Composite Over-Wrapped Pressure Vessels
GO2	Gaseous Oxygen
GSE	Ground Support Equipment
HEPA	High Efficiency Particulate Air
LO2	Liquid Oxygen
MSDS	Materials Safety Data Sheet
NVR	Nonvolatile Residue
PFEP	Polyfluoroethylenepropylene
PPM	Parts Per Million

<b>MSFC Technical Standard EM50</b>		
<b>Title:</b> Cleanliness of Components for Use in Oxygen, Fuel, and Pneumatic Systems, Specification for	<b>Document No.:</b> MSFC-SPEC-164	<b>Revision:</b> D
	<b>Effective Date:</b> January 30, 2014	<b>Page</b> 26 of 27

## **APPENDIX B - DEFINITIONS**

**Cleaning** - Removal of particulate and incompatible materials from significant surfaces of components and systems.

**Contaminant** - Any material that could chemically interact or mechanically interfere with the component or system function

**Fiber** - a particle having a length to width ratio of 10 as a minimum i.e., length-to-width ratio of 10 - to 1 or greater.

**Inert Storage Package** - A barrier material used to encase a cleaned item to maintain item cleanliness level and which, when properly sealed, cannot introduce contaminants to the protected item.

**Integrity Seal** - Decal or other device applied to a package or closure in such a manner that it becomes visually damaged or destroyed when the package or closure is opened, providing evidence of tampering or unauthorized access.

**Micron** - 0.001 millimeter

**Milligram (mg)** - 0.001 gram

**Nonvolatile Residue (NVR)** - The quantifiable substance remaining after filtration and controlled evaporation of final flush.

**Particle** - A minute quantity of matter, metallic or non-metallic, with observable length, width and thickness.

**Procuring activity** - The first tier NASA customer of the user of this standard.

**pH** - A unit of measure from 0-14 representing acidity/alkalinity of an aqueous solution.

**Scale** – Surface oxidation in the form of partially adherent layers of corrosion products, left on metals by casting or heat treatment in air or other oxidizing atmosphere.

**Significant Surface** - All component surfaces that may come into contact with the respective service medium (wetted areas).

**Silting** - an accumulation of minute particles in the size range normally not counted but of sufficient quantity to interfere with sample analysis.

<b>MSFC Technical Standard EM50</b>		
<b>Title:</b> Cleanliness of Components for Use in Oxygen, Fuel, and Pneumatic Systems, Specification for	<b>Document No.:</b> MSFC-SPEC-164	<b>Revision:</b> D
	<b>Effective Date:</b> January 30, 2014	<b>Page</b> 27 of 27

**Visually Clean** - An article is classified visually clean when free of dirt, scale, oil, or other contamination when viewed at a distance of 0.6 to 1.2 meters (2 to 4 feet) under a minimum incident light level 500 lumens/meter<sup>2</sup> (50 foot-candles) with normal or corrected vision. A borescope is allowed to aid visual examination.