

**BY ORDER OF THE COMMANDER
AIR FORCE SPACE COMMAND**

**AIR FORCE SPACE COMMAND
MANUAL 91-710, VOLUME 2**

1 JULY 2004



Safety

**RANGE SAFETY USER REQUIREMENTS
MANUAL VOLUME 2 - FLIGHT SAFETY
REQUIREMENTS**

NOTICE: This publication is available digitally on the AFDPO WWW site at:
<http://www.e-publishing.af.mil>

OPR: AFSPC/SEC (Lt Col John Humphries)

Certified by: AFSPC/SE (Col Billy Colwell)

Pages: 61

Distribution: F

This manual implements Department of Defense Directive (DoDD) 3100.10, *Space Policy*, DoDD 3200.11, *Major Range and Test Facility Base*, DoDD 3230.3, *DoD Support for Commercial Space Launch Activities*, AFD 91-1, *Nuclear Weapons and Systems Surety*, AFD 91-2, *Safety Programs*, AFD 63-12, *Assurance of Operational Safety, Suitability, and Effectiveness*, AFI 91-202, *The US Air Force Mishap Prevention Program* (AFSPC Sup.1) and the *Memorandum of Agreement between the Department of the Air Force and the Federal Aviation Administration on Safety for Space Transportation and Range Activities*. This volume incorporates information previously found in Eastern and Western Range 127-1, Chapter 2, *Flight Analysis*. It establishes the requirements for flight safety for vehicles launched and operations conducted from the Air Force Space Command (AFSPC) ranges, including the Eastern Range (ER) and Western Range (WR). The volume includes requirements for the following programs: ballistic missiles and space vehicles; cruise missiles and remotely piloted vehicles; small unguided rockets or probe vehicles; aerostats or balloons systems; projectiles, torpedoes, and non-propulsive air-dropped bodies; air-launched vehicles; intended support plans for aircraft and ships; directed energy systems; and the launch of large nuclear systems into space. Flight Safety Requirements approval is a necessary prerequisite for conducting operations covered by this volume. By itself, Flight Safety Requirements approval does not constitute permission to conduct an operation. Unless specifically noted in this volume, the term *Range Safety* refers to the Operations Support and Flight Safety Requirements groups at the ER and WR.

This volume applies to all Range Users conducting or supporting operations on the AFSPC ranges. Range Users include any individual or organization that conducts or supports any activity on resources (land, sea, or air) owned or controlled by AFSPC ranges. This includes such organizations as the Department of Defense (DoD), United States (US) government agencies, civilian launch operators, and foreign government agencies and other foreign entities that use AFSPC range facilities and test equipment; conduct pre-launch and launch operations, including payloads to orbital insertion or impact; and/or require on-orbit or other related support. Commercial users intending to provide launch services from one of the ranges shall have a license or license application in process from the Department of Transportation's Federal Aviation Administration (FAA) or have a DoD sponsorship and be accepted by the DoD to use the ER or WR. Foreign government organizations or other foreign entities shall be sponsored by an appropriate US govern-

ment organization or be a customer of a Range User. This volume applies to the Air National Guard. It does not apply to the Air Force Reserve Command.

NOTE: Volume 1 includes a complete table of contents for all the volumes of AFSPCMAN91-710. In addition each individual volume contains its own table of contents. Volume 7 contains a glossary of references, acronyms and abbreviations, and terms for use with all the volumes. Special publication formatting features are described in paragraph 1.1 of this volume.

Chapter 1— GROUND RULES	6
1.1. Organization of the Volume.	6
1.1.1. Main Chapters.	6
1.1.2. Open Text.	6
1.1.3. Bordered Paragraphs:	6
1.2. Impact Restrictions:	6
1.5. Data Submission:	7
1.5.1. General.	7
1.5.2. Statement of Program Justification.	7
1.6. Range User Responsibilities.	8
1.6.9. Range User Range Tracking System Performance Requirements.	8
Chapter 2— FLIGHT ANALYSIS APPROVAL AND DATA REQUIREMENTS	11
2.1. Introduction.	11
2.1.1. Security and Data Delivery Lead Times:	11
Table 2.1. Data Requirements Documentation Lead Times.	11
2.2. Flight Plan Approval and Data Requirements Overview.	12
2.2.1. Approval Phases.	12
2.2.2. Data Requirements.	13
2.2.3. Preliminary Flight Plan Approval and Data Package Requirements:	13
2.2.4. Final Flight Plan Approval and Data Package Requirements:	18
2.3. Aircraft/Ship Intended Support Plans and Data Package Requirements:	20
2.3.1. Purpose.	20
2.3.2. ISP Development and Submittal.	20
2.3.3. ISP Data Package Requirements.	20
2.4. Directed Energy Plan Approval and Data Requirements.	21
2.4.1. Purpose.	21
2.4.2. DEP Submittal:	21

2.4.3. Laser Operational Procedures:	22
2.4.4. DEP Data Package Requirements:	22
2.4.5. Coordination with the Strategic Command Control Center.	26
2.5. Large Nuclear Systems Approval and Data Requirements.	26
2.5.1. Environment Impact Statement: L-3 years.	26
2.5.2. Final Safety Analysis Report: L-1 year.	26

Chapter 3— PROGRAM-SPECIFIC FLIGHT ANALYSES

27

3.1. Trajectory Analysis:	27
3.1.1. General.	27
3.1.2. Trajectory Analysis Products:	27
3.2. Malfunction Turn Analysis.	37
3.2.1. General.	37
3.2.2. Malfunction Turn Analysis Products:	37
3.3. Debris Analysis.	37
3.3.1. General.	37
3.3.2. Debris Analysis Products:	37
3.4. Debris Risk Analysis	38
3.4.1. General:	38
3.4.2. Debris Risk Analysis Products:	38
3.5. Acoustic Analysis.	39
3.5.1. Acoustic Analysis Products:	39
3.6. Sonic Boom Analysis.	39
3.6.1. Sonic Boom Analysis Products:	40
3.7. FTS Determination Analysis.	40
3.7.1. General.	41
3.7.2. FTS Determination Analysis Products:	41
3.8. Post-Flight Vehicle Performance Analysis.	41

Attachment 1— TRAJECTORY DATA

44

A1.2.1.XYZ Coordinates.	44
A1.2.2.Trajectory Data Item Requirements.	44
A1.2.3.Nominal (Reference) Trajectory.	45
A1.2.4.Three-Sigma Dispersed Trajectories.	45

Table A1.1. Trajectory Types for Single Flight Azimuths.	46
Table A1.2. Trajectory Types for Variable Flight Azimuths.	47
Table A1.3. Trajectory Types for Multiple Liquid Propellant Engines Thrusting at Liftoff.	47
Table A1.4. Trajectory Data Items.	47
Attachment 2— MALFUNCTION TURN DATA	53
Attachment 3— FRAGMENT DATA	58
Attachment 4— JETTISONED BODY DATA	61

CHAPTER 1

GROUND RULES

1.1. Organization of the Volume.

1.1.1. Main Chapters. The main chapters of this volume include common requirements for all vehicle classes. Appendixes include additional requirements to supplement the main chapters.

1.1.2. Open Text. The open text contains the actual mandatory performance-based requirements. The only tailoring expected for these requirements would be the deletion of non-applicable requirements. For example, solid rocket motor performance requirements would be deleted for launch systems that do not use solid rocket motors.

1.1.3. Bordered Paragraphs:

1.1.3.1. Bordered paragraphs are non-mandatory and are used to identify some of the potential detailed technical solutions that meet the performance requirements. In addition, the bordered paragraphs contain lessons learned from previous applications of the performance requirement, where a certain design may have been found successful, or have been tried and failed to meet the requirement. These technical solutions are provided for the following reasons:

1.1.3.1.1. To aid the tailoring process between Range Safety and Range Users in evaluating a potential system against all the performance requirements.

1.1.3.1.2. To aid Range Safety and Range Users in implementing lessons learned.

1.1.3.1.3. To provide benchmarks that demonstrate what Range Safety considers an acceptable technical solution/implementation of the performance requirement and to help convey the level of safety the performance requirement is intended to achieve.

1.1.3.2. The technical solutions in the bordered paragraphs may be adopted into the tailored version of the requirements for a specific program when the Range User intends to use that solution to meet the performance requirement. At this point, they become mandatory requirements to obtain Range Safety approval. This process is done to:

1.1.3.2.1. Provide an appropriate level of detail necessary for contractual efforts and to promote efficiency in the design process.

1.1.3.2.2. Avoid contractual misunderstandings that experience has shown often occur if an appropriate level of detail is not agreed to. The level of detail in the bordered paragraphs is necessary to avoid costly out-of-scope contractual changes and to prevent inadvertently overlooking a critical technical requirement.

1.1.3.3. The Range User always has the option to propose alternatives to the bordered paragraph solutions. Range User proposed alternative solutions shall achieve an equivalent level of safety and be approved by Range Safety. After meeting these two requirements, the Range User proposed solutions become part of the tailored AFSPCMAN 91-710 for that specific program.

1.1.3.4. Range Safety has final decision authority in determining whether Range User proposed detailed technical solutions meet AFSPCMAN 91-710 performance requirements.

1.2. Impact Restrictions:

1.2.1. No launch vehicle, payload, or jettisoned body shall be intentionally impacted on land unless approved by the Chief of Safety and meets the public risk criteria in Volume 1, 3.2 of this publication. Proposed flights shall be planned and trajectories shaped so that normal impact dispersion areas for such items do not encompass land.

1.2.2. If any jettisoned body remains buoyant after impact and presents a hazard to maritime vessels or platforms, a means of sinking or recovering the body shall be provided.

1.2.3. For space vehicles, if a stage contains multiple-burn engines, the impact dispersion area corresponding to any planned cutoff before orbital insertion shall be entirely over water.

Time permitting, critical events, such as the arming of engine cutoff circuits and the transmission of backup engine cutoff commands, should be sequenced to occur when the impact dispersion areas are entirely over water.

1.2.4. In accordance with DoDD 4540.1, *Use of Airspace by U.S. Military Aircraft and Firings Over the High Seas*, all operations shall be conducted with due regard for the safety of all air and surface traffic. Areas for activities shall be selected so as not to interfere with established air routes and ocean shipping lanes.

1.3. Land Overflight. The overflight of any inhabited landmasses is discouraged and is approved only if operation requirements make overflight necessary and risk studies indicate the probability of impact and casualty expectancy is acceptable.

1.4. Trajectory Safety Margins:

1.4.1. The flight trajectory shall be designed to accommodate Range Safety capability to control launch-related risks.

1.4.2. A sufficient safety margin shall be provided between the intended flight path and protected areas so a normal vehicle does not violate destruct criteria.

1.4.3. During the initial launch phase, the launch profile shall not be so steep that critical coastal areas cannot be protected by standard safety destruct criteria.

1.4.4. No hazardous condition is acceptable if mission objectives can be obtained from a safer approach, methodology, or position.

1.5. Data Submission:

1.5.1. General. The Range User is only required to supply required data once if no changes occur from operation to operation. If this is the case, the Range User shall state, in writing to Range Safety, that there are no changes. However, if any changes occur from operation to operation, the Range User shall identify, in writing to Range Safety, all data that have changed from a specified baseline mission and specify the document, paragraph, and page number where each change item can be found. This statement shall be submitted to Range Safety according to established lead times.

1.5.2. Statement of Program Justification. The Range User shall provide the following additional supporting data justification before a Range Safety program approval can be made. The level of detail

required for this information shall be established in preliminary discussions with Range Safety or in the Chief of Safety's response to a Range User's written request for approval.

1.5.2.1. Detailed explanation of the operation/mission objectives.

1.5.2.2. Operation/mission objectives that will not be met if the proposed plan must be modified as suggested by Range Safety or is not approved.

1.5.2.3. Alternate or modified plans that will accomplish the operation/mission objective.

1.5.2.4. Effects on the operation/mission such as cost, schedule, data requirements, vehicle reliability, reserve propellants, and launch window, if the plan must be modified or if the plan is not approved.

1.5.2.5. Other data the Range User may wish to submit.

1.6. Range User Responsibilities. Range Users shall be responsible for the following:

1.6.1. Submitting all data identified as requirements for Range Safety support of planned operations.

1.6.2. Complying with data submission lead times and Range Safety approval conditions.

1.6.3. Advising Range Safety of changes to operational scenarios to determine if approvals are affected.

1.6.4. Providing specific data required for the scheduled operation day.

1.6.5. Ensuring accuracy and relevancy of all data to support the requests for approvals.

1.6.6. Providing anticipated trajectory data to the lead range when the Program Requirements Document (PRD) is submitted, when trajectories are changed, or when additional trajectories are added. Range Users should contact Range Safety for flight trajectory data preparation, submittal, and processing.

1.6.7. Revising theoretical trajectory data when use of the trajectory, as supplied, will adversely affect the support needed by either the planning or operational phases of the Range User program.

1.6.8. Providing hazard assessments (the process of identifying operation-related hazards, assessments of those hazards, and quantification of risk to establish operation constraints.)

The hazards associated with each source of risk (debris impact, toxic chemical dispersion, and acoustic overpressure) have an associated set of critical parameters and thresholds of acceptability. Changes in the launch parameters, such as azimuth, payload, and launch site, and the need for flight safety controls, including the evacuation of personnel, enforcement of road-blocks, and restriction of sea lanes or airspace, depend on the results of the hazard assessments.

1.6.9. Range User Range Tracking System Performance Requirements. The following requirements apply to Range Users who use other than AFSPC range assets for range tracking. The range tracking system (RTS) consists of the hardware, software, and personnel required to transmit, receive, process, and display launch vehicle data for Range Safety purposes.

1.6.9.1. General. An RTS, including at least two adequate and independent instrumentation data sources shall be provided and shall be maintained from T-0 through each phase of powered flight up to the end of Range Safety responsibility.

1.6.9.2. Tracking Source Adequacy. Each tracking source, provided for Range Safety, shall provide real-time state vector accuracy (position and velocity), timeliness, and reliability so that when extrapolated to the instantaneous impact point (IIP) space, the following criteria shall be met:

1.6.9.2.1. Accuracy. The three-sigma present position and IIP uncertainty, resulting from all error sources, shall be no greater than the following:

1.6.9.2.1.1. Eastern Range:

1.6.9.2.1.1.1. Sensor performance benchmarks shall be provided for the launch area and downrange (as defined below) in terms of the arc range to IIP (RIIP), assuming a pad launch from Cape Canaveral Air Force Station (CCAFS). The accuracy benchmarks for other than pad launches (such as sea launches and reusable launch vehicles) shall be based on the arc range to the nearest populated landmass.

1.6.9.2.1.1.1.1. Launch Area Benchmarks:

1.6.9.2.1.1.1.1.1. Differential Global Positioning System (DGPS):

DGPS benchmarks are based on the acceptable worst case accuracy of DGPS as a range tracking system and by themselves will not prevent a vehicle from launching. The radar benchmarks are based on the current ER average prime source launch area accuracy of approximately 15 meters (one sigma). In addition, of the real-time state vectors that do not meet the benchmarks, no more than 10 real-time state vectors (i.e., one second period, assuming a 10 pps update rate) should occur consecutively. Implied in this is that the total system delay time, from vehicle state vector through destruct activation on the vehicle will be ≤ 4 seconds.

1. The present position uncertainties shall not exceed 250 feet when the RIIP $\leq 66,000$ feet.
2. The crossrange IIP uncertainties shall not exceed 330 feet when the RIIP $< 66,000$ feet.

1.6.9.2.1.1.1.1.2. Radar:

1. The present position uncertainties shall not exceed 140 feet when the RIIP $\leq 50,000$ feet.
2. The crossrange IIP uncertainties shall not exceed 300 feet when the RIIP $< 20,000$ feet.
3. The downrange IIP uncertainties shall not exceed 300 feet when the RIIP $< 6,000$ feet.

1.6.9.2.1.1.1.2. Downrange Benchmarks:

1.6.9.2.1.1.1.2.1. DGPS:

1. The crossrange IIP uncertainty shall not exceed 0.5 percent of the vacuum impact range when the RIIP $> 66,000$ feet.
2. The downrange IIP uncertainty shall not exceed 1.0 percent of the vacuum impact range when the RIIP $> 66,000$ feet.

1.6.9.2.1.1.2.2. Radar:

1. The crossrange IIP uncertainty shall not exceed 250 feet + 0.25 percent of the vacuum impact range when $20,000 \text{ feet} < \text{RIIP} \leq 100,000 \text{ feet}$.
2. The crossrange IIP uncertainty shall not exceed 0.5 percent of the vacuum impact range when the $\text{RIIP} > 100,000 \text{ feet}$.
3. The downrange IIP uncertainty shall not exceed 5.0 percent of the vacuum impact range when the $\text{RIIP} > 6,000 \text{ feet}$.

1.6.9.2.1.2. Western Range:

1.6.9.2.1.2.1. The launch area IIP uncertainties shall not exceed 1,000 feet.

1.6.9.2.1.2.2. The midcourse IIP uncertainties shall not exceed 1.0 percent of the IIP range.

1.6.9.2.1.2.3. The terminal area IIP uncertainties shall not exceed 7,000 feet.

1.6.9.2.1.2.4. Accuracy:

1.6.9.2.1.2.4.1. Accuracy is determined in terms of the radius of a circle that contains three sigma of all possible instantaneous impact points.

1.6.9.2.1.2.4.2. Launch area accuracy applies until the hazardous debris impact areas are entirely over water.

1.6.9.2.1.2.4.3. Terminal area accuracy applies only to ballistic vehicles with a maneuverable upper stage targeted for the Reagan Test Site.

1.6.9.2.2. Timeliness:

1.6.9.2.2.1. The IIP display update rate shall be ≥ 10 samples per second and each update shall meet the requirements of paragraphs 1.6.8.3.1 and 1.6.8.3.2.2.

1.6.9.2.2.2. The time delay between vehicle event and firing of the vehicle ordnance, excluding the Mission Flight Control Officer (MFCO) reaction time, shall be within the total Range Safety System response time budget. This budget includes hardware and software delays inherent to both airborne and ground equipment. The budget for the ER is either 1.5 or 3.5 seconds depending on the time of flight and Range Safety System configuration for each operation. The WR budget is 1.0 second, except for ballistic operations targeted for the Reagan Test Site and orbital operations with a low launch azimuth (typically < 170 degrees) for which the budget is 500 milliseconds during critical portions of the flight.

1.6.9.2.3. RTS Reliability. The reliability of the RTS ground segment shall be ≥ 0.999 at a 95 percent confidence level for a 1 hour duration during the period of Range Safety responsibility.

1.6.9.3. Tracking Source Independence. Each tracking source provided for Range Safety shall be electrically, mechanically, and structurally separate from the vehicle guidance and telemetry systems and any other tracking source, so that one tracking source will not influence another tracking source.

CHAPTER 2

FLIGHT ANALYSIS APPROVAL AND DATA REQUIREMENTS

2.1. Introduction. The Range User shall initiate flight analysis approval at the earliest practical date to establish that the proposed program is acceptable from a safety standpoint. Early action by the Range User keeps data requirements to a minimum and ensures that the effort and expense of planning a program or computing pre-operation trajectories is not wasted. The specific approval depends on the type of program activity. Developing the safest operation consistent with program objectives can take several months while changes in the proposed plan are made. This chapter is subdivided into four distinct classes of flight analysis approvals: Flight Plan Approval (FPA) and Data Requirements, Aircraft/Ships Intended Support Plans (ISP) Approval and Data Requirements, Directed Energy Plan (DEP) Approval and Data Requirements, and Large Nuclear Systems Approval and Data Requirements.

2.1.1. Security and Data Delivery Lead Times:

2.1.1.1. Security. The Range User shall provide a Security Classification Guide for all classified program information.

2.1.1.2. Lead Times. Before Range Safety approval is granted, the Range User shall provide required data in specified formats in accordance with the lead times listed in Table 2.1. Lead times may be modified depending on the complexity of the program. If the requirements are not provided within the lead-time specified, Range Safety may not be able to prepare all necessary safety criteria in time to support a proposed operation. In this event, the operation shall not be conducted until Range Safety can make adequate safety preparations.

Table 2.1. Data Requirements Documentation Lead Times.

Vehicle/Missile	Lead Time Before Launch (Calendar Days) New/Existing
Ballistic Missile	
Preliminary Flight Plan Approval (PFPA)	2Y/1Y
Final Flight Plan Approval (FFPA)	120D/60D
Space Vehicle: Single Flight Azimuth	
PFPA	2Y/1Y
FFPA	120D/60D
Project Firing Tables	7D
Space Vehicle: Variable Flight Azimuth	
PFPA	2Y/1Y
FFPA	12M/6M
Project Firing Tables	45D

Vehicle/Missile	Lead Time Before Launch (Calendar Days) New/Existing
Cruise Missile/Remotely Piloted Vehicle	
PFPA	2Y/1Y
FFPA	120D/60D
Small Unguided Rocket	
PFPA	2Y/1Y
FFPA	120D/60D
Aerostat/Balloon	
PFPA	2Y/1Y
FFPA	120D/60D
Projectile, Torpedo, Air-Launched Device	
PFPA	2Y/1Y
FFPA	120D/60D
Ship and Aircraft ISP	20 D
Directed Energy Systems	1Y/30D
Large Nuclear Systems	See 2.5.

2.2. Flight Plan Approval and Data Requirements Overview. Flight plan approval (FPA) is applicable to the following programs: ballistic missile and space vehicles; cruise missiles and remotely piloted vehicles; small unguided rockets or probes; aerostats or balloon systems; projectiles, torpedoes, non-propulsive air-dropped bodies, or any small devices to be flight tested.

2.2.1. Approval Phases. The FPA process incorporates two formal approval phases: Preliminary Flight Plan Approval (PFPA) and Final Flight Plan Approval (FFPA).

2.2.1.1. Programs usually fall into two categories: new or existing. New programs include existing programs whose FPA supporting data has changed significantly. New programs shall submit the data requirements for both PFPA and FFPA. Existing programs generally shall submit the data requirements for only FFPA. For either new or existing programs that do not involve long lead times for planning or payload development, formal approval may, of necessity, occur only a few months before the desired operation date.

2.2.1.2. In each FPA phase, Range Safety shall respond to the Range User's written request for approval in one of the following ways: (1) by issuing a letter of approval, (2) by issuing a letter of disapproval, (3) by requesting that a change in the proposed plan be made or evaluated, or (4) by requesting additional data. After all the requested data have been provided and evaluated, the Range User shall be given an "approval," "conditional approval," or "disapproval" letter. If the

flight plan or mission is approved, the letter shall specify the conditions of approval pertaining to such things as launch azimuth limits, trajectory shaping, wind restrictions, locations of impact areas, times of discrete events, and number of operations for which the approval applies. The approval shall be final as long as the operation(s) remain within the stated conditions. If significant changes to the flight plan occur after approval has been granted, further analysis of the revised plan may be necessary. The Range User is responsible for advising Range Safety of any such changes or anticipated changes as early as possible.

2.2.2. Data Requirements. Data requirements for the PFPA and FFPA are found in two chapters of this volume. The requirements in Chapter 2 apply to all programs. Requirements for specific programs, including detailed analyses, are in Chapter 3 of this volume. All requirements may be tailored by Range Safety, as required. The Preliminary Flight Data Package (PFDP) and the Final Flight Data Package (FFDP) are submitted in support of the PFPA and FFPA, respectively. The data packages may be submitted in any convenient format. The following general format, that conforms to the order in which requirements are established, is suggested for any Range User who desires a standard submission form. If this format is adopted and the information submitted in response to a requirement cannot easily be placed in the data package, it should be made an appendix to the specific part. For example, compact disks and listings for trajectories would be an appendix to Part III in the format shown below.

Table of Contents

Part I: Introduction

Part II: General Vehicle Data

Part III: Trajectory Data

Part IV: Additional Data

2.2.3. Preliminary Flight Plan Approval and Data Package Requirements:

2.2.3.1. PFPA. The FPA process for all new programs begins with an introductory meeting followed by the submittal of required data and a formal written request for a PFPA. Existing programs shall also request a PFPA when previously approved supporting data is not applicable to the planned operation. The purpose of the PFPA is to ensure Range Safety requirements are included in the overall system design and to determine if the specific program is conceptually acceptable. In preliminary meetings, Range Safety can define acceptable flight limits and conditions, specify which parts of the flight plan need special emphasis, and identify requirements applicable to the program. Data regarding anticipated flight trajectories, booster configuration, and flight termination system (FTS) configuration shall be included in the PFPA. Lack of some pertinent data should not be cause for delaying the initial written request, particularly if preliminary discussions have not been held. The Range User should begin PFPA action during the Preliminary Design Review (PDR) phase of the program planning or, in any event, immediately after Range Safety has replied to the Program Introduction (PI) in a Statement of Capability. For new programs, the PFPA usually occurs at least two years (one year for existing programs) before the planned operation.

2.2.3.2. Preliminary Flight Data Package Requirements. In addition to the program-specific requirements listed in Chapter 3 of this volume, the PFPA data package shall include the following:

2.2.3.2.1. Basic program description and objectives including number, designation, and purpose of operation(s) for which the proposed flight plan is applicable.

- 2.2.3.2.2. General operation scenarios and proposed target areas and a statement indicating whether the proposed trajectory (or flight plan) is similar to some prior operation.
- 2.2.3.2.3. Intended launch or flight test date(s).
- 2.2.3.2.4. Map and listing of downrange and crossrange vacuum instantaneous impact points (IIPs) for each second of powered flight time.
- 2.2.3.2.5. General description of launch vehicle and payload in sufficient detail for hazard assessment providing the following information:
 - 2.2.3.2.5.1. Type, weight, and TNT equivalency of all propellants.
 - 2.2.3.2.5.2. Description of ordnance items.
 - 2.2.3.2.5.3. Description of toxic and radioactive materials.
 - 2.2.3.2.5.4. Characteristics of high pressure vessels, lasers, and batteries.
 - 2.2.3.2.5.5. Description of materials, thickness, and safety factors of pressure vessels.
 - 2.2.3.2.5.6. Thrust and burn times of motors and thrusting devices.
 - 2.2.3.2.5.7. Description of guidance and control system.
 - 2.2.3.2.5.8. Drawings and diagrams showing structural arrangement and layout of significant components in each stage or payload.
- 2.2.3.2.6. General description and location of the airborne FTS (made up of the command and automatic destruct subsystems) or statement indicating that the planned system is similar to one already in use. Range Safety shall be involved before the PDR time frame if a new design is to be considered.
- 2.2.3.2.7. Preliminary estimate of fragment characteristics such as number, composition, dimensions, and weight due to all potential modes of vehicle breakup such as destruct and aerodynamic loading.
- 2.2.3.2.8. Tracking aids such as C-Band transponder, global positioning system (GPS) receivers/translators installed in the vehicle that can be used for flight safety purposes and their locations in the stages or sections.
- 2.2.3.2.9. Telemetry measurement listing and data word definitions.
- 2.2.3.2.10. Description of launch site facilities, support buildings, and the structural integrity information for each of these.
- 2.2.3.2.11. Geodetic latitude, longitude, and designation of proposed launch site, or location on the earth's surface for launches that occur above or below the earth's surface; if launch or test initiation can occur inside an area rather than at a single specified location, this area shall be defined.
- 2.2.3.2.12. Launch azimuth for single azimuth launches or desired azimuth sector(s) for variable azimuth launches.
- 2.2.3.2.13. Estimates of the nominal impact point and the three-sigma drag-corrected dispersion area for each jettisoned body.

2.2.3.2.14. Buoyancy analysis of all jettisoned bodies that impact water; for bodies that remain buoyant after impact and present a hazard to maritime vessels or platforms, a means of sinking or recovering the body is required. If recovery is desired, a recovery procedure shall be identified.

2.2.3.3. Reliability and Malfunction Analysis Data Requirements. Reliability of each stage and probability of a normal mission or failure rate data for each stage shall be provided. The following data shall be provided:

2.2.3.3.1. Description of Failure Modes That Can Result in Abnormal Flight. An analysis of all subsystems shall be made to determine failure modes that would result in a catastrophic event. Typical malfunctions that should be considered include failure of the hydraulic and electrical systems, failure of the guidance and control system, failure of separation mechanisms between stages, failures that lead to premature thrust termination, overshoot, or shifting of the platform reference.

2.2.3.3.2. An estimate of the probability of occurrence or failure rate (versus time) for each failure mode and an explanation of the method(s) used for the estimate; any other information considered pertinent with respect to critical portions of flight, such as vehicle stability characteristics and structural limits.

2.2.3.3.3. Description of All Credible Failed Vehicle Response Modes. A response mode is a category of vehicle dynamic response, including vehicle breakup, that results from one or more failure modes. At a minimum, the response modes should include on-trajectory failures such as thrust termination and explosion and malfunction turn (loss of thrust vector control, tumble turn, nozzle burn-through failures). On-trajectory failures should be subdivided according to the type of breakup (for example, aerodynamic or explosive) that will result. Malfunction turns should be subdivided into tumble turns and trimmed turns if trimmed turns are a credible response mode.

2.2.3.3.4. Summary of past vehicle performance giving number launched, launch location, number that performed normally, behavior and actual (if available) or estimated impact location for any that malfunctioned, time and nature of malfunction, and corrective action.

2.2.3.4. Propellant Description. If a vehicle has the capability of exploding as a result of self-initiation, FTS activation, or ground or water impact or if a vehicle uses propellants that are toxic in gaseous or vapor states due to combustion or release to the atmosphere, the following data shall be provided:

2.2.3.4.1. Types of propellant or a statement indicating the same propellant formulation is already in use. The following thermodynamic and chemical information shall be provided for each propellant type used on the vehicle:

2.2.3.4.1.1. List of Major Chemical Constituents. A major constituent is defined as a chemical component that (1) constitutes more than 1 percent of the propellant mass, (2) is a toxic chemical, or (3) produces a toxic combustion product. The list of combined constituents shall account for at least 99 percent of the total propellant mass.

2.2.3.4.1.2. Chemical formula for each major constituent.

2.2.3.4.1.3. Mass fraction of each major constituent relative to the total mass propellant.

2.2.3.4.1.4. Reference temperature of chemical constituents in their normal state; for example 25°C.

2.2.3.4.1.5. Enthalpy of formation for each chemical constituent at the reference temperature (calorie/gram-mole).

2.2.3.4.1.6. Designation of each chemical constituent as fuel or oxidizer (F or O).

2.2.3.4.1.7. Molecular weight of each chemical constituent.

2.2.3.4.2. TNT equivalency of remaining propellant versus flight time and explosion scenario for each separate stage (or motor) and each possible combination of stages that could result from malfunction conditions.

2.2.3.4.3. An estimate for the probability of explosion versus flight time for each of the following: self-initiation, FTS activation, and ground or water impact. A comprehensive description of the methods used to derive the estimate shall be provided.

2.2.3.4.4. Description of methods used to minimize the possibility of explosion.

2.2.3.4.5. Time of day when launches will be scheduled and the number of launches.

2.2.3.4.6. Maximum total quantities of liquid and solid propellants.

2.2.3.4.7. Nominal vehicle altitude versus time through 3,000 meters in the following format:

$$t = a * z^b + c$$

Where:

t = time (seconds) after ignition

z = height (meters) of the vehicle above ground, and a, b, c, are coefficients found by a least squares fit to an estimated time-height profile

2.2.3.4.8. Exhaust plume heat content (calorie/gram), mass flux (gram/second), and chemical composition (mass fractions and chemical species) for all motors ignited at liftoff. This data shall be evaluated at a point sufficiently far downstream from the nozzle exit plume such that plume afterburning is essentially complete and the plume has expanded and cooled sufficiently to allow high temperature combustion species to have completed recombination actions. Total mass flux shall indicate nominal engine burn propellant mass flux as well as entrained air mass flux. Documentation of this data shall include reference to the method of calculation, distance downstream from the nozzle, possible chemical interactions between main engines and strap-on boosters (if appropriate), and radiation heat loss. Chemical composition of the plume shall cover all major species such that (1) at least 99 percent of total plume mass is represented, and (2) all major toxic species are included. Chemical species of concern to Range Safety include, but are not necessarily limited to, hydrogen chloride, carbon dioxide, carbon monoxide, aluminum oxide, hydrazine, unsymmetrical dimethylhydrazine, monomethylhydrazine, nitrogen tetroxide, nitrogen dioxide, nitric acid, nitrosodimethylamine, formaldehyde dimethylhydrazine, benzene, toluene, and other volatile organic compounds.

2.2.3.4.9. Solid propellant burn time (seconds) and average burn rate (grams/seconds) for propellant fragments burning at 1 atmosphere of pressure following an accidental or FTS-initiated

destruct for each motor containing solid propellant. Fuel fragmentation assumptions (number and size of fragments, surface area, inches/second burn rate) used to generate the average solid propellant burn time and mass burn rate shall be included.

2.2.3.4.10. Liquid propellant expenditure rate (grams/seconds) for nominal launch for the first 3,000 meters of vehicle ascent.

2.2.3.4.11. For catastrophic abort or FTS vehicle destruct of vehicles using liquid propellants, the information described below is required to support Range Safety toxic risk analyses. Depending on the similarity of the program vehicle's propellants to existing vehicle propellants, the Range User may be required to perform significant additional technical analyses to provide this information.

2.2.3.4.11.1. Percentages of available liquid fuel and oxidizer mixed and reacted within each stage during the first several hundred milliseconds of the initiating destruct mechanism.

2.2.3.4.11.2. Percentage of available liquid propellants mixed and reacted during the active fireball burn phase that typically last several seconds past the initiating event. Provide assumptions about the degree of mixing and the nature of chemical reaction between vehicle stages, including solid rocket motors and the extent of air entrainment and after-burning of fuel species.

2.2.3.4.11.3. Percentage of available liquid propellants dispersed by vehicle explosion that do not undergo chemical reactions but remain as vaporized unreacted propellant. The objective of obtaining this information is to characterize and quantify the types of chemical reactions among the vehicle propellants so that the chemical composition and total heat content of the liquid propellant fireball can be computed from input reactant data.

2.2.3.4.12. Initial Exhaust Cloud Data. The following information shall be provided to specify the initial parameters required to calculate buoyant cloud rise in support of Range Safety toxic risk analyses. These values describe the exhaust ground cloud when the horizontal momentum produced by the ducting or reflection in the launch mount becomes negligible compared to the buoyant forces within the cloud for the nominal launch scenario. Depending on the similarity of the program vehicle to existing vehicles, the Range User may be required to perform significant additional technical analyses to provide this information.

2.2.3.4.12.1. Initial exhaust ground cloud radius for normal launches. Assume a spherical cloud with a volume equivalent to that estimated for the actual ground cloud.

2.2.3.4.12.2. Initial radius of the area over which solid propellant fragments are dispersed due to a vehicle abort on the pad. For aborts during the first 50 seconds of flight, provide estimates of solid propellant fragment number, size, mass, ballistic coefficient, explosion-induced fragment velocity, and nominal vehicle position; and, at 10-second intervals, velocity vector.

2.2.3.4.12.3. Vertical velocity of the ground cloud centroid for nominal launch cases.

2.2.3.4.12.4. Initial ground cloud centroid height (meters above ground level [AGL]).

2.2.3.5. Explosive Reentry Vehicle or Warhead Information. An operation that includes the use of an explosive reentry vehicle (RV) or warhead shall not be conducted without the approval of the Space Wing Commander. For these operations, the following data are required:

- 2.2.3.5.1. A complete justification for the proposed operation.
- 2.2.3.5.2. The proposed position and altitude of the RV or warhead detonation point.
- 2.2.3.5.3. The effects of the detonation on the missile and RV or warhead in terms of number, weights, cross-sectional areas, ballistic coefficients, and velocities imparted to the pieces.
- 2.2.3.5.4. The impact dispersion area for all fragments including diffusion and dispersion of any toxic or radioactive clouds or fragments and the radiation exposure characteristics.

2.2.4. Final Flight Plan Approval and Data Package Requirements:

2.2.4.1. FFPA. The FFPA is applicable to each program operation. The FFPA is based on detailed analyses of the operation objectives, vehicle performance, and other data items required. In response to the Range User request, the FFPA is issued when the Chief of Safety is satisfied that a specific operation can be supported within the limits of flight safety control capabilities to provide positive protection to life and property. Any constraints or conditions identified in the PFPA may be superseded by those stated in the FFPA. The FFPA applies to a specific operation and does not guarantee that similar operations will receive an FFPA. If a program consists of identical operations, a blanket FFPA may be granted that would remain in effect throughout the life of the program as long as the operations remain within the specified safety constraints. The request for FFPA and the supporting data are typically received by Range Safety at 120 calendar days (new programs) or 60 calendar days (existing programs) before the planned operation. Past data submissions may be referenced if that data has not changed from previous operations.

2.2.4.2. Final Flight Data Package Requirements.

2.2.4.2.1. General. These data requirements apply to requests for FFPA for all programs specified in 2.2. The analysis-specific data requirements in Chapter 3, 3.1 through 3.7 of this volume are also required before an FFPA is issued. The FFDP shall include items that were changed from or not provided in the PFDP. The FFDP is made up of the data requirements used to produce the final set of operational rules and flight control criteria and ensures all data complies with the conditions of the PFPA and data format requirements. The request for FFPA shall specify the operation designation, intended operation date, and references to all applicable supporting data products. In meeting the FFPA requirements, some of the information submitted by the Range User may not change from the PFDP or from operation to operation. In such cases, the information need be supplied only once. However, for each operation, the Range User shall state in writing which supporting data are applicable and specify the document, page number, and paragraph where each required item can be found. In other cases where the proposed plan deviates from the PFPA or previously accepted limits, additional data shall be provided.

2.2.4.2.2. Limits of a Useful Mission.

2.2.4.2.2.1. These data requirements apply solely to space operations. They are used to establish guidelines or limits for land overflight prior to orbital insertion.

2.2.4.2.2.2. The permissible limits for overflight depend not only on this data, but also on estimated overflight hazards, the operational objectives, and the importance of these objectives. The Range User shall provide the following data:

2.2.4.2.2.2.1. Launch azimuth limits for which the primary operation objectives can be met and for which a useful orbit can be attained.

2.2.4.2.2.2.2. Operational objectives that will be met or the extent to which the primary objectives will be degraded.

2.2.4.2.2.2.3. Description of limiting orbit(s) (apogee, perigee, period, and inclination) as a function of overflight azimuth.

2.2.4.2.2.2.4. Circumstances or types of malfunctions that could cause the vehicle to fly outside the three sigma limits of normality, but remain within the limits for which a useful orbit can be attained.

2.2.4.2.2.2.4.1. The probability of occurrence of these malfunctions.

2.2.4.2.2.2.4.2. The affects of these malfunctions on the success of succeeding burns or stages.

2.2.4.2.2.2.5. The most lofted and depressed trajectories for which the primary operation objective can be met and for which a useful orbit can be attained, given the information requested in paragraphs 2.2.4.2.2.2.1 through 2.2.4.2.2.2.4.2. In deriving these trajectories, only perturbations that result in deviations in the pitch plane shall be considered. If these trajectories cannot be provided to Range Safety, the following may be substituted:

2.2.4.2.2.2.5.1. If the stage that achieves orbit does not contain an FTS, the Range User shall provide the upper and lower altitude limits at shutdown of the last sub-orbital stage if the succeeding stage is to attain a useful orbit.

2.2.4.2.2.2.5.2. If the stage that achieves orbit contains an FTS, the Range User shall provide the upper and lower altitude limits as the vacuum impact point reaches the continent to be overflown by the first orbital stage if this stage is to attain a useful orbit.

2.2.4.2.2.2.5.3. The Range User shall provide the minimum impact range that the last suborbital stage must achieve, if the succeeding stage is to attain a useful orbit and a minimum orbit (perigee ≥ 70 miles).

2.2.4.2.3. Solid Propellant Data Requirements. The following data are required for solid propellants:

2.2.4.2.3.1. Burning rate of solid propellants, in inches/second, as a function of pressure, including ambient atmospheric pressures.

2.2.4.2.3.2. Percent propellant TNT equivalency for each stage as a function of relevant impact parameters, such as weight of propellant, impact velocity, surface composition, and impact geometry.

2.2.4.2.3.3. Stage ignition and burntime, propellant weight versus time, and propellant density.

2.3. Aircraft/Ship Intended Support Plans and Data Package Requirements:

2.3.1. Purpose. The purpose of the ISP approval is to ensure maximum safety consistent with the operation objectives. To the extent possible, this means that support positions and flight plans should be established outside impact limit lines. When the required support data cannot be collected from such remote locations, support positions located in relatively hazardous areas shall be carefully planned to minimize the ship or aircraft hit probability. Hazards to ships and aircraft exist primarily in the launch area, along the flight azimuth where jettisoned stages and components reenter and breakup, and in the target area where reentry vehicles and final stages impact. ISP approval is applicable to each ship and aircraft supporting an operation requirement identified in the Universal Documentation System (UDS) or participating in an operation on a non-interference basis. Policies and procedures for control of test support aircraft are given in 30 RANS Operating Instruction (OI) 55- 33, *Air Control/Control Procedures*, or 45 SWI 13-201, *Eastern Range Air Space Management Procedures*. Similar regulations for ships do not exist.

2.3.2. ISP Development and Submittal. ISPs for ships and aircraft shall be developed either by the Range User or by support agencies that are responding to requirements contained in the PRD or the Operations Requirements Document (ORD). In either case, the developing organization shall furnish the ISP for review and approval, either directly to Range Safety or through the Range Squadron.

2.3.3. ISP Data Package Requirements. For operations requiring support aircraft or ships, the Range User shall provide the following additional information 20 calendar days before the mission. All identifying points and positions shall be time correlated using the operation start time as a reference.

2.3.3.1. Aircraft Flight Profile Requirements:

2.3.3.1.1. Type of aircraft.

2.3.3.1.2. Aircraft physical dimensions as described in Jane's aircraft publications. The following data shall be provided as a minimum:

2.3.3.1.2.1. One-half wing span – the length of the wing measured from the fuselage to the wing tip edge.

2.3.3.1.2.2. Maximum width of the fuselage measured in the top view.

2.3.3.1.2.3. Average thickness of the wing measured in the side view.

2.3.3.1.2.4. Average fuselage thickness measured in the side view.

2.3.3.1.2.5. Overall area (in square feet) measured in the top view.

2.3.3.1.2.6. Overall perimeter (in feet) measured in the top view.

2.3.3.1.3. Call sign.

2.3.3.1.4. Registration Number ("N" number).

2.3.3.1.5. Tail number.

2.3.3.1.6. Warning area and mission area penetration points (entry and exit).

2.3.3.1.7. Holding fixes and altitudes.

2.3.3.1.8. Primary and alternate Mission Support Positions (MSPs), including geodetic latitude, longitude, heading, speed, and time of arrival.

2.3.3.1.9. Written and graphic flight path location describing the maneuvers within 200 miles of the MSP giving orbit or loiter locations, positions along ground track in latitude and longitude, turn points, turn radii where applicable, speeds, and headings.

2.3.3.1.10. Course, speed, and altitudes from the MSP to the terminal end of the data run.

2.3.3.1.11. Departure route after mission completion, including maneuvers for departure to recovery base.

2.3.3.1.12. Final staging and recovery bases.

2.3.3.2. Ship Cruise Profile Information:

2.3.3.2.1. Class of ship.

2.3.3.2.2. Dimensions of ship measured in the top view.

2.3.3.2.3. Call sign.

2.3.3.2.4. Registration Number.

2.3.3.2.5. Name.

2.3.3.2.6. Warning area and mission area penetration points (entry and exit).

2.3.3.2.7. Primary and alternate MSPs including geodetic latitude, longitude, heading and speed.

2.3.3.2.8. Course and speed from the MSP to the terminal end of the data run.

2.3.3.2.9. Planned location (support plan), both written and graphic, of the vessel during the period from launch until operation termination or impact.

2.4. Directed Energy Plan Approval and Data Requirements. These requirements apply to all forms of directed energy systems. Laser design, test, and documentation requirements are also addressed in 8.2. Laser Systems of Volume 3 of this publication. Reasonable and prudent operational procedures shall be established so that hazards from directed energy system operations present virtually no risk to the general public.

2.4.1. Purpose. The purpose of the Directed Energy Plan (DEP) approval is to ensure the operation is conducted safely with consideration for the operation requirements and national need. The DEP approval applies to programs using directed energy systems. These systems include, but are not limited to, lasers and neutral particle and ion beams, with any combination of surface, air, or space locations for the energy source and target. In this volume, the term *laser* is used as a generic reference to all directed energy systems. In general, those laser operations in the following categories are subject to review:

2.4.1.1. Laser operations requesting range support through the provision of the UDS.

2.4.1.2. Laser illumination, for which an Operations Directive (OD) does not exist, conducted in conjunction with a scheduled range operation for which an OD does exist.

2.4.1.3. Laser operations having the potential to impair Range Safety controls or reduce the reliability of Range Safety systems .

2.4.2. DEP Submittal:

2.4.2.1. Requests for DEP approval shall be forwarded directly to Range Safety or through either the Plans Office for new programs or the Range Squadron for existing programs. Lead times and requirements may vary and shall be tailored depending on the specific characteristics of the system and proposed operating scenarios. Lead times for data requirements reflect the dependence of mission success on planned laser operations. For instance, laser operations performed on a non-interference basis using scheduled launches as a target of opportunity will have lead times different from directed energy activities that are integral to a scheduled operation.

2.4.2.2. Laser operations considered mandatory by the Range User shall be included as part of the Program Introduction (PI). If the laser operation is not mandatory in accordance with Range User requirements, the initial request for laser program approval is desired at least one year before the planned operation date.

2.4.2.3. Requests for Range Safety review of recurring laser operations are desired 30 calendar days before each planned operation date.

2.4.2.4. Modifications to existing laser systems or changes to current operating plans should be discussed with Range Safety during the planning phase to determine the need for additional data requirements and establish mutually agreeable lead times for submission of additional data.

2.4.3. Laser Operational Procedures:

2.4.3.1. Avoidance Volume:

2.4.3.1.1. The avoidance volume shall encompass that portion of the laser beam that is capable of causing either permanent or temporary ocular impairment.

2.4.3.1.2. The computation of the avoidance volume radial distance from the center of the laser beam shall consider, at a minimum, the following variables:

2.4.3.1.2.1. Time delays between aircraft detection and laser termination.

2.4.3.1.2.2. Average aircraft speeds.

2.4.3.1.3. Laser operating parameters and the reliability of system controls.

2.4.3.1.4. Laser beam azimuth and elevation restrictions shall be defined so that the laser beam avoidance volume is constrained to airspace for which an approved surveillance capability has been established.

2.4.3.2. Airspace Surveillance:

2.4.3.2.1. Organizations conducting laser operations shall provide for an airspace surveillance capability and procedures that ensure the laser operation can be terminated before a non-participating aircraft enters the pre-defined laser beam avoidance volume.

2.4.3.2.2. The American National Standard Institute (ANSI) ANSI Z136.1, *Safe Use of Lasers*, paragraph 4.3.11.2, and ANSI Z136.6, *Safe Use of Lasers Outdoors*, paragraph 4.6.1. require coordination with the Federal Aviation Administration when laser programs include the use of Class 3a, 3b, and 4 lasers within navigable airspace. For Range Safety purposes, air-

space control is a desirable safety measure; however, it is considered a secondary protection measure to surveillance requirements. Airspace controls shall be initiated by Range Safety when the value added to safety is justifiable.

2.4.3.3. Weather Constraints. The laser operation shall be terminated during periods when weather conditions obstruct or adversely affect an approved surveillance method.

2.4.4. DEP Data Package Requirements:

2.4.4.1. General Data. The following data are required for each operation or group of operations. Additional data may be required depending on the laser system.

2.4.4.1.1. Complete description of surveillance methods, surveillance range limits, and a description of the procedures used to terminate laser operations when necessary.

2.4.4.1.2. General information on the purpose of the operation.

2.4.4.1.3. Description of the laser and its operation.

2.4.4.1.4. Laser classification in accordance with ANSI Z136.1.

2.4.4.1.5. Description of operation scenarios and proposed target areas.

2.4.4.1.6. Copies of safety analyses and test procedures conducted on the system.

2.4.4.1.7. Laser Emission Characteristics:

2.4.4.1.7.1. Mode of operation (continuous wave or pulsed).

2.4.4.1.7.2. Wavelength (nanometers).

2.4.4.1.7.3. Energy per pulse in Joules for pulsed lasers or power in watts for continuous wave lasers.

2.4.4.1.7.4. Pulse repetition frequency (Hertz).

2.4.4.1.7.5. Pulse width and separation (seconds).

2.4.4.1.7.6. Beam diameter – the diameter of a circular beam at a point where the intensity drops to 1/e (0.368) of its maximum value usually located at the exit aperture or at the waist if convergent beam (centimeters).

2.4.4.1.7.7. Beam divergence angle at the aperture or waist (radians).

2.4.4.1.8. Number and designation of laser operations to which the proposed operation applies.

2.4.4.1.9. A statement indicating whether the proposed operation is similar in its safety aspects to that of some prior operation for which documentation is available.

2.4.4.1.10. Intended operation dates.

2.4.4.1.11. Functional description of the target acquisition and laser firing process and of any error/failure detection and correction or termination capability, including its reliability and response time.

2.4.4.2. Scenario Type. The scenario type can be any combination of the following:

2.4.4.2.1. Fixed laser and/or target.

2.4.4.2.2. Moving laser and/or target.

2.4.4.3. Laser and Target(s) Position Data:

2.4.4.3.1. Fixed - latitude, longitude, and altitude where laser beam exits the protective housing of each target.

2.4.4.3.2. Moving - position and velocity vector versus time of each object in an Earth Centered Rotating (EFG) Coordinate System.

2.4.4.4. Nominal Operation Scenario Data. The following information shall be provided:

2.4.4.4.1. Desired operating azimuth and elevation sectors.

2.4.4.4.2. Event times; for example, acquisition, arming, and firing on/off times.

2.4.4.4.3. Duration of each laser firing (seconds).

2.4.4.4.4. Slew rate (radians/seconds).

2.4.4.4.5. Hardware and software stops (angles from forward direction, radians).

2.4.4.4.6. Pointing accuracy (radians); brief description of laser beam pointing aids including their location.

2.4.4.4.7. Laser platform/vehicle attitude control accuracy (static, radians; dynamic, radians/seconds).

2.4.4.5. Target Data:

2.4.4.5.1. Target size - radius or height, width, and length.

2.4.4.5.2. Orientation - angle of each target surface with respect to the incident beam.

2.4.4.5.3. Type of reflection possible, such as specular or diffuse.

2.4.4.5.4. Reflection coefficients.

2.4.4.6. Exposure Controls. Exposure controls shall be calculated in accordance with ANSI Z136.1.

2.4.4.6.1. Maximum permissible exposure (MPE) level, nominal optical hazard distance in vacuum, and other applicable hazard ranges for each laser.

2.4.4.6.2. Description of the maximum region around each target that can be subjected to the hazard during a nominal operation.

2.4.4.6.3. Reflection characteristics of other significant objects in the hazard region around each target. The hazard region is the zone where the laser radiation levels may exceed the MPE level.

2.4.4.7. Risk Study. In some instances, laser operations may include test parameters or characteristics that may not allow for the laser beam to be safely contained within a predicted control volume. In such cases, Range Safety may require a risk study. If a risk study is required, the following data shall be submitted:

2.4.4.7.1. Probability of Occurrence Data. The probability of occurrence versus time of operation for each of the following generic hazard modes (modes of beam control error or failure): Pointing Error, Inadvertent Slewing, Premature Firing, Delayed Firing, Beam Focusing Error,

Loss of Focus, and other modes such as Wrong Target Acquisition applicable to the system. If the probability of occurrence is non-zero for any of these hazard modes, then probability distributions for the random hazard mode parameters describing how each mode can occur over time shall be provided. The following parameters describe each of the stated failure modes:

2.4.4.7.1.1. Pointing Error Hazard Mode. Offset angle (radians) between the correct laser system to target pointing direction and the incorrect pointing direction (angle assumed constant during a firing).

2.4.4.7.1.2. Inadvertent Slewing Hazard Mode:

2.4.4.7.1.2.1. Time (seconds) during firing at which the inadvertent slewing starts.

2.4.4.7.1.2.2. Azimuth angle (radians measured from North) of the slew plane; it is assumed that, over time, the laser-to-target line remains contained in a plane.

2.4.4.7.1.2.3. The angular rate (radians/seconds) of slewing in the plane (rate assumed constant).

2.4.4.7.1.2.4. Duration of the slewing (seconds), if other than that of the nominal firing time remaining after the start of the slewing.

2.4.4.7.1.3. Premature Firing Mode. The number of seconds before the nominal start time that laser firing occurs.

2.4.4.7.1.4. Delayed Firing Termination Mode. The number of seconds after the nominal termination time that laser cutoff occurs.

2.4.4.7.1.5. Beam Focusing Error Mode. The range (meters) along the laser-to-target vector at which the convergent beam is misfocused; the incorrect range can either be too long or too short relative to the nominal focus range.

2.4.4.7.1.6. Loss of Focus Mode:

2.4.4.7.1.6.1. Time (seconds) during firing at which the loss of focus occurs.

2.4.4.7.1.6.2. Beam divergence angle (radians) that measures the spreading of the beam (assumed to remain centered on the laser-to-target vector).

2.4.4.7.2. Failure Modes, Effects, and Criticality Analysis:

2.4.4.7.2.1. Applicable hazard modes shall be defined and documented by a failure modes, effects, and criticality analysis (FMECA) in accordance with MIL-STD-882, **Department of Defense Standard Practice for System Safety**, or the equivalent.

2.4.4.7.2.2. Their probabilities of occurrence and the probability distributions of their descriptive parameters shall be quantified with fault tree analysis or the equivalent.

2.4.4.7.2.3. The level of analysis conducted in each case shall be the level at which appropriate component error/failure data are available.

2.4.4.7.2.4. If necessary for confidence in the results, analyses of the effects of the uncertainties in the component data shall be carried out.

2.4.4.7.3. Alternative Data Submission. The Range User may arrange to have the risk study done by Range Safety. The following data shall be provided to support this option:

2.4.4.7.3.1. System design description and performance data and functional and reliability block diagrams for portions of the system affecting beam control, including platform attitude control

2.4.4.7.3.2. Associated component (including hardware, software, and human) reliabilities or, at a minimum, component and component environment descriptions allowing the estimation of these reliabilities

2.4.5. Coordination with the Strategic Command Control Center. Coordination with the Strategic Command CMOC/J3SX is required for all Class 3 and 4 lasers operated outside of a confined laboratory environment. Unless waived by the Strategic Command CMOC/J3SX, firing time coordination for those systems shall be accomplished to verify that on-orbit objects of national interest are not affected by the laser operation.

2.5. Large Nuclear Systems Approval and Data Requirements. Range Users employing radioactive materials that exceed the limits established by the Office of Science Technology Policy (OSTP) shall comply with Presidential Directive/National Security Council 25, *Scientific or Technological Experiments with Possible Large Scale Adverse Environmental Effects and Launch of Nuclear Systems into Space*. The Range User shall provide Range Safety with a copy of the following documents. Nuclear system design, test, and documentation requirements are also addressed in Chapter 9 of Volume 3 of this publication.

2.5.1. Environment Impact Statement: L-3 years.

2.5.2. Final Safety Analysis Report: L-1 year.

2.5.3. Interagency Nuclear Safety Review Panel (INSRP) Safety Evaluation Report: L-7 months. In the event that the INSRP is not impaneled by the OSTP, the provisions of the latest version of AFI 91-110, *Nuclear Safety Review and Launch Approval for Space or Missile Use of Radioactive Material and Nuclear Systems*, shall be performed by the Chief, Weapons, Space and Nuclear Safety Division and the results provided to Range Safety in lieu of the INSRP Safety Evaluation Report.

2.5.4. Certification of Presidential Approval for Flight: L-10 days. A copy of the OSTP approval letter or the National Security Council approval letter meets this certification requirement.

CHAPTER 3

PROGRAM-SPECIFIC FLIGHT ANALYSES

3.1. Trajectory Analysis:

3.1.1. General. The Range User shall perform a trajectory analysis to determine a vehicle's nominal trajectory and potential three-sigma trajectory dispersions about the nominal trajectory. The Range User's trajectory analysis shall also determine, for any time after liftoff, the limits of a launch vehicle's normal flight. *Normal flight* is defined as a properly performing vehicle whose real-time IIP does not deviate from the nominal IIP by more than those of three-sigma dispersed trajectories generated according to Attachment 1, A1.2.4 of this volume.

3.1.2. Trajectory Analysis Products:

3.1.2.1. Ballistic Missiles and Space Vehicles:

3.1.2.1.1. Ballistic Missile and Space Vehicle PFDP. The following data are required in addition to the data requirements specified in 2.2.3.

3.1.2.1.1.1. Nominal Trajectory. Position and velocity vectors as a function of time from liftoff until the vehicle attains an altitude of 100,000 feet (may vary depending on the program). If position and velocity components are not available, ground range and altitude may be substituted for the position vector, and the total earth-fixed velocity and flight path angle may be substituted for the velocity vector. The data should be provided in time increments no larger than 5 seconds (may vary depending on the program).

3.1.2.1.1.2. Maps:

3.1.2.1.1.2.1. A map showing the planned vacuum locus of impact points for the intended flight azimuth or azimuth sector. The vacuum impact points at times of discrete events, such as arming of engine cutoff circuits, ignition of upper stages, firing of retro-rockets, and the end of burns that occur before orbital insertion, shall be indicated.

3.1.2.1.1.2.2. A map showing the best estimates of mean impact points and the three-sigma drag-corrected impact dispersion area for each jettisoned body.

3.1.2.1.1.3. Orbit Parameters and Sequence of Events. The following data should be provided for space vehicles only:

3.1.2.1.1.3.1. Apogee, perigee, period, and inclination of intended orbits.

3.1.2.1.1.3.2. The approximate times from liftoff when engine cutoff circuits are armed, when upper stages will be cutoff by backup devices, and when control modes will be switched.

3.1.2.1.2. Ballistic Missile and Space Vehicle FFDP. The following data are required in addition to the data requirements specified in 2.2.4:

3.1.2.1.2.1. Trajectories. These requirements identify the types of trajectories required for the following flight plans. All trajectories shall be developed using the procedures and format described in Attachment 1 of this volume.

3.1.2.1.2.1.1. Single Flight Azimuths. See Attachment 1 of this volume, Table A1.1 (Items 1-8).

3.1.2.1.2.1.2. Variable Flight Azimuths. Space vehicle launches with variable flight azimuths shall provide a complete set of firing tables detailing launch times and flight azimuths for each day of the launch window. See Attachment 1 of this volume, Table A1.2.

3.1.2.1.2.1.3. Multiple Liquid Propellant Engines Thrusting at Liftoff. For single or variable azimuth flight plans with launch vehicles having multiple liquid propellant engines that normally thrust at liftoff, the trajectories in Table A1.3 of Attachment 1 of this volume are required for engine-out (not-thrusting) conditions. Range Safety shall specify the precise engine-out condition(s) after the vehicle configuration is known.

3.1.2.1.2.2. Jettisoned Body Data. Nominal impact point, associated drag data, and impact dispersion data for each jettisoned body. (See Attachment 4 of this volume.)

3.1.2.1.2.3. Sequence of Events. Times from liftoff of discrete events such as ignition, cut-off, and separation of stages, firing of ullage rockets, jettisoning of components, firing of separation rockets, initiation and termination of various control and guidance modes, starting and ending of coast periods and control modes, arming of engine cutoff circuits, and settings for backup engine cutoff signals.

3.1.2.1.2.4. High Q Flight Region. A statement indicating the flight time interval when the vehicle is experiencing the "high q" flight regime. This *high q flight region* is defined as the time during flight when the dynamic pressure can cause vehicle aerodynamic breakup during a malfunction turn with the result of creating little or no crossrange displacement.

3.1.2.1.2.5. Orbital Parameters for Space Vehicles:

3.1.2.1.2.5.1. Apogee, perigee, inclination, and period of orbits to be achieved; the time, altitude, latitude, and longitude of the submissile point for injection events such as ignition and cutoff of each stage, separation of payload, and reignition of upper stages.

3.1.2.1.2.5.2. The state vector (position and velocity components) at the beginning and ending of each thrusting phase after initial orbital insertion.

3.1.2.1.2.5.3. The state vector for any separated stage or component at the beginning of its final coast or free-flight phase.

3.1.2.1.2.6. Approximate elapsed time from the receipt of an FTS signal at the command antenna until the FTS charges explode.

3.1.2.2. Cruise Missiles and Remotely Piloted Vehicles. In general, cruise missile operations involving intentional land overflight (except for launch and landing) will not be approved. In highly unusual situations where the operation objectives dictate otherwise and preliminary flight plan approval has been granted, the information requested in 3.1.2.2.2.2 will be used to establish guidelines or limits for land overflight. The permissible limits will depend not only on this information but also on estimates of overflight hazards, the operation objectives, and the importance of these objectives. The following items are required for each flight or group of similar flights and shall be updated as vehicle configuration changes occur or revised information becomes available.

3.1.2.2.1. Cruise Missile and Remotely Piloted Vehicle PFDP. The following data are required in addition to the data requirements specified in 2.2.3:

3.1.2.2.1.1. Position and velocity vectors expressed in the coordinate system defined in Attachment 1, A1.2.1 of this volume as a function of time from launch until cruise altitude or a cruise condition is reached. If position and velocity components are not available, ground range and altitude may be substituted for the position vector, and the total earth-fixed velocity and flight path angle may be substituted for the velocity vector. The data shall be provided in time increments no larger than 5 seconds. If trajectory data cannot be provided, the steepness of the trajectory in the launch area shall be compared with the trajectory from any prior similar operation.

3.1.2.2.1.2. A map showing the expected flight path over the earth's surface. Times are to be indicated at regular intervals along the path.

3.1.2.2.1.3. A graph showing an altitude profile correlated with the flight path. Times are to be indicated at regular intervals along the path.

3.1.2.2.1.4. A map showing the estimate of nominal impact points and three-sigma drag-corrected impact dispersion areas for each jettisoned body.

3.1.2.2.2. Cruise Missile and Remotely Piloted Vehicle FFDP. The following data are required in addition to the data requirements specified in 2.2.4:

3.1.2.2.2.1. General Data:

3.1.2.2.2.1.1. General information concerning the nature and purpose of the flight.

3.1.2.2.2.1.2. A scaled diagram of the general arrangements and dimensions of the vehicle.

3.1.2.2.2.1.3. Tracking aids, such as S- or C-Band transponder or GPS receiver and telemetry transmitter, in the vehicle that can be used for flight safety purposes; the stage or section where each is located.

3.1.2.2.2.1.4. Trajectory deviations or other conditions beyond which the Range User is willing to accept flight termination action even though the vehicle has not reached a dangerous position or attitude.

3.1.2.2.2.1.5. Approximate elapsed time from the receipt of an FTS signal at the command antenna until FTS explosive charges explode or the recovery sequence is initiated.

3.1.2.2.2.1.6. Graphs of fuel weight (pounds) versus time (seconds or minutes).

3.1.2.2.2.1.7. Graphs of gross weight (pounds) versus time (seconds or minutes).

3.1.2.2.2.1.8. Graphs of maximum cruising speed (feet/seconds) versus altitude (feet).

3.1.2.2.2.2. Land Overflight Data:

3.1.2.2.2.2.1. The flight azimuth limits or the maximum deviations from the nominal flight path for which the primary operation objectives can be met.

3.1.2.2.2.2. The flight azimuth limits or the maximum deviations from the nominal flight path for which a useful operation can be accomplished, even though the vehicle is outside the normal three-sigma limits.

3.1.2.2.2.3. The operation objectives that will not be met or the extent to which primary objectives will be degraded if land overflight is not permitted when the missile is outside the three-sigma normal limits.

3.1.2.2.2.4. Circumstances or types of malfunctions that can cause the missile to fly outside the three-sigma limits of normality but still accomplish useful objectives.

3.1.2.2.2.5. The probability of occurrence of the malfunctions listed in response to the requirements in 3.1.2.2.2.4.

3.1.2.2.3. Trajectories. These requirements identify the types of trajectories required for the following flight plans. All trajectories are to be developed using the procedures and format described in Attachment 1 of this volume.

3.1.2.2.3.1. Single Flight Azimuths. See Attachment 1, Table A1.1 of this volume.

3.1.2.2.3.2. Variable Flight Azimuths. Operations with variable flight azimuths shall provide a complete set of firing tables detailing launch times and flight azimuths for each day of the launch window. See Attachment 1, Table A1.2 of this volume.

3.1.2.2.3.3. Multiple Liquid Propellant Engines Thrusting at Ignition. For single or variable azimuth flight plans with vehicles having multiple liquid propellant engines that normally thrust at liftoff, the trajectories in Table A1.3 of Attachment 1 of this volume are required for engine-out (not thrusting) conditions. Range Safety shall specify the precise engine-out conditions after the vehicle configuration is known.

3.1.2.2.4. Jettisoned Body Data. Nominal impact point, associated drag data, and impact dispersion data for each jettisoned body. (See Attachment 4 of this volume.)

3.1.2.2.5. Sequence of Events. Using the launch or drop time as the zero reference, time of discrete events such as ignition, cutoff, separation of booster stages, jettisoning of components, starting and ending of control modes, and initiation of recovery devices.

3.1.2.3. Small Unguided Rockets and Probe Launch Vehicles. The term *small unguided rocket* is not precisely defined here; it generally refers to one- or two-stage rockets having maximum impact ranges less than 100 nautical miles. Small rockets are not required to carry FTSs when dispersion analyses and control of launch conditions indicate that all vehicle components can be contained within predetermined safe areas. Unguided rockets of more than two stages or with impact ranges greater than 100 nautical miles are required to carry an FTS. In this event, the data requirements specified in 3.1.2.1. for ballistic missiles and space vehicles shall apply. The following vehicle-related items are required for each rocket flight or group of similar flights and shall be updated as vehicle configuration changes occur or revised information becomes available.

3.1.2.3.1. Small Unguided Rocket and Probe Launch Vehicle PFDP. The following data are required in addition to the requirements in 2.2.3:

3.1.2.3.1.1. Burn time of each stage.

3.1.2.3.1.2. Graphs of impact range versus launch elevation angle for the planned elevation angle sector.

3.1.2.3.1.3. Graphs of ground range versus altitude for the planned elevation angle sector.

3.1.2.3.1.4. Proposed flight azimuth limits and elevation angle limits.

3.1.2.3.1.5. Summary of past vehicle performance giving number launched, launch location, number that performed normally and number that malfunctioned, behavior and impact location for those that malfunctioned, nature of malfunction and corrective action; this requirement can be met by submission of portions of 2.2.3.3.

3.1.2.3.2. Small Unguided Rocket and Probe Launch Vehicle FFDP. The following data are required in addition to requirements specified in 2.2.4:

3.1.2.3.2.1. General Data:

3.1.2.3.2.1.1. General information concerning the purpose and objectives of the operation, such as data to be obtained, number of launches planned, and a brief description of the payload, giving approximate weights.

3.1.2.3.2.1.2. Scaled diagram of the vehicle.

3.1.2.3.2.1.3. Geodetic latitude and longitude of launch point or launcher.

3.1.2.3.2.1.4. Desired Launch Azimuth and Launch Elevation Angles. Provide the variation in azimuth and elevation angles that are acceptable from the standpoint of the operation objectives. Indicate which of the operation objectives actually determine the acceptable limits for azimuth and elevation angles.

3.1.2.3.2.1.5. A brief description of the type of launcher; for example zero length or short rail, travel distance of the rocket to clear the launcher, the amount of effective guidance, launcher adjustments available in quadrant elevation angle (QE) and azimuth, and the smallest increment for these adjustments.

3.1.2.3.2.1.6. Total vehicle weight at liftoff.

3.1.2.3.2.1.7. Total propellant weight in each stage at liftoff.

3.1.2.3.2.1.8. Inert weight of each stage and separable component after burnout or jettison.

3.1.2.3.2.2. Jettisoned Body Data. Nominal impact point, associated drag data, and impact dispersion data for each jettisoned body. See Attachment 4 of this volume.

3.1.2.3.2.3. Wind Effects Data. In most cases, wind is the largest independent factor causing displacement of unguided vehicle impact points. Accompanied by tabulations, charts, and a comprehensive discussion of their formulation, the following data are required to predict the magnitude and direction of this effect:

3.1.2.3.2.3.1. Ballistic wind-weighting factors versus altitude in feet. The effects of booster and first-stage wind drifts are of prime importance since the first-stage motor impact point is usually near the launch site. The wind-weighting factor shall be presented in percent of wind effect for specific wind altitude intervals or for specific alti-

tude interval as percentage of the total wind effect. The ballistic wind-weighting factors shall include the effects of both weather cocking and drift.

3.1.2.3.2.3.2. Change in the nominal impact point location due to missile weather cocking and drift as a result of ballistic winds (head, tail and cross; or resultant wind effect). The deviation is required in feet or nautical miles per foot per second of the wind. Since deviations vary significantly with a change in launch quadrant elevation angle (QE), values shall be supplied in a table of launcher QE versus unit wind effect. The table shall cover the range of elevation angles for which launches are to occur with an elevation angle interval no greater than 2 degrees and include plus and minus 12 degrees from the desired resultant QE up to a maximum launcher setting of 88 degrees.

3.1.2.3.2.3.3. Launcher adjustment curve or launcher tilt effect to correct the launcher in azimuth and elevation for wind effects. A discussion of methods to be used in adjusting the launcher settings to compensate for winds is required. This data is required only if the Range User desires to adjust the launcher azimuth and elevation to correct for wind effects and shall be supplied for all desired resultant QEs. Wind compensation minimizes the area clearance problem by maintaining a constant impact point. A thorough description of the correction method and the expected accuracies to be achieved are required in addition to the proper curves and tabulation data.

3.1.2.3.2.3.4. A graphical and tabular presentation of the impact point displacement due to earth rotation versus QE. Calculations for this information are based on the latitude of the launcher and the desired launch azimuth. The table shall cover the range of elevation angles for which launches are to occur with an elevation angle interval no greater than 2 degrees and include plus and minus 12 degrees from the desired resultant QE up to a maximum of 88 degrees.

3.1.2.3.2.3.5. When a computer program is used to perform the calculation required for adjustment of the launcher in QE and azimuth or to verify the impact predictions of all stages, the Range User shall include a discussion of the intended use of the program. If the Range User uses one of the computer programs available at the range, Range Safety should be consulted to make sure that requirements in 3.1.2.3.2.3.1 are presented in a form compatible with the computer input requirements.

3.1.2.3.2.4. Analyses for Long Range Probes. All analyses for long-range probes (500 nautical miles plus) shall be calculated using a rotating spherical or ellipsoidal gravity field. In contrast to the majority of probe vehicles, long-range probes normally require an FTS incorporated into the vehicle. The data requirements are the same as those specified for 3.1.2.1 for guided ballistic missiles. A debris risk analysis (3.4) is required to evaluate requests to waive the requirement for an FTS on a long-range probe vehicle.

3.1.2.3.2.5. Trajectory Requirements. See Attachment 1 of this volume.

3.1.2.3.2.6. Graphs. In addition to the tabular nominal trajectory data, graphs of the following shall be provided for each stage and payload weight:

3.1.2.3.2.6.1. Impact range versus launch elevation angle (feet or nautical miles versus degrees).

3.1.2.3.2.6.2. Apogee altitude versus launch elevation angle (feet or nautical miles versus degrees).

3.1.2.3.2.6.3. Altitude versus ground range (feet versus feet or nautical miles).

3.1.2.4. Aerostats and Balloon Systems. These trajectory and performance data requirements apply to large unmanned, untethered, and tethered aerostats and balloons. They do not apply to small weather balloons and other such objects that are released routinely throughout the country and the world for scientific purposes.

3.1.2.4.1. Aerostat and Balloon System PFDP. The following data are required in addition to the requirements in 2.2.3:

3.1.2.4.1.1. Description of the proposed flight plan giving particulars about the location and boundaries of the proposed test area, time sequence and description of significant events, flight duration, altitude, and speed limits.

3.1.2.4.1.2. Method of control, including emergency control procedures.

3.1.2.4.2. Aerostat and Balloon System FFDP. The following data are required in addition to requirements in 2.2.4:

3.1.2.4.2.1. Untethered Aerostats and Balloons. Large unmanned and untethered aerostats and/or balloons flight tested on the range shall carry an approved FTS capable of causing rapid deflation upon command. The following vehicle-related items are required for each flight or group of similar flights. The data shall be updated as vehicle configurations vary or revised information becomes available.

3.1.2.4.2.1.1. Detailed information concerning the purpose and objectives of the mission, data to be obtained, number of flights planned, and proposed flight dates.

3.1.2.4.2.1.2. A statement indicating whether the vehicle and proposed flights are similar to prior flights either on the range or elsewhere.

3.1.2.4.2.1.3. A description of the vehicle giving dimensions, component weights, materials, and characteristics of propulsion, control, and recovery systems, including estimates of system reliability.

3.1.2.4.2.1.4. Accuracy of the guidance and control system in maintaining the desired aerostat position.

3.1.2.4.2.1.5. Description and location of the FTS.

3.1.2.4.2.1.6. Description and location of tracking aids.

3.1.2.4.2.1.7. Wind restrictions for launch and flight.

3.1.2.4.2.1.8. Description of the Proposed Flight Plan:

3.1.2.4.2.1.8.1. Location of the proposed test area.

3.1.2.4.2.1.8.2. Graph of altitude (feet) versus time (minutes) from release until float altitude is reached.

3.1.2.4.2.1.8.3. Total duration of flight.

3.1.2.4.2.1.8.4. Graph of altitude (feet) versus time (minutes) for the entire operation or indication of how altitude will be varied throughout the flight.

3.1.2.4.2.1.8.5. Maximum possible altitude without bursting.

3.1.2.4.2.1.8.6. Maximum aerostat speed in still air as a function of altitude.

3.1.2.4.2.1.8.7. Location and size of impact dispersion areas for any bodies jettisoned during flight.

3.1.2.4.2.1.8.8. Location and size of final impact dispersion area or intended recovery area.

3.1.2.4.2.1.9. Drag coefficient (C_d) versus Mach number giving reference area and weight for each jettisoned body and for the entire vehicle (or resulting components) after activation of the FTS; the same data should also be provided for a normal recovery sequence if different from the above.

3.1.2.4.2.2. Tethered Aerostats and Balloons. Tethered aerostats and/or balloons shall carry an approved automatic FTS that will cause rapid deflation if the balloon escapes its mooring or the tether breaks. The following vehicle-related items are required for each flight or group of similar flights. The data shall be updated as vehicle configurations vary or revised information becomes available.

3.1.2.4.2.2.1. Detailed information concerning the purpose and objectives of the mission, data to be obtained, number of flights planned, and proposed flight dates.

3.1.2.4.2.2.2. Description and location of the FTS.

3.1.2.4.2.2.3. Description of the mooring tethering system giving lengths and breaking strength of the tether.

3.1.2.4.2.2.4. Operational method of measuring tension in the tether.

3.1.2.4.2.2.5. Wind and weather restriction for launch and flight.

3.1.2.4.2.2.6. Maximum float altitude.

3.1.2.4.2.2.7. Planned and maximum duration of flight.

3.1.2.5. Projectiles, Torpedoes, Air-Dropped Bodies, and Small Devices. These data requirements apply to projectiles, torpedoes, air-dropped bodies, and small devices that normally would not contain an FTS and that may or may not be propulsive.

3.1.2.5.1. Projectiles, Torpedoes, Air-Dropped Bodies, and Small Device PFDP. The following data are required in addition to the requirements in 2.2.3:

3.1.2.5.1.1. Description of the proposed flight plan giving particulars about the location and boundaries of the proposed operation area, time sequence, and description of significant events.

3.1.2.5.1.2. Burn or thrust time of each thrusting item.

3.1.2.5.1.3. Graphs of the impact range (nautical miles) versus launch elevation angle (degrees) for the planned elevation angle sector or drop altitude sector.

3.1.2.5.1.4. Ground range (nautical miles) versus altitude (feet) for the planned elevation angle sector.

3.1.2.5.1.5. Nominal impact location in geodetic latitude (degrees) and longitude (degrees) for each jettisoned or impacting body.

3.1.2.5.1.6. Estimates of the three-sigma dispersion area in downrange (feet or nautical miles) and crossrange (feet or nautical miles) measured from the nominal impact location

3.1.2.5.2. Projectiles, Torpedoes, Air-Dropped Bodies, and Small Device FFDP. The following data are required in addition to the requirements specified in 2.2.4:

3.1.2.5.2.1. Detailed information concerning the purpose of the operation, data to be obtained, description of objects, number of operations in the program, and proposed operation dates.

3.1.2.5.2.2. Scaled diagram of vehicle.

3.1.2.5.2.3. Latitude and longitude of the desired drop point and the maximum region around the point where launch could occur. This information may be provided in distances downrange and crossrange relative to the expected drop point or by providing the geodetic latitude and longitude of the corners of the area.

3.1.2.5.2.4. Jettisoned Body Data. See Attachment 4 of this volume.

3.1.2.5.2.4.1. Latitude and longitude of the desired impact or target point.

3.1.2.5.2.4.2. The three-sigma downrange and crossrange impact dispersions or circular error probability (CEP) of impact points for each impacting body. This information may be provided in distances downrange and crossrange relative to the expected launch point or by providing the geodetic latitude and longitude of the corners of the area.

3.1.2.5.2.4.3. For air-dropped bodies, the effect of the three-sigma aircraft position and velocity error at drop.

3.1.2.5.2.4.4. If the body descends on a parachute or other device, drag data before and after chute opening.

3.1.2.5.2.5. For air-dropped bodies, the data items in 3.1.2.6 shall be provided.

3.1.2.5.2.6. The effect of head wind, tail wind, and cross wind on the impact point location in terms of displacement distance (feet or nautical miles) per knot (or feet/seconds) of wind.

3.1.2.5.2.7. Trajectory Requirements. The following trajectory data items are required for each operation or group of similar operations:

3.1.2.5.2.7.1. A graph of the nominal trajectory, including a plot of altitude (feet) versus downrange distance (feet or nautical miles); timing marks (seconds), including the impact time, shall be indicated along the trajectory; separate graphs are required for each planned launch point or other condition.

3.1.2.5.2.7.2. The maximum horizontal distance (feet or nautical miles) that can be traveled by the objects from the launch point to impact.

3.1.2.5.2.7.3. If the objects descend on a parachute, a plot of altitude (feet) versus range (feet or nautical miles) for the case where the chute fails to open.

3.1.2.6. Air-Launched Vehicle Data Requirements. These data requirements apply to all programs that use an aircraft as the originating platform for the operation. If the air-launched vehicle is a space vehicle, the requirements of 3.1.2.1. also apply.

3.1.2.6.1. General Data Requirements:

3.1.2.6.1.1. General information concerning the nature and purpose of the flight.

3.1.2.6.1.2. The minimum weather requirements for the operation.

3.1.2.6.1.3. Emergency Requirements. Special emergency requirements shall be specified, including:

3.1.2.6.1.3.1. Search and rescue support requirements.

3.1.2.6.1.3.2. Emergency Recovery Plan, including minimum field length(s).

3.1.2.6.1.3.3. Description of ditching characteristics, if known.

3.1.2.6.1.3.4. Description of secondary communication procedures to be used in the event of primary communications failure.

3.1.2.6.1.3.5. If structural flight and system tests are to be conducted, any weather minimums and special requirements.

3.1.2.6.2. Aircraft Data Requirements:

3.1.2.6.2.1. Aircraft type (such as chase, tanker), aircraft registration number/serial number, and the performance capability of aircraft, such as turn rate, climb rate, and velocity.

3.1.2.6.2.2. For other than level flight launches, an additional statement describing how the aircraft path angle and launch azimuth are determined for vehicle release.

3.1.2.6.2.3. Description of guidance system used and how ignition and altitude are determined.

3.1.2.6.3. Aircraft Flight Plan Data Requirements:

3.1.2.6.3.1. Description of drop aircraft flight plan, such as aircraft flight azimuth (degrees from true North), speed (knots), altitude (feet), flight path angle (degrees) of the velocity vector relative to local horizontal at the vehicle launch point; a map showing the flight path over the earth's surface with altitudes and speeds indicated at appropriate way points.

3.1.2.6.3.2. The expected maximum region around the launch point (a launch point envelope where the operation is conducted) provided as distances in altitude, downrange, uprange, and crossrange relative to the expected launch point and perpendicular to the launch azimuth or by the geodetic latitude and longitude of the corners of the launch box.

3.1.2.6.3.3. A definition and description of events occurring before vehicle release and to the time of vehicle engine ignition.

3.1.2.6.3.4. Predicted impacts of jettisoned hardware associated with the vehicle launch system and their impact dispersion.

3.1.2.6.3.5. For ballistic air-launched bodies, altitude of the aircraft, true air speed, and dive angle beginning 60 seconds before launch and continuing through launch.

3.1.2.6.4. Launched Vehicle Data Requirements:

3.1.2.6.4.1. A nominal flight profile for each stage from launch to impact, showing altitude (feet) versus downrange (feet) is required. Profiles shall include parachute opening, parachute not opening, all unignited and non-separation conditions of the vehicle. Timing marks in seconds shall be indicated on the trajectory, as well as total time of flight for each object dropped. Drag data before and after chute opening shall be provided.

3.1.2.6.4.2. The drop rate of launched vehicles and description of control system used.

3.1.2.6.4.3. Method of booster ignition and position of the vehicle relative to the earth at ignition.

3.2. Malfunction Turn Analysis. These requirements apply to the following programs: ballistic missiles, space vehicles, cruise missiles, remotely piloted vehicles (RPVs), small unguided rockets, and probe launch vehicles.

3.2.1. General. The Range User shall perform a malfunction turn analysis to determine a vehicle's maximum turning capability as a function of trajectory time. The Range User shall use the products of the malfunction turn analysis as input to its range safety analysis and other analyses where it is necessary to determine how far a vehicle's impact point can deviate from the nominal impact point after a malfunction occurs.

3.2.2. Malfunction Turn Analysis Products:

3.2.2.1. Malfunction Turn Analysis PFDP. The Range User shall provide the vehicle maximum turn capability that will cause the furthest distance the vehicle impact point can deviate from nominal if a thrust vector offset or other malfunction were to occur. The corresponding changes in vehicle velocity vector flight path angle and magnitude shall also be provided. The Range User shall generate the detailed information described in Attachment 2 of this volume.

3.2.2.2. Malfunction Turn Analysis FFDP. The Range User shall provide the same information as in the PFDP but updated to reflect performance caused by changes in flight plans or vehicle configuration.

3.3. Debris Analysis. These requirements apply to the following programs: ballistic missiles, space vehicles, cruise missiles, RPVs, small unguided rockets, and probe launch vehicles.

3.3.1. General. The Range User shall perform a debris analysis that identifies inert, explosive, and other hazardous vehicle debris resulting from a vehicle malfunction and from any planned jettison of vehicle components for orbital and suborbital launches.

3.3.2. Debris Analysis Products:

3.3.2.1. Debris Analysis PFDP. The Range User shall provide a preliminary estimate of fragment characteristics such as number, composition, dimensions, and weight due to all potential modes of vehicle breakup such as destruct and aerodynamic loading.

3.3.2.2. Debris Analysis FFDP. The Range User shall generate the detailed information described in Attachment 3 of this volume. In addition, the PFDP shall be updated to reflect any changes in the results presented.

3.4. Debris Risk Analysis . These requirements apply to the following programs: ballistic missiles and space vehicles, cruise missiles and RPVs, and small unguided rockets and probe launch vehicles.

3.4.1. General:

3.4.1.1. The Range User shall perform a debris risk analysis to determine the expected average number of casualties (E_c) to the collective members of the public exposed to inert and explosive debris hazards from the proposed vehicle flight. The results of the debris risk analysis shall be included in the Range User's demonstration of compliance with the public risk criteria of Volume 1 of this publication.

3.4.1.2. Due to the large number of potential variables, it is strongly recommended that the Range User coordinate with Range Safety on the areas that should be covered in the debris risk analysis to facilitate Range Safety approval. This coordination is especially important if the flight plan involves any of the following hazardous conditions:

3.4.1.2.1. Direct overflight of land before thrust termination or orbital insertion.

3.4.1.2.2. Flight so close to land that destruct criteria may be violated by a normal vehicle or debris could impact land if a destruct event were to occur.

3.4.1.2.3. A launch area trajectory so steep that critical coastal areas or launch area facilities cannot be protected by standard destruct criteria without endangering a normal missile.

3.4.1.2.4. A period during flight when land areas cannot be protected from a malfunctioning vehicle because (1) the vehicle has no FTS or premature separation destruct capability or (2) the capability of the flight safety system is surpassed by the vehicle performance.

3.4.2. Debris Risk Analysis Products:

3.4.2.1. Debris Risk Analysis PFDP. The Range User shall generate the reliability and malfunction data requirements of 2.2.3. In addition, the Range User shall generate the following information:

3.4.2.1.1. Computation of IIP dwell time over land.

3.4.2.1.2. Probability of impact density functions for each failure or malfunction mode in terms of downrange and crossrange components.

3.4.2.1.3. A list of all population centers or the population density along the flight path that could have debris impacting on them after a destruct event. The list shall include the identifier of the population center or grid cell, area (A_p) in ft^2 , population center centroid in geodetic latitude and longitude, the total number of persons in the population center (N), and the number of persons in each shelter category within each population center. Population data and shelter statistics shall be provided and substantiated by the Range User if the data is not available from Range Safety. The shelter categories are defined below:

3.4.2.1.3.1. Heavy – Blockhouse bunkers and heavily reinforced structures.

3.4.2.1.3.2. Medium – Buildings with concrete or reinforced roofs, and all floors except the top floor in multi-story buildings.

3.4.2.1.3.3. Light – Single story buildings, trailers, and top floors of multi-story buildings

3.4.2.1.3.4. Exposed – No protection from falling debris.

3.4.2.1.4. Evaluation of casualty area (A_c) based on vehicle breakup analysis.

3.4.2.1.5. Probability of impact (P_i) for each population center computed by summing the individual failure mode probabilities of impact over all fragment groups; the failure rates for each of the failure modes and the IIP dwell time over each population center are included in the computation.

3.4.2.1.6. Casualty expectation (E_c) for each population center. Total population center E_c is computed by summing the E_c values over all fragments affecting each population center. In simplified terms, not accounting for possible sheltering of persons,

$$\text{Total } E_c = N/A_p * \sum_i (P_{Li} * A_{Ci})$$

Where i is a fragment in the fragmentation group

3.4.2.1.7. Sample calculations and supporting documents.

3.4.2.2. Debris Risk Analysis FFDP. The Range User shall provide the same information as in the PFDP but updated to reflect performance caused by changes in flight plans, vehicle configuration, or more accurate analyses.

3.5. Acoustic Analysis. These requirements apply to ballistic missiles, space vehicles, cruise missiles, small unguided rockets, probe launch vehicles, and air-launched vehicles.

3.5.1. Acoustic Analysis Products:

3.5.1.1. Acoustic Analysis PFDP. The Range User shall provide the following information. If the information is not available at the PFDP delivery date, it shall be included as part of the FFDP.

3.5.1.1.1. Acoustic intensity contours above 85 dB at 10 dB intervals that are generated during launch of the vehicle.

3.5.1.1.2. The predominant acoustical bands above 85 dB at distances of .5, 1, 2, and 3 nautical miles surrounding the launch pad.

3.5.1.2. Acoustic Analysis FFDP. The data requirements for the FFDP are the same as those for the PFDP but updated to reflect the performance caused by changes in flight plans, vehicle configuration, or more accurate analyses.

3.6. Sonic Boom Analysis. These requirements apply to ballistic missiles, space vehicles, cruise missiles, small unguided rockets, probe launch vehicles, and air-launched vehicles. In addition to these requirements, the Range User shall comply with the requirements of AFI 13-201, *U.S. Air Force Air-space Management*.

3.6.1. Sonic Boom Analysis Products:

3.6.1.1. Sonic Boom Analysis PFDP. The Range User shall provide the following information. If the information is not available at the PFDP delivery date, it shall be included as part of the FFDP.

3.6.1.1.1. Control Information:

3.6.1.1.1.1. R – distance (feet) from the vehicle where the Near Field Signature (NFS) is determined.

3.6.1.1.1.2. LM - length (feet) of the model of the vehicle.

3.6.1.1.1.3. LR - vehicle length (feet).

3.6.1.1.2. NFS Data With Exhaust Plume. The inclusion of the plume applies only to ballistic missiles and space vehicles.

3.6.1.1.2.1. θ - Roll Angle (degrees) (ground launch).

3.6.1.1.2.2. M – Mach Number.

3.6.1.1.2.3. N – Number of points in NFS.

3.6.1.1.2.4. X – Vehicle station (feet) on model where pressure perturbation was measured.

3.6.1.1.2.5. $\Delta P/P$ – Pressure perturbation divided by ambient pressure.

3.6.1.1.3. Flight Profile Data:

3.6.1.1.3.1. Time (seconds).

3.6.1.1.3.2. Vehicle altitude (feet) above reference ellipsoid .

3.6.1.1.3.3. Geodetic latitude (degrees) of vehicle.

3.6.1.1.3.4. Longitude (degrees) of vehicle.

3.6.1.1.3.5. Vehicle flight path angle (degrees) positive up from the local horizontal.

3.6.1.1.3.6. Vehicle freestream Mach number.

3.6.1.1.3.7. Vehicle heading (degrees) from true North.

3.6.1.1.3.8. \dot{M} – The time rate of change of Mach number (per second).

3.6.1.1.3.9. Time rate of change of flight path angle (degrees/seconds).

3.6.1.1.3.10. Time rate of change of heading (degrees/seconds).

3.6.1.1.3.11. Roll angle (degrees) measured from local horizontal to right wing as viewed from behind the vehicle (air launch).

3.6.1.2. Sonic Boom Analysis FFDP. The data requirements for the FFDP are the same as those for the PFDP but updated to reflect performance caused by changes in flight plans, vehicle configuration, or more accurate analyses.

3.7. FTS Determination Analysis. These requirements apply to ballistic missiles, space vehicles, cruise missiles, small unguided rockets, probe launch vehicles, and air-launched vehicles.

3.7.1. General. The threat from any payload or stage without an FTS shall be analyzed to determine the risk associated with a malfunctioned vehicle whose payload or stage may separate prematurely.

3.7.2. FTS Determination Analysis Products:

3.7.2.1. FTS Determination Analysis PFDP. The Range User shall provide the data and analyses listed below for the payload or stage deemed hazardous by Range Safety. The data and the results of these analyses shall be provided to Range Safety at least three months (time will vary with program) before the time that a waiver of the FTS is required. If the resulting impact dispersions are small enough for inclusion as offsets in the Range Safety destruct computations, there may be no need for a risk study.

3.7.2.1.1. Functional description of structural, mechanical, and electrical inhibits or safeguards for preventing premature separation and ignition of payload or stage propulsion systems; extent to which such inhibits are independent; simplified schematics and operational description of propulsion system ignition circuits; extent to which circuits and systems are shielded.

3.7.2.1.2. Failure modes that can lead to premature separation and/or ignition of upper-stage propulsion systems; probability of occurrence for each failure mode including method of derivation and a fault tree analysis if multiple components or subsystems are involved.

3.7.2.1.3. Probability of stable flight and stability characteristics of prematurely separated and thrusting stage, stage and payload, and payload alone, both within and outside the sensible atmosphere; effects of structural confinement such as payload fairing on prematurely separated upper stage or payload.

3.7.2.1.4. Risk Study. Results of the risk study shall include the impact probability for critical facilities and land areas that can be endangered by the payload or stage before orbital insertion.

3.7.2.1.5. Residual Thrust Dispersion Analysis. The residual thrust dispersion analysis shall show the extent to which the impact points(s) can deviate from nominal if the payload or stage separates prematurely and the propulsion system ignites. Computations are generally required from liftoff until upper stage fuel depletion or orbit insertion.

3.7.2.1.6. Intact Impact Analysis. The intact impact analysis shall address the explosive effects of solid rocket and liquid motors upon ground impact. The Range User shall supply stage or payload data requested by Range Safety to support this analysis. The analysis shall contain piece description, number of pieces, and the range the explosion propels pieces from the motor impact point.

3.7.2.2. FTS Determination Analysis FFDP. The Range User shall provide the same information as in the PFDP but updated to reflect performance caused by changes in flight plans or vehicle configuration.

3.8. Post-Flight Vehicle Performance Analysis. These requirements apply to all programs identified in this volume.

3.8.1. Within three months after an operation has been conducted, the Range User shall provide the Range Safety Office a statement of vehicle performance. This information may be provided in a special report or by supplying performance evaluation documents prepared for other purposes. This information is needed for evaluation of vehicle performance capabilities upon which changes in safety

abort criteria are based and for updating the failure rate information used in the various risk analysis models.

3.8.2. The report(s) shall include the following information:

3.8.2.1. Qualitative statement about the performance of each stage and various subsystems.

3.8.2.2. Failures that occurred and resulting flight conditions produced.

3.8.2.3. Probable cause of failure and corrective action taken.

3.8.2.4. Actual (if available) or estimated impact points for stages.

3.8.2.5. Miss distances for weapon system tests and orbital parameters for space vehicle flights.

3.8.2.6. Comparison of planned and achieved cutoff conditions for each stage.

3.8.2.7. Performance of on-board safety instrumentation.

3.8.2.8. Small Unguided Rockets and Probe Launch Vehicles. The following additional data are required for small unguided rockets and probe launch vehicles:

3.8.2.8.1. Vehicle type and number, launch location, operation number, payload type and weight.

3.8.2.8.2. Actual launcher azimuth and elevation settings (degrees).

3.8.2.8.3. For each stage and payload, the predicted range (nautical miles) from launcher to impact point and the azimuth of the impact point. The impact point prediction is based on the predicted winds at time of launch.

3.8.2.8.4. Actual range (nautical miles) and azimuth (degrees from true North) from the launcher to impact points for all stages and payload(s).

3.8.2.8.5. Actual impact range (nautical miles) for each stage and payload giving components measured along and perpendicular to the predicted impact azimuth. Where a stage is not tracked to impact, the impact point shall be computed using the best estimates of the drag characteristics and of the winds at launch.

3.8.2.8.6. Predicted QE (degrees) of trajectory for each stage.

3.8.2.8.7. Actual QE (degrees) of trajectory for each stage.

3.8.2.8.8. Predicted range (nautical miles) and altitude (feet) of apogee for each stage.

3.8.2.8.9. Actual range (nautical miles) and altitude (feet) of apogee for each stage.

3.8.2.8.10. A tabulation of the reduced wind data used in the launcher-setting calculations giving speed (feet/seconds) and direction (degrees) as a function of altitude (feet).

3.8.2.8.11. A reference list of all documents, graphs, and tabulations that were used in making the launcher-setting calculations (wind-weighting curves, ballistic wind-weighting factors, and unit wind effect).

3.8.2.8.12. Description of the tracking data source.

BILLY R. COLWELL, Col, USAF
Director of Safety

ATTACHMENT 1

TRAJECTORY DATA

A1.1. Introduction. This attachment provides background information and details about Range Safety trajectory requirements. It is applicable to ballistic, space, cruise, remotely piloted, and small unguided vehicles. Range Users should contact Range Safety for flight trajectory data preparation, submittal, and processing. The trajectory and two printouts with a letter of transmittal are required.

A1.2. Trajectory Details:

A1.2.1. XYZ Coordinates. The X, Y, Z, coordinates referred to in Volume 2 shall be referenced to an orthogonal, earth-fixed, left-handed system with its origin at the launch point or at a point on the earth's surface above or below the launch point. The XY plane shall be tangent to the ellipsoidal earth at the origin, the positive X axis shall coincide with the launch azimuth, and the positive Z axis shall be directed away from the earth, and the Y axis shall be positive to the right looking downrange.

A1.2.2. Trajectory Data Item Requirements. The required trajectories from Table A1.1 through Table A1.3 shall be calculated using a 6 degree-of-freedom program. Table A1.4 lists the data items to be provided for each required trajectory. The data items are required in 1-second intervals.

A1.2.2.1. Ballistic Missiles and Space Vehicles. All trajectories except the three-sigma launch area trajectories shall be provided from launch up to a point in flight where effective thrust of the final stage has terminated, or to thrust termination of that stage or burn that places the vehicle in orbit. The launch area trajectories are required from liftoff until the vehicle attains an altitude of 100,000 ** feet.

The double asterisks used in this attachment mean that the magnitude, interval, or duration for the required item varies from program to program. The value given is typical.

A1.2.2.2. Cruise Missiles and Remotely Piloted Vehicles. The data items are required in tabular form in 1-second intervals for the first 2** minutes of flight, in 15-second** intervals from this point until the missile reaches cruise altitude, in 1-minute** intervals throughout the cruise phase until the terminal phase of flight is reached, and at 15-second** intervals thereafter until operation termination or impact. For each program, Range Safety provides the Range User with the specific value to use for each parameter marked with the double asterisks. The time 0.0 seconds shall correspond to first motion for pad-launched missiles and to the instant of drop for air launches.

A1.2.2.3. Small Unguided Rockets or Probe Vehicles. Table A1.4 (Items 5 - 13) lists the data items to be provided for each trajectory from launch until burnout of the final stage for each desired nominal quadrant elevation angle and payload weight. These items shall be provided in tabular form as a function of time with each column of the table containing only a single parameter. Time shall be given at even intervals, not to exceed 1-second increments during thrusting flight, and for times corresponding to ignition, thrust termination or burnout, and separation of each stage. If stage burning times are less than 4 seconds, time intervals should be reduced to 0.2 seconds or less.

A1.2.3. Nominal (Reference) Trajectory. The nominal or reference trajectory is the trajectory that the vehicle would fly if all vehicle parameters were exactly as expected, if all vehicle systems performed exactly as planned, and there were no external perturbing influences.

A1.2.4. Three-Sigma Dispersed Trajectories. The three-sigma dispersed trajectories define the downrange and crossrange limits of normality for the vehicle IIP at any time after launch. The three-sigma trajectories shall be computed using annual wind profiles unless the launch is to be conducted at a particular time of the year and only at that time. Care should be exercised in the selection of the cumulative percentage frequency of the wind profile used for the computation of these trajectories. Selecting a wind profile as severe as the worst wind conditions when a launch would be attempted is usually recommended. In critical instances, this has the disadvantage of limiting the allowable launch azimuth or reducing the allowable launch day winds in the flight safety restrictions for wind drift of vehicle fragments resulting from FTS action. The flight termination criteria allow for as much vehicle deviation due to wind as shown in these trajectories, but do not account for wind conditions that exceed those used in these computations.

Table A1.1. Trajectory Types for Single Flight Azimuths.

Item #	Program	Trajectory Type	Reference
1	All Programs	Nominal or reference.	A1.2.3.
2	Ballistic Missiles and Space Vehicles	Three-sigma maximum-performance	A1.2.4.1.
3		Three-sigma minimum-performance	A1.2.4.1.
4		Three-sigma lateral left	A1.2.4.2.
5		Three-sigma lateral right	A1.2.4.2.
6		Three-sigma steep launch area	A1.2.4.3.
7		Three-sigma lateral launch area	A1.2.4.3.
8		Fuel-exhaustion.	A1.2.4.4.
9	Cruise Missile and Remotely Piloted Vehicles	Three-sigma maximum-altitude. The maximum altitude deviations (feet) above nominal as a function of ground range from the launch or drop point may be substituted for Table A1.4, Item 3.	A1.2.4.1. A1.2.4.1.1.
10		Three-sigma minimum-altitude. The maximum altitude deviations (feet) below nominal as a function of ground range from the launch or drop point may be substituted for Table A1.4, Item 3.	A1.2.4.1. A1.2.4.1.1.
11		Three-sigma lateral. The maximum lateral deviations (feet or nautical miles) from the nominal flight path as a function of ground range from the launch or drop point may be substituted for Table A1.4, Item 3	A1.2.4.2. A1.2.4.2.4.
12		Fuel-exhaustion. Table A1.4, Items 3 and 4, are required from launch or drop until the vehicle reaches a steady-state cruise condition. The three-sigma high-performance trajectory should define the vehicle capability limits in climbing to maximum altitude at the maximum possible rate.	A1.2.4.4. A1.2.4.4.1.

Table A1.2. Trajectory Types for Variable Flight Azimuths.

Item #	Trajectory Type	Reference
1	Nominal, reference, central, or middle trajectory.	A1.2.3.
2	Extreme right-hand nominal or steepest nominal trajectory.	A1.2.3.
3	Extreme left-hand nominal or shallowest nominal trajectory.	A1.2.3.
4	Three-sigma maximum-performance trajectory for the centrally located flight azimuth	A1.2.4.1.
5	Three-sigma minimum-performance trajectory for the centrally located flight azimuth	A1.2.4.1.
6	Three-sigma lateral trajectories for the centrally located flight azimuth	A1.2.4.2.
7	Three-sigma left for smallest flight azimuth	A1.2.4.1
8	Three-sigma right for largest flight azimuth	A1.2.4.1
9	Three-sigma steep launch area	A1.2.4.3.
10	Three-sigma lateral launch area	A1.2.4.3.
11	Fuel-exhaustion	A1.2.4.4.

Table A1.3. Trajectory Types for Multiple Liquid Propellant Engines Thrusting at Liftoff.

Item #	Trajectory Type	Reference
1	Three-sigma steep launch area trajectory with one or more engines not thrusting	A1.2.4.3.
2	Three-sigma lateral launch area trajectory with one or more engines not thrusting	A1.2.4.3.

Table A1.4. Trajectory Data Items.

Item #	Data Item	Comments
1	A brief discussion of the parameters considered, their standard deviations, and all assumptions and procedures used in deriving each of the dispersed trajectories.	
2	A graph and tabular listing of the wind profiles used (wind magnitude and direction versus altitude)	The source of the wind profiles used in the computations shall be identified.

Item #	Data Item	Comments
3	X, Y, Z versus Time (feet and seconds)	Cruise Missile and Remotely Piloted Vehicles: Units are feet or nautical miles and seconds or minutes. After the first 2** minutes of flight, with Range Safety approval, X, Y, Z, may be replaced by ground range along the earth's surface from launch point to sub-missile point versus time, altitude above earth's surface versus time, and cross range displacement from nominal versus time.
4	XDOT, YDOT, ZDOT versus time (feet/seconds and seconds)	Cruise Missile and Remotely Piloted Vehicles: Units are the nearest one-tenth foot/second and seconds or minutes. After the first 2** minutes of flight, with Range Safety approval, XDOT, YDOT, ZDOT may be replaced by speed (feet/second) versus time and path angle (degree) of velocity vector relative to local horizontal versus time.
5	Speed versus time (feet/second and seconds)	
6	Path angle of velocity vector relative to local horizontal versus time (degree and seconds)	
7	Altitude above the sub-vehicle point on the reference spheroid versus time (feet and seconds)	
8	Total weight versus time (pounds and seconds)	
9	Ground range along reference spheroid from the origin (launch point) to a point directly beneath the missile versus time (nautical miles and seconds)	For Small Unguided Rocket or Probe Vehicle: Ground range units are feet.
10	Thrust versus time (pounds and seconds)	
11	Instantaneous impact point data	Geodetic latitude, longitude, impact range (nautical miles) and remaining flight time (seconds) versus time (seconds).
12	Launch azimuth	Degrees measured clockwise from true North.

Item #	Data Item	Comments
13	The name, coordinates, and mean sea level elevation of the coordinate system origin (launch pad).	
14	Name of reference spheroid used in trajectory calculations.	

A1.2.4.1. Generating a Single Composite Three-Sigma Trajectory. To generate a single composite three-sigma trajectory in terms of instantaneous impact range, the following procedure is suggested. If the following procedure is not used, a description of the method used to generate the three-sigma trajectories shall be provided.

A1.2.4.1.1. *Step 1:* Identify individual parameters such as thrust, weight, specific impulse, and atmospheric density that significantly affect the performance of the vehicle IIP. Estimate three-sigma dispersions for these parameters.

A1.2.4.1.2. *Step 2:* Run a series of trajectory computations or simulations where three-sigma values of significant perturbing parameters are introduced one at a time. At a suitable number of time points, tabulate the IIP deviations from nominal that have been caused by perturbing each parameter.

A1.2.4.1.3. *Step 3:* At each time point and direction, calculate the square root of the sum of the squares of all deviations to arrive at the three-sigma IIP deviations.

A1.2.4.1.4. *Step 4:* By further trajectory computations or simulations, generate a thrusting flight trajectory (a three-sigma, no-wind trajectory) that matches as closely as possible the three-sigma deviations calculated in Step 3. This may be done by perturbing only a few key parameters at varying magnitudes throughout the run.

A1.2.4.1.5. *Step 5:* Compute the required three-sigma trajectory using worst case winds together with the parameter magnitudes used to calculate the three-sigma, no-wind trajectory. The wind dispersed trajectories indicate vehicle performance deviations due to the effects of severe winds. This data should be supplied until the vehicle attains an altitude where there is essentially no wind effect. It is usually sufficient to use 100,000 feet as this altitude limit. Computations should not be limited to wind drift but include all wind effects.

A1.2.4.2. Three-Sigma Maximum and Minimum Performance Trajectories. The three-sigma maximum and three-sigma minimum-performance trajectories define at any time after launch the limits of normality as far as impact downrange is concerned. The three-sigma maximum-performance trajectory provides the maximum downrange distance of the vacuum IIP for any given time and the three-sigma minimum-performance trajectory provides the minimum downrange distance of the IIP for any time. In calculating these trajectories, head and tail wind profiles should be used that represent the worst wind conditions for which a launch would be attempted. For any particular time after launch, approximately 99.73 percent of all normal vehicles (assuming a normal Gaussian distribution) that are subjected to the assumed wind will have impact ranges lying between the extremes achieved at that time by three-sigma maximum performance and three-sigma minimum-performance vehicles. Of the 0.27 percent of the normal vehi-

cles that fall outside the three-sigma limits, approximately half would be short and half would be long. It is recognized that it may not be possible for a normally performing, fully guided vehicle to fly either the three-sigma maximum or minimum-performance trajectory as defined above. However, what is wanted is a single trajectory having an impact range at any time greater than the impact range of 99.865 percent of all normal vehicles, and a single trajectory with an impact range at any time less than the impact range of 99.865 percent of all normal vehicles. Any deviation outside of three-sigma limits indicates that the vehicle is probably behaving in an abnormal, though not necessarily dangerous, fashion. Those parameters having a significant effect upon impact range, such as thrust, specific impulse, weight, variation in firing times of different stages, and fuel flow rates, should be combined in the best considered fashion to produce the required results.

A1.2.4.2.1. Cruise Missiles and Remotely Piloted Vehicles. The three-sigma high performance trajectory should define the vehicle capability limits in climbing to maximum altitude at the maximum possible rate. It defines, at any time after launch, the limits of normality as far as impact range is concerned. The three-sigma high-performance trajectory provides the maximum downrange distance of the vacuum instantaneous impact point (IIP) for any given time. The three-sigma maximum and minimum-altitude trajectories define for any ground range the limits of normality as far as altitude is concerned. In other words, for any particular ground range approximately 99.73 percent of all normal vehicles (assuming a normal Gaussian distribution) will have altitudes between the extremes defined by three-sigma maximum altitude and three-sigma minimum-altitude trajectories. Any deviation outside these limits indicates that the vehicle is behaving in an abnormal, though not necessarily dangerous, fashion. However, the Mission Flight Control Officer (MFCO) may destroy such a vehicle if it is approaching land or threatening to get outside or below the command destruct coverage area.

A1.2.4.3. Three-Sigma Lateral Trajectory Requirements:

A1.2.4.3.1. Definition. Three-sigma lateral trajectories define the crossrange limits of normality for the vacuum instantaneous impact point (IIP). Both a three-sigma left and a three-sigma right trajectory shall be provided. These trajectories should be calculated using the worst lateral wind conditions for which a launch would be attempted. For any downrange distance, the IIP traces for 99.73 percent of all normal vehicles subjected to the assumed winds lie between the three-sigma lateral IIP traces. For variable azimuth launches, a three-sigma left trajectory for the smallest flight azimuth in the approved azimuth sector and a three-sigma right trajectory for the largest flight azimuth in the approved sector are required in addition to three-sigma lateral trajectories for a centrally located flight azimuth. Unless the procedure is invalid, the assumption will be made that the three-sigma left and right trajectories provided for the centrally located azimuth can be used to produce a reasonable approximation of the three-sigma left and right trajectories for other flight azimuths by reorienting the X and Y axis of the data. For example, if the three-sigma lateral trajectories have been computed for a central flight azimuth of 100 degrees, the three-sigma lateral trajectories for a 90-degrees flight azimuth will be determined simply by assuming that the X axis is 90 degrees instead of 100 degrees. If this assumption is not reasonable, additional trajectories shall be provided to define the extreme left and right lateral limits.

A1.2.4.3.2. Use. Three-sigma lateral trajectories are needed to determine whether a normal vehicle experiencing a three-sigma deviation will violate flight safety destruct criteria. They may also be used as guidelines by the MFCO in deciding whether a vehicle will be allowed to

continue in flight or to over fly land. When used for comparison with the impact predictor destruct criteria, the vacuum IIP data are required. When used on the present-position display, values of X, Y, Z along the three-sigma lateral trajectories are required. The three-sigma lateral trajectories, as defined in A1.2.4.2.1. in terms of IIP, may not provide three-sigma deviations of the lateral position Y as a function of X, although this is normally assumed to be the case. If this assumption is not valid, the Range User should also submit three-sigma trajectories that define the lateral limits of Y in terms of X.

A1.2.4.3.3. Calculation. In calculating a three-sigma lateral trajectory, those parameters having a significant effect on the lateral deviation of the IIP (or of the position Y in terms of X) should be combined in the best considered fashion to produce the required results. The procedures described in A1.2.4 and A1.2.4.1 for calculating three-sigma maximum and minimum-performance trajectories are also suggested here.

A1.2.4.3.4. Cruise Missiles and Remotely Piloted Vehicles. The three-sigma lateral trajectory defines the lateral limits within which 99.73 percent of all normal missiles are expected to remain. This trajectory should be calculated using the worst lateral wind condition for which a launching would be attempted. Since only one three-sigma lateral trajectory is requested, the assumption will be made that the three-sigma left and three-sigma right trajectories are symmetric about the nominal trajectory. If this assumption is not reasonable, then both three-sigma left and three-sigma right trajectories shall be provided. A missile that deviates outside the three-sigma lateral limits is subject to possible destruction if it is approaching land or threatening to get outside or below the command destruct coverage area.

A1.2.4.4. Dispersed Launch Area Trajectories. If the dispersed launch area trajectories are computed as specified and the proposed flight plan is approved, the launch agency can be certain that a normal vehicle will not violate the safety destruct criteria in the launch area, irrespective of the actual winds existing at launch. Unfortunately, there is also a distinct disadvantage in using extreme winds to calculate the dispersed trajectories. To arrive at destruct lines that will not be violated by vehicles flying the extreme trajectories, the allowances made for wind effects in the destruct line computations must be kept small. This, in turn, means that wind restrictions must be imposed on launch day. The wind profile used in the destruct calculations may be much smaller than the extreme wind profiles used to calculate the dispersed trajectories. In general, the greater the wind profile used in calculating the dispersed launch area trajectories, the steeper the trajectories are; and the steeper the dispersed trajectories, the more severe the Range Safety wind restriction must be on launch day to have acceptable destruct criteria. Reducing the wind profile in calculating the dispersed trajectories lessens the probability of a hold due to wind, but increases the probability that a normal vehicle will fly outside the limits defined by the dispersed trajectories. This, in turn, increases the probability that a normal vehicle will be destroyed. For those vehicle flights for which severe launch area wind restrictions are required, it may be necessary for the Range User to supply dispersed launch area trajectories for two or three different wind profiles. By so doing, the probability of a safety hold due to wind is thus reduced.

A1.2.4.4.1. Three-Sigma Steep Launch Area Trajectory. The three-sigma steep launch area trajectory should maximize Z as a function of X', where the azimuth of the X' axis must be specified by Range Safety for each program or group of similar flights. The positive X' axis is directed downrange from the launch point directly away from the uprange impact limit line so the negative X' axis intersects the impact limit line at right angles. In calculating this trajec-

tory a head wind (or tail wind) blowing toward (or away from) the impact limit line, that is, blowing from (or toward) the positive X' direction, normally is used. This wind profile should, but may not always, represent the worst conditions for which a launch would be attempted. Therefore, other wind azimuths may need to be examined for worst conditions depending on the particular vehicle's guidance system response to wind direction. If other perturbing factors such as gyro drift or high thrust add significantly to the uprange deviations caused by wind, these factors should also be included in the calculations. The steep launch area trajectory is a three-sigma trajectory in that, for any X' , the value of Z along the three-sigma steepest trajectory would be greater than the corresponding values of Z achieved by 99.865 percent of all normal missiles subjected to the assumed head wind.

A1.2.4.4.2. Three-Sigma Lateral Launch Area Trajectory. The three-sigma lateral launch area trajectory should maximize Z as a function of Y' , where the azimuth of the Y' axis must be specified by the Flight Safety Analysis Section for each program or group of similar flights. When looking down-range, the negative Y' axis is laterally directed to the right with respect to the intended flight line, the actual direction being perpendicular to the lateral impact limit line being protected. In calculating this trajectory, a lateral wind blowing toward (or away from) the impact limit line, that is, blowing from (or toward) the positive Y' direction normally is used. This wind profile should, but may not always, represent the worst conditions for which a launch would be attempted. Therefore, other wind azimuths may need to be examined for worst conditions depending on the particular vehicle's guidance system response to wind direction. Other perturbing factors that add significantly to the vehicle lateral movement, such as gyro drift, roll program error, and alignment errors, should also be included in the calculations. The lateral launch area trajectory is a three-sigma trajectory in that, for any Y' , the value of Z along the three-sigma lateral launch area trajectory would be greater than the corresponding values of Z achieved by 99.865 percent of all normal missiles subjected to the assumed lateral wind.

A1.2.4.5. Fuel-Exhaustion Trajectory. For many flights, a programmed thrust termination may be scheduled well in advance of fuel exhaustion. To know whether a potential safety problem can arise if the vehicle should fail to cut off, trajectory data through fuel exhaustion are needed. For ballistic missile flights, the information should be provided only for the last stage in accordance with assumptions mutually agreed to by the Range User and Range Safety. For orbital flights, the fuel exhaustion trajectory should be provided for the last suborbital stage. The requirement should be met by extending either the nominal or three-sigma maximum-performance trajectory through fuel exhaustion, depending on which produces a greater impact range.

A1.2.4.5.1. Cruise Missiles and Remotely Piloted Vehicles. In calculating this trajectory, a tail-wind profile should be used that represents the worst wind conditions for which a launching would be attempted. For any particular time after launch, approximately 99.73 percent of all normal vehicles (assuming a normal Gaussian distribution) will have impact ranges less than the range achieved at that time by a three-sigma high performance mission.

ATTACHMENT 2

MALFUNCTION TURN DATA

A2.1. Introduction. This attachment provides background information and details about Range Safety malfunction turn data requirements. It is applicable to ballistic, space, cruise, and remotely piloted vehicles. The turn data shall describe the turning capability of the vehicle velocity vector as a function of thrust vector offset or other parameters characterizing the turns. This information is used to determine how fast a vehicle or, more exactly, a vehicle impact point can deviate from the nominal if a malfunction occurs. Velocity vector turn data is required only for the thrusting periods from launch up to a point in flight where effective thrust of the final stage has terminated or to thrust termination of that stage or burn that places the vehicle in orbit.

A2.2. Turn Definitions:

A2.2.1. *Yaw turn* - the angle turned in the lateral direction by the total velocity vector. The *lateral plane* is defined as the plane normal to the vector generated by the cross-product of the unit vectors of the total velocity and the normal to the nominal trajectory plane, not the angle turned in the horizontal plane by the horizontal component.

A2.2.2. *Maximum turn capability* - the envelope of the maximum-rate trim and all tumble velocity vector turn angle curves for a given malfunction time, irrespective of how unlikely this rate is to occur.

A2.2.3. *Trim turn* - a turn resulting from a malfunction that causes the launch vehicle thrust moment to balance the aerodynamic moment while imparting a constant rotation rate to the vehicle longitudinal axis. The maximum-rate trim turn is the trim turn made at or near the greatest angle of attack that can be maintained while the aerodynamic moment is just balanced by the thrust moment, whether the vehicle is stable or unstable.

A2.2.4. *Tumble turn* - the family of tumble turns that results if the airframe rotates in an uncontrolled fashion at various angular rates, each rate being brought about by a different, constant value of the thrust vector offset angle or constant value of another parameter that defines the tumble turn.

A2.2.5. *90-degree option* - the turn produced by directing and maintaining the vehicle thrust at about 90 degrees to the velocity vector without regard for how this situation can be brought about.

A2.3. Malfunction Turn Computation Requirements:

A2.3.1. Turning information need be computed for the nominal or reference trajectory only.

A2.3.2. In the various velocity vector turn computations, it should be assumed that the vehicle performance is normal up to the point of the malfunction that produces the turn.

A2.3.3. The effects of gravity shall be omitted from the final turn data calculations.

A2.3.4. If pitch and yaw turn angles are essentially the same except for the effects of gravity, the yaw turn angles may be determined from pitch calculations that, in effect, have had the gravity component subtracted out at each step in the computations.

A2.3.5. During the first 100** seconds of flight both pitch and yaw turns shall be provided. After 100** seconds, turns need be computed only in the yaw plane. For each program, Range Safety provides the Range User with the specific value to use for each parameter marked with the double aster-

isks. **Exception:** During the first 100** seconds of flight, when neglecting gravity, if the pitch and yaw turns are the same, only the yaw turns are required.

The double asterisks used in this attachment mean the magnitude, interval, or duration for the required item varies from program to program. The value given is typical.

A2.3.6. Malfunction turn data are required for malfunctions initiated at even 4** second intervals beginning 4** seconds after first motion continuing for the first 100** seconds of flight or through the first-stage thrusting phase and into the second-stage phase for at least one time point, and at even 8** second intervals thereafter.

A2.3.7. One possible difficulty needs to be mentioned in connection with calculating tumble turns for aerodynamically unstable missiles. In the high aerodynamic region, it often turns out that no matter how small the initial deflection of the rocket engine, the airframe tumbles through 180 degrees or one-half cycle in less than the specified time period for which the calculations are to be carried out. In such a case, if the computation is carried out for the specified time period, part of the angle turned by the velocity vector during the first half cycle is then canceled out during the second half cycle of the turn. If only tumble turns were considered in such cases, the conclusion would be reached that the vehicle velocity vector can turn through a greater angle in a shorter time period than it can in a longer time period. This is an unacceptable conclusion from a safety viewpoint. The envelope of the family of tumble turns must rise continuously throughout the specified malfunction time period. One generally acceptable way to satisfy this requirement is to compute tumble turn angles without considering aerodynamic forces. Although such a vacuum turn cannot actually be simulated in the atmosphere by means of a constant engine deflection, in all likelihood there is some particular intelligent behavior of the engine that can approximate the turn fairly closely. If, however, vacuum tumble turns are considered unrealistic and unjustifiable, other types of malfunctions shall be considered.

A2.3.8. The turn data shall be defined for a series of malfunction modes such as thrust vector offset. Turn data computations shall include a credible distribution (range) of parameter values to demonstrate the variation of the turn characteristics caused by each malfunction mode. If the turns can occur as a function of more than one malfunction mode (for example, solid rocket motor (SRM) thrust vector offset angle for thrust vector control failures and thrust dissipation time for SRM nozzle burn through), turn data are required for each mode. Where possible, the same set of malfunction modes shall be used for each turn initiation time.

A2.4. Turn Trajectories. Although velocity vector turning computations are not required for the three-sigma maximum and three-sigma minimum performance trajectories, a method for applying the turn angles to these trajectories shall be provided. The trajectory data items of A1.2.2 shall also be applied for the trajectory used to start the turn computations, if this trajectory is not one of those provided in response to A1.2.1. Range Users should contact Range Safety regarding data format requirements. A columnar or block printout is acceptable. In addition, a complete discussion is required of assumptions made, methods of calculation, and equations used in deriving the malfunction turns.

A2.5. Determining Types of Turns to Submit. In determining the maximum turn capability of a vehicle, the usual procedure is for the Range User to consider both trim turns and tumble turns, in both the pitch and yaw planes. However, with Range Safety approval, the Range User may elect to calculate turn rates using the 90-degree option in lieu of trim and tumble turns. If the 90-degree option is ruled out, the

criteria for each of the vehicle conditions listed in A2.5.2 through A2.5.4 should be used to determine whether trim turns, tumble turns, or both should be provided at each turn initiation time.

A2.5.1. 90-Degree Option. In some cases, Range Safety may accept turning angles or rates computed on the basis of the 90-degree assumption even though it is extremely unlikely for the missile to achieve these turn rates. This option is usually quite disadvantageous to the Range User, since larger turning angles (higher turn rates) lead to more restrictive destruct criteria. Such unduly restrictive criteria could necessitate the revision of a proposed flight plan that may otherwise have been allowed or could result in somewhat earlier destruction of an erratic missile.

A2.5.2. Condition 1: For Vehicles Aerodynamically Unstable at All Angles of Attack. During that part of flight where the maximum trim angle of attack is small, it may be obvious that tumble turns lead to greater turning angles. If the maximum trim angle of attack is large, trim turns will in all probability lead to higher turning angles than tumble turns and to more restrictive destruct criteria.

A2.5.2.1. If the Range User can state that the probability of flying a trim turn even for a period of only a few seconds is virtually zero, only tumble turns are required.

A2.5.2.2. If the Range User cannot so state, a series of trim turns (that includes the maximum-rate trim turn) and the family of tumble turns shall be provided.

A2.5.3. Condition 2: For Vehicles Stable at All Angles of Attack:

A2.5.3.1. If the vehicle is so stable that the maximum thrust moment cannot produce tumbling, but produces a maximum-rate trim turn at some angle of attack less than 90 degrees, a series of trim turns that includes the maximum-rate trim turn shall be provided.

A2.5.3.2. If the maximum thrust moment results in a maximum-rate trim turn at some angle of attack greater than 90 degrees, a series of trim turns shall be provided only for angles of attack up to and including 90 degrees.

A2.5.4. Condition 3: For Vehicles Unstable at Low Angles of Attack but Stable at Some Higher Angle of Attack Region:

A2.5.4.1. If large engine deflections result in tumbling, whereas small engine deflections do not, a series of trim and tumble turns should be generated as prescribed in A2.5.2 for aerodynamically unstable missiles. The same difficulty discussed in A2.3.5 with tumble turns may arise here; namely, the envelope of the computed tumble turns may fail to rise continuously throughout the entire time period for which the calculations are to be carried out. In this event, either tumble-turn calculations neglecting aerodynamic forces or trim-turn calculations must be made as discussed in A2.5.2.

A2.5.4.2. If both large and small constant engine deflections result in tumbling, irrespective of how small the deflection might be, the turn data achieved at the stability angle of attack, assuming no upsetting thrust moment, are required in addition to the turn data achieved by a tumbling vehicle. This situation arises because the stability at high angles of attack is insufficient to arrest the angular velocity that is built up during the initial part of a tumble turn where the vehicle is unstable. Although the missile cannot arrive at this stability angle of attack as a result of the constant engine deflection, there is some deflection behavior that will produce this result. If arriving at such a deflection program is too difficult or too time consuming, it may be assumed that the vehicle somehow instantaneously rotated to the trim angle of attack and stabilizes at this point. If so, tum-

ble turn angles may be used in Range Safety destruct calculations during that part of flight for which the envelope rises continuously for the duration of the computation.

A2.6. Turn Duration. The malfunction turn data (turn angle and velocity magnitude curves) are to be provided at 1**second intervals, for at least 12** seconds into the turn and until one of the following two conditions are met. Various time intervals or time delays shall be considered, since the delays that are built into the Range Safety destruct calculations depend upon the accuracy, sensitivity, and type of presentation associated with a particular instrumentation system as well as missile characteristics.

A2.6.1. The vehicle reaches a critical loading condition that will cause breakup.

A2.6.2. The vehicle is tumbling so rapidly that the effective thrust acceleration is negligible; for example, the projected vacuum impact point is no longer moving significantly.

A2.7. Turn Data Format. Malfunction turn data shall be delivered in the form of graphs. Scale factors of plots shall be selected so the plotting and reading accuracies do not degrade the basic accuracy of the data. In addition, tabular listings of the data used to generate the graphs are required in ASCII format files on floppy or compact disks or other electronic media, with corresponding hard copies.

A2.7.1. Velocity Turn Angle Graphs. For turn angle graphs, the ordinate represents the total angle turned by the velocity vector in degrees; and the abscissa, the time duration of the turn in seconds.

A2.7.2. Velocity Magnitude Graphs. For velocity magnitude graphs, the ordinate represents the magnitude of the velocity vector in feet per second; and the abscissa, the time duration of the turn in seconds.

A2.8. Turn Data Items. The following data items are required for each malfunction initiation time. The information that describes the turn is required at intervals of 1 second or less.

A2.8.1. Velocity Turn Angle. One graph is required for each malfunction mode at each initiation time. For tumble turns, each graph is to include the envelope of all tumble turns for all possible constant thrust vector offset angles (or other parameter). In this case, plots of the individual tumble turn curves that are used to define the envelope are required on the same sheet with the envelope. For trim turns, a series of trim turn curves for representative values of thrust vector offset (or other parameter) is required. The series of trim turn curves shall include the maximum-rate trim turn.

A2.8.2. Velocity Magnitude. Either total velocity magnitude or incremental change in velocity magnitude from time of malfunction can be presented although the incremental change in the velocity is desired. For each thrust vector offset angle (or other parameter), the point on the velocity graph corresponding to the point of tangency on the tumble turn-angle envelope shall be indicated. For tumble turns, velocity magnitudes are required in graphical form as a function of time for each thrust vector offset (or other parameter) used to define the tumble turn envelope.

A2.8.3. Vehicle Orientation. If the vehicle has thrust augmenting rocket motors, then the vehicle attitude (in the form of the angular orientation of the vehicle longitudinal axis) as a function of time into the turn is required for each turn initiation time.

A2.8.4. Onset Conditions. The vehicle state at the beginning of the turn, including the thrust, weight, and state vector (including velocity magnitude) shall be provided for each set of curves.

A2.8.5. Breakup Information. The Range User shall specify if the vehicle will remain intact throughout the turn. If the vehicle will breakup during a turn, then the point (time) for which vehicle breakup is expected to occur shall be indicated. The time into the turn at which vehicle breakup would occur can be a specific value or a probability distribution for time to breakup.

A2.8.6. Probability of Occurrence. The distribution for the probability of occurrence for the value of the parameter defining the turns, such as thrust vector offset, shall be defined for each parameter (as a function of turn initiation time if the distribution varies with time). Also, information defining how the probability distribution was determined shall be provided.

A2.9. Velocity Vector Turn Data for Cruise Missiles and Remotely Piloted Vehicles:

A2.9.1. From launch or drop until cruise altitude is reached, this information is required to provide a means of determining the maximum angle through which the missile velocity vector can turn in the event of a malfunction. The maximum angles turned for time intervals up to about 30** seconds in duration are required. (The actual times will depend on the delays included in the FTS as well as other factors). Both pitch and yaw turns should be investigated and the larger presented. It should be assumed that the missile has followed the nominal trajectory up to the point of malfunction that produces the maximum-rate trim turn. Thereafter, it should be assumed that the missile is trimmed to the maximum air load that the structure can stand, or that the missile is flying out of control in an attitude that produces maximum lateral acceleration (for example, a near 90-degree bank with a maximum pitch turn). During the launch phase, the missile may not be able to fly for 30** seconds under these extreme conditions. In this event, it should be assumed that the missile is turning at the maximum rate for which these flight conditions can be maintained for required time duration. A complete discussion of the methods used in the calculations shall be provided. This discussion should include assumptions made, types of malfunctions considered, forces producing turns, equations used, and sample computations.

A2.9.2. During the cruise phase, the maximum turn capability of the velocity vector as a function of altitude is required. Rates should be based on normal missile weights and the expected cruising speeds at each altitude. For this phase of flight, the data may be expressed in the form of maximum lateral accelerations, if desired. A complete discussion similar to that requested for A2.9.1 is required. Also required is the maximum turn capability that the guidance system and the autopilot can command during the cruise phase.

A2.9.3. A cruise missile may be boosted from the launch pad by separable rockets or by a booster motor that is an integral part of the missile. While the booster motor is thrusting, the missile may perform more as a ballistic missile or space vehicle than as a cruise missile. In such cases, maximum turning capability data during the boost phase will be required as specified in A2.5 rather than as specified in A2.9.1. For each missile program, Range Safety shall indicate which procedures are to be used in computing malfunction turn data during the boost phase.

ATTACHMENT 3

FRAGMENT DATA

A3.1. Introduction. Fragment listings and characteristics for all potential modes of vehicle breakup are required. At a minimum, the following modes of vehicle breakup shall be considered: (1) breakup due to FTS activation, (2) breakup due to an explosion, and (3) breakup due to aerodynamic loads, inertial loads, and atmospheric reentry heating. Fragment data is required up to thrust termination of the last stage that carries a destruct system. All fragments shall be included; however, similar fragments can be accounted for in fragment groups.

A3.2. Describing Fragment Groups. A fragment group is one or more fragments whose characteristics are similar enough to allow all the fragments to be described by a single “average” set of characteristics. The following information is provided to aid in determining fragment groups:

A3.2.1. Fragment Type. All fragments shall be of the same type (for example solid propellant, explosive, or inert), including whether or not propellant fragments are burning following breakup.

A3.2.2. Ballistic Coefficient (beta). The maximum beta in the group should be no more than about a factor of 3 times the minimum (except for very low beta fragments where betas ranging from near 0 to about 3 pounds per square foot [lb/ft^2] can be grouped together).

A3.2.3. Weight. If the fragments contain propellant that is burning during free fall, the maximum weight of propellant in a fragment group should be no more than a factor of 1.2 times the minimum weight of propellant. The fragments included in a group should be such that the kinetic energies (KE) based on terminal velocity ($KE = 13 \times W \times \text{beta}$, foot pounds force $\{\text{ft}\cdot\text{lb}_f\}$ [The 13 has units of ft^3/lb_f]) are within the following guidelines:

A3.2.3.1. Fragments having $KE < 35$ are grouped.

A3.2.3.2. Fragments having $35 < KE < 100$ are grouped.

A3.2.3.3. Fragments having $100 < KE < 6,200$ should be grouped so that the maximum fragment KE is no more than about three times the minimum.

A3.2.3.4. Fragments having $6,200 < KE < 33,670$ should be grouped so that the maximum fragment KE is no more than about three times the minimum.

A3.2.3.5. Fragments having $33,670 < KE < 74,000$ should be grouped so that the maximum fragment KE is no more than about three times the minimum.

A3.2.3.6. Fragments having $74,000 < KE < 1,616,000$ should be grouped so that the maximum fragment KE is no more than about three times the minimum.

A3.2.3.7. Fragments having $KE > 1,616,000$ are grouped.

A3.2.4. Velocity Perturbation. The maximum expected destruct explosion or pressure rupture induced velocity in the group should be no more than a factor of 1.2 times the minimum induced velocity.

A3.2.5. Projected Area. For explosive fragments, the range of projected areas should be controlled by requiring that the maximum value of the weight of propellant at impact is no more than a factor of two

times the minimum; however, if the propellant is burning during free fall the factor is 1.2. There is no limit on the range of projected areas for inert fragments.

A3.3. Fragment Data Items. These requirements provide a description of the data items required for each fragment or fragment group for each potential mode of vehicle breakup. The variation of the fragment characteristics with flight time shall be defined. Normally this is accomplished by specifying multiple fragment lists, each of which is applicable over a specified period of flight.

A3.3.1. That fragment that, in the absence of winds, is expected to travel a maximum distance, and that fragment(s) that, in the absence of winds, is expected to travel a minimum distance shall be included.

A3.3.2. Fragment group name.

A3.3.3. Number of fragments.

A3.3.4. General description(s) of fragments such as part/component, shape, dimensions, figure.

A3.3.5. Breakup Altitude. For breakup due to atmospheric reentry, the altitude at which breakup is expected to occur shall be provided.

A3.3.6. Ballistic Coefficient (beta). Nominal, plus three-sigma, and minus three-sigma values (psf) for each fragment or group; including graphs of the coefficient of drag (C_d) versus Mach number for the nominal and three-sigma beta variations for each fragment or group. Each graph shall be labeled with the shape represented by the curve and reference area used to develop the curve. A C_d versus Mach curve for axial, transverse, and tumble orientations (when applicable) shall be provided for fragments not expected to stabilize during free-fall conditions. For fragments that may stabilize during free-fall, C_d versus Mach curves should be provided for the stability angle of attack. If the angle of attack where the fragment stabilizes is other than 0 degrees, both the coefficient of lift (C_L) versus Mach number and the C_d versus Mach number curves should be provided. If available, equations for C_d versus Mach curves should be provided. The difficulty of estimating drag coefficient curves and weights for vehicle pieces is fully realized. If this cannot be done satisfactorily, an estimate of the subsonic and supersonic $W/C_d A$ for each major piece may be provided instead. In either case, three-sigma tolerance limits shall be included for the drag coefficients for the maximum and minimum-distance pieces.

A3.3.7. Weight per Fragment. Include the possible three-sigma weight (pounds) variation for the fragment or group. The fragment data shall approximately add up to the total weight of inert material in the vehicle plus the weight of contained liquid propellants and solid propellant that is not consumed in the initial breakup and/or conflagration.

A3.3.8. Projected Area per Fragment (ft^2). Include the axial, transverse, and tumbling area for the fragment or group. This information is not required for those fragment groups classed as uncontained propellant fragments (as described below).

A3.3.9. Estimates of the maximum incremental velocities (feet/seconds) imparted to the vehicle pieces due to FTS activation, explosive and/or overpressure loads at breakup. The velocity is normally assumed to be Maxwellian distributed with the specified maximum value equal to the 97th percentile. If the distribution is known to be significantly different than the Maxwellian, the correct distribution is required, including if the specified value should be interpreted as a fixed value with no uncertainty.

A3.3.10. Fragment Group Type:

A3.3.10.1. Type 1 = inert fragments; for example, no volatile type material that could be burning or could explode.

A3.3.10.2. Type 2 = uncontained solid propellant fragments; for example, solid propellant exposed directly to the atmosphere and will not explode upon impact.

A3.3.10.3. Type 3 = contained propellant fragments; for example, propellant that is enclosed in a container, such as a motor case or pressure vessel, and will not explode upon impact.

A3.3.10.4. Type 4 = contained explosive propellant fragments; for example, propellant that is enclosed in a container, such as motor case or pressure vessel, and will explode upon impact.

A3.3.10.5. Type 5 = uncontained explosive solid propellant fragments; for example, solid propellant exposed directly to the atmosphere and will explode upon impact.

A3.3.11. Casualty Area per Fragment (ft^2). The casualty area per fragment shall be based on a fragment falling vertically at impact, and should reflect the credible fragment orientation giving the maximum projected area.

A3.3.12. Vehicle stage where fragment group originated.

A3.3.13. For those fragment groups defined as uncontained propellant fragments, contained propellant fragments, and explosive fragments, an indication as to whether or not the propellant fragments are burning during free fall.

A3.3.14. For those fragment groups defined as contained propellant fragments, explosive or non-explosive, the initial weight of contained propellant (pounds) and the consumption rate during free fall (pounds per second); the initial weight of the propellant in a contained propellant fragment is the weight of the propellant before and after the anomalous event.

A3.3.15. Diffusion and dispersion of any fragments containing toxic or radioactive materials and the radiation and exposure characteristics.

A3.4. Residual Thrust Dispersion. If an upper stage can be ignited as a result of FTS activation on a lower stage, sufficient information is required to evaluate the effects and duration of thrust, and the maximum deviation of the impact point that can be brought about by this thrust. The explosion effects on remaining fuels, pressurized tanks, and remaining stages are required, particularly with respect to ignition or detonation of upper stages if destruct action is taken during the burning period of a lower stage. For each thrusting or non-thrusting stage having residual thrust capability following FTS activation, provide either the total residual impulse (pounds-seconds) imparted after "arm" and "destruct," or the full-residual thrust (pounds-feet) versus time (s). Otherwise, a detailed analysis that clearly shows the stages are not capable of thrusting after FTS activation is required.

ATTACHMENT 4

JETTISONED BODY DATA

A4.1. General Data Requirements. The following data shall be provided for each jettisoned body:

A4.1.1. The nominal impact point. The nominal impact point (or aiming point) for each jettisoned body shall be given in terms of geodetic latitude and longitude in decimal degrees, and range (nautical miles) from the pad. Computations shall be made for an ellipsoidal rotating earth taking into account drag and, if applicable, lift.

A4.1.2. The number of fragments resulting from a specific scheduled jettison. If the jettisoned body is expected to break up during reentry, an estimate of the number of pieces, their approximate weights, cross-sectional areas, ballistic coefficients and their impact ranges are required.

A4.1.3. Jettison flight time (seconds), total weight (pounds) jettisoned and weight per fragment (pounds), reference area per fragment (ft^2), and the best estimate of C_d versus Mach number and subsonic and supersonic ballistic coefficient for each stage or piece. The C_d versus Mach number data are to be provided in graphical and tabular format for the nominal, minus three-sigma and plus three-sigma drag coefficients and shall cover the range of possible Mach numbers from 0 to the maximum values expected during free fall. Also indicate whether bodies are stable and, if so, at what angles of attack. For pieces that can possibly stabilize during free flight, drag coefficient curves shall be provided for the stability angle of attack. If the stability angle of attack is other than 0 degrees, both coefficient of lift (C_L) versus Mach number and C_d versus Mach number curves shall be provided. State briefly how drag curves were determined.

A4.1.4. The three-sigma uprange-downrange (nautical miles) and crossrange (nautical miles) impact dispersions and the azimuth orientation of the dispersion major axis (degrees clockwise from true North), assuming a normally functioning vehicle. Three-sigma wind effects acting upon the descending body or pieces shall be included in the dispersion area. A brief discussion of the method used to determine dispersions is also required. The magnitude of the wind contribution in the total dispersions is required.

A4.1.5. The resultant ballistic coefficient at time of debris impact.

A4.1.6. Maximum possible impact range of each impacting stage or reentry vehicle for a missile burning to fuel exhaustion.

A4.2. Reentry Vehicle Data. The items below are required as part of the trajectory or with general vehicle data:

A4.2.1. Type of reentry vehicle (RV) heat protection (ablation or heat sink); if ablation, provide ablation tables. The ablation table is a listing of Mach number or altitude versus the ratio W/W_0 , where W equals the instantaneous RV weight during reentry and W_0 equals the vehicle weight before ablation.

A4.2.2. The RV weight before ablation.

A4.2.3. A table of RV drag coefficient versus Mach number.

A4.2.4. A table of RV drag coefficient as a function of altitude.

A4.2.5. RV aerodynamic reference area associated with the drag coefficients.

A4.3. Small Unguided Rockets and Probe Vehicles. Three-sigma range and cross-range dispersions are required for each stage, separable fragment or component, and payload. Since the magnitude of these dispersions may determine whether a destruct system deviation equivalent level of safety certification or waiver will be granted or the extent to which shipping must be clear of impact areas, a careful analysis is essential.

A4.3.1. The following factors should be considered in determining three-sigma impact dispersions about predicted impact points:

- A4.3.1.1. Variation in thrust.
- A4.3.1.2. Error in drag estimates.
- A4.3.1.3. Thrust misalignment.
- A4.3.1.4. Fin and body misalignment.
- A4.3.1.5. Variation in weight.
- A4.3.1.6. Variation in ignition times of stages.
- A4.3.1.7. Impulse errors.
- A4.3.1.8. Tip-off and separation perturbations.
- A4.3.1.9. Errors in wind velocity measurements.
- A4.3.1.10. Errors in launcher setting.
- A4.3.1.11. Other significant perturbing influences, such as wind effects .

A4.3.2. The three-sigma variation in each factor shall be provided in tabular format in addition to the extent to which each factor displaces the impact point of each stage in the downrange and crossrange directions. Then, total impact dispersion is computed by a statistical combination of the individual displacements.

A4.3.3. A brief discussion of the assumptions made, method of analysis, and method of computation is required. The extent to which the three-sigma impact dispersion areas change with quadrant elevation angle is also required.