

NOT MEASUREMENT  
SENSITIVE

AFGS-87241A  
Amendment 1  
29 October 1990

**U. S. AIR FORCE GUIDE SPECIFICATION  
SIMULATORS, FLIGHT**

This amendment forms a part of AFGS-87241A,  
dated 9 January 1989, and is approved for use  
by the Department of the Air Force, and is available for use  
within the distribution limitations noted below.

PAGE 5

3.3.7, line 2: Insert a comma after the words normal and degraded.

PAGE 18

Table V, column 2: Delete "Shaft" and substitute "Shift".

PAGE 20

3.6.5.2, last line: Delete "g" and substitute "g-peak".

3.6.5.2.1, line 4: Delete "g" and substitute "g-peak".

PAGE 50

Table VII, column 1, item 3f: Delete "Phygoid" and substitute "Phugoid".

1 of 3

AMSC: N/A

FSC: 6930

**DISTRIBUTION STATEMENT D**

Distribution authorized to the Department of Defense and DoD contractors only; contains critical technology (3 February 1986). Other requests should be referred to ASD/ENES, Wright-Patterson AFB OH 45433-6503.

**AFGS-87241A  
Amendment 1**

PAGE 54

TABLE VII: Add the following notes after the table:

“NOTES:

1. Frequency response tests (controls cycled at discrete amplitudes and frequencies, phase angles and amplitude ratios measured from control position signature).
2. BOF – breakout force, GW – gross weight, PA – Power approach, DR – damping ratio, ROD – rate of descent, AOA – angle of attack, ROC – rate of climb.
3. Unless indicated, all engine tests performed with normal systems horsepower bleed/extraction.
4. N<sub>1</sub> – fan speed, N<sub>2</sub> – compressor speed, EPR – engine pressure ratio, TIT – turbine interstage temperature, TLA – throttle lever angle, W<sub>f</sub> – fuel flow.
5. The following power plant tolerances apply to steady state engine operation:

TLA	– one degree
W <sub>f</sub>	– 5% of 100 lb/hr
N <sub>1</sub> , N <sub>2</sub>	– 2% or 100 RPM
EPR	– 5%
TIT	– 5°C”

PAGE 55

TABLE VIII, column 1: Delete items 4f, g, and h and substitute:

- “f. Takeoff with engine failure at critical engine failure speed
- g. Minimum control speed for single engine operation
- h. Exercise abnormal/emergency procedures associated with takeoff and climb”

PAGE 183

3.6.2.5, REQUIREMENT LESSONS LEARNED, last column: Delete “Excursion” and substitute “Velocity”.

PAGE 211

3.6.5.2, last line: Delete “g” and substitute “g–peak and under 0.4 g–peak”.

3.6.5.2, REQUIREMENT LESSONS LEARNED, line 2: Delete “0.01 g” and substitute “0.010 g–peak”.

**AFGS-87241A**  
**Amendment 1**

PAGE 212

3.6.5.2.1, line 4: Delete "g" and substitute "g-peak and under 0.4 g-peak".

3.6.5.2.1, REQUIREMENT GUIDANCE: Delete "0.4 g" and substitute "0.4 g-peak".

Custodian:  
Air Force - 11

Preparing activity:  
Air Force - 11

Project No. 6930-F100